

## PRODUCT SPECIFICATIONS



### Main Unit

#### Type

Color Laser Multifunctional

#### Core Functions

Standard: Print, Copy, Scan, Send, Store  
Optional: Fax

#### Processor

Canon Dual Custom Processor (Shared)

#### Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

#### Memory

4.0 GB RAM

#### Hard Disk Drive

Standard: 250 GB  
Maximum: 1 TB

#### Mirroring Hard Disk Drive

Optional: (250 GB, 1 TB)  
Method: Raid1

#### Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)

#### Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

#### Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets  
Maximum: 6,350 Sheets

#### Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes,  
100-sheet Stack Bypass

Optional: Dual 550-sheet Paper Cassettes  
(CASSETTE FEEDING UNIT-AM1),  
2,450-sheet High-Capacity Paper  
Cassette (HIGH CAPACITY CASSETTE  
FEEDING UNIT-A1), 2,700-sheet Paper  
Deck (PAPER DECK UNIT-F1)

#### Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets  
Maximum: 3,450 Sheets  
(with External Finisher and Copy Tray)

#### Finishing Capabilities

Standard: Collate, Group  
With Inner Finisher: Collate, Group, Offset, Staple, Hole Punch,  
Staple-Free Staple, Staple On Demand  
With External Finishers: Collate, Group, Offset, Staple, Booklet, Hole  
Punch, Staple-Free Staple, Staple On Demand

#### Supported Media Types

Paper: Thin, Plain, Recycled, Color, Heavy,  
Cassettes: Pre-punched, Letterhead, Bond,  
(1/2): Transparency, Tab, Envelope

Stack Bypass: Thin, Plain, Recycled, Color, Heavy,  
Pre-punched, Labels, Letterhead,  
Bond, Coated, Transparency, Tab,  
Tracing,<sup>1</sup> Envelope

#### CASSETTE FEEDING UNIT-AM1

Thin, Plain, Recycled, Color, Heavy, Pre-punched,  
Letterhead, Bond, Transparency

#### HIGH CAPACITY CASSETTE FEEDING UNIT-A1

Thin, Plain, Recycled, Color, Heavy, Pre-punched,  
Letterhead, Bond

#### PAPER DECK UNIT-F1

Thin, Plain, Recycled, Color, Heavy, Pre-punched,  
Letterhead, Bond

#### Supported Media Sizes

Paper: Letter, Executive, Statement-R, Envelope  
Cassette 1: [No.10 (COM10), DL, ISO-C5], Custom Size  
(3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")

Paper: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
Cassette 2: Executive, Statement-R, Envelope [No.10  
(COM10), Monarch, DL, ISO-C5], Custom  
Size (3-7/8" x 7-1/8" to 12" x 18")

Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
Executive, Statement, Statement-R,  
Envelope [No.10 (COM10), Monarch,  
DL, ISO-C5], Envelope Custom Size  
(3-7/8" x 3-7/8" to 12-5/8" x 18"),  
Custom Size (3-7/8" x 5-1/2" to  
12-5/8" x 18"), Free Size (3-7/8" x 5-1/2"  
to 12-5/8" x 18")

## CASSETTE FEEDING UNIT-AM1

12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (3-7/8" x 7-1/8" to 12" x 18")  
HIGH CAPACITY CASSETTE FEEDING UNIT-A1: Letter  
PAPER DECK UNIT-F1: Letter

### Supported Media Weights

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)  
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

### Warm-up Time

From Power On: 30 Seconds

From Sleep Mode: 10 Seconds

Quick Startup Mode: 4 Seconds<sup>2</sup>

### Dimensions (W x D x H)

24-3/8" x 29-1/4" x 37-3/8" (620 mm x 742 mm x 950 mm)<sup>3</sup>

### Installation Space (W x D)

Basic: Stack Bypass + Cassette drawers open:  
37-1/8" x 46-3/8" (943 mm x 1,176 mm)<sup>3</sup>

### Weight

Approx. 313.1 lb. (142 kg)<sup>4</sup>

## Print Specifications

### Print Speed

iR ADV C5560i: Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")

iR ADV C5550i: Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")

iR ADV C5540i: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")

iR ADV C5535i: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

### Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

### Standard Page Description Languages

UFR II, PCL<sup>®</sup>6, Adobe<sup>®</sup> PS<sup>®</sup> 3

### Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access<sup>5</sup>

### Supported File Types

PDF, TIFF, JPEG, EPS,<sup>6</sup> XPS

### Printing from Mobile and Cloud

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),<sup>7</sup> Barcode Fonts<sup>8</sup>

PS fonts: 136 Roman

### Operating System<sup>9</sup>

UFR II: Server 2003/Server 2003 R2/Windows Vista<sup>®</sup>/Server 2008/Windows<sup>®</sup> 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later)

PCL: Server 2003/Server 2003 R2/Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10

PS: Server 2003/Server 2003 R2/Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later)

### Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction, Poster Printing

## Copy Specifications

### Copy Speed

iR ADV C5560i: Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")

iR ADV C5550i: Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")

iR ADV C5540i: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")

iR ADV C5535i: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

### First-Copy-Out Time (Letter)

iR ADV C5560i: As fast as 2.9 seconds (BW)/4.5 seconds (Color)

iR ADV C5550i: As fast as 3.5 seconds (BW)/5.2 seconds (Color)

iR ADV C5540i: As fast as 4.1 seconds (BW)/6.1 seconds (Color)

iR ADV C5535i: As fast as 4.9 seconds (BW)/7.4 seconds (Color)

### Copy Resolution

Reading: 600 dpi x 600 dpi

Printing: 1200 dpi x 1200 dpi

### Multiple Copies

Up to 9,999 copies

### Copy Exposure

Automatic or Manual (9 Levels)

### Magnification

25%-400% (1% Increments)

### Preset Reductions

25%, 50%, 64%, 73%, 78%

### Preset Enlargements

121%, 129%, 200%, 400%

### Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

### Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size Original, Color Balance, Adjust One-Touch Color, Area Designation

## Scan Specifications

### Type

Color Platen and Single-pass Duplexing Automatic Document Feeder

### Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

### Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m<sup>2</sup>)

CL Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m<sup>2</sup>)

### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

### Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows Vista/7/8/8.1/10

Windows Server 2003/Server 2003 R2/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2

### Scan Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

### Scan Speed (Letter)

Single-sided Scanning (BW):

80 ipm (300 dpi)/80 ipm (600 dpi)

Single-sided Scanning (Color):

80 ipm (300 dpi)/60 ipm (600 dpi)

Double-sided Scanning (BW):

160 ipm (300 dpi)/150 ipm (600 dpi)

Double-sided Scanning (Color):

160 ipm (300 dpi)/80 ipm (600 dpi)

## Send Specifications

### Destination

E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

### Color Mode

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

### Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

### Send Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

### Communication Protocol

File: FTP, SMB, WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

### File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b), XPS (Compact, Searchable), Office Open XML (PowerPoint<sup>®</sup>, Word)

Optional: PDF (Trace & Smooth, Encrypted), PDF/XPS (Digital Signature)

### Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

## Fax Specifications

### Maximum Number of Connection Lines

4

### Modem Speed

Super G3: 33.6 kbps

G3: 14.4 kbps

### Compression Method

MH, MR, MMR, JBIG

### Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

### Sending/Recording Size

Statement-R to 11" x 17"

### Fax Memory

Up to 30,000 pages

### Speed Dials

Max. 200

### Group Dials/Destinations

Max. 199 dials

### Sequential Broadcast

Max. 256 addresses

### Memory Backup

Yes

### Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

## Store Specifications

### Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows Vista/7/8/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)

Approx. 480 GB (1 TB HDD)

### Advanced Box Features:

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

### Memory Media

Standard: USB

## Security Specifications

### Authentication

Standard: Universal Login Manager, User Authentication, Department ID Authentication, (Device and Function Level Log-in), Access Management System

Optional: uniFLOW

### Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated)

Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

### Document

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration

Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80 % RH (no condensation)

### Power Requirements

C5560i/C5550i: 120-127V AC 60 Hz, 11.5 A

C5540i/C5535i: 120-127V AC, 60 Hz, 10 A

### Plug (Main Unit)

C5560i/C5550i: NEMA 5-20P

C5540i/C5535i: NEMA 5-15P

### Power Consumption

Maximum: Approx. 1.8 kWh

Standby: Approx. 66.2 W

Sleep Mode: Approx. 0.8 W<sup>10</sup>

Typical Electricity Consumption (TEC) Rating:

3.2 kWh (iR ADV C5560i)

2.5 kWh (iR ADV C5550i)

2.0 kWh (iR ADV C5540i)

1.6 kWh (iR ADV C5535i)

### Standards

ENERGY STAR® Certified

Rated EPEAT® Gold<sup>11</sup>

EU RoHS Compliant

Ecomark

Blue Angel

## Consumables

### Toner

GPR-55 Toner<sup>12</sup>

### Toner Yield (Estimated @ 6% Coverage)

Black: 69,000 Images

Color (C,M,Y):<sup>12</sup> 60,000 Images

## Fiery Print Controller Specifications (Optional)

### ColorPASS-GX500 (External)

#### System

Fiery FS200 Pro

#### Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

#### Standard Page Description Languages

Adobe PS 3, PCL5 (Driverless)

#### Memory

4 GB

#### Hard Disk Drive

1 TB

#### Processor

Intel Core i5-4570S 2.9 GHz up to 3.6 GHz w/Turbo

#### Fonts

PS: 138 Adobe PS Fonts

PCL: 113 PCL Fonts

#### Supported Operating Systems

Windows Vista (32 and 64 bit)/Windows 7 (32 and 64 bit)/Windows 8 (32 and 64 bit)/Windows 8.1 (32 and 64 bit)/Windows 10 (32 and 64 bit)/Windows Server 2008 (32 and 64 bit)/Windows Server 2008 R2 (64 bit only)/Windows Server 2012 (64bit only)/Windows Server 2012 R2 (64bit only)/MAC OS (10.7, 10.8, 10.9, 10.10, 10.11)

#### Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 6 (Front x 2, Rear x 4), USB2.0 x 2 (Front x 2)

#### Network Protocols

TCP/IP (LPR/Port 9100/SNMP/IPP/HTTP/HTTPS/FTP/SMB)/DNS

#### Direct Print

PDF1.7(APPE3), EPS, TIFF6, JDF1.4/JMF

#### VDP

FreeForm2.1, PDF/VT-2, PPML3, VPS

#### Fiery Print Controller Standard Features

FIERY HOT FOLDERS/Virtual Printers/Unity Display (Monitor required)/FIERY JDF/FIERY COMMAND WORKSTATION 5/Paper Catalog/FIERY SPOT-ON/FIERY REMOTE SCAN

#### Fiery Print Controller Options

FIERY IMPOSE, FIERY COMPOSE, FIERY IMPOSE AND COMPOSE, Graphic Arts Package Premium Web Activate/Removable HDD Kit-BI/Integration Interface and Stand (19" display, keyboard and mouse)

#### Dimensions (W x D x H)

8-1/2" x 19" x 19-1/8" (215 mm x 483 mm x 485 mm)

### imagePASS-P1 (Embedded)

#### System

Fiery FS200

#### Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

#### Standard Page Description Languages

PCL6, Adobe PS 3

#### Memory

2 GB

#### Hard Disk Drive

500 GB

#### Processor

Intel Celeron G1820 2.7 GHz

#### Fonts

PS: 138 Adobe PS Fonts

PCL: 113 PCL Fonts

#### Supported Operating Systems

Windows Vista (32 and 64 bit)/Windows 8 (32 and 64 bit)/Windows 8.1 (32 and 64 bit)/Windows 7 (32 and 64 bit)/Windows Server 2008 (32 and 64 bit)/Windows Server 2008 R2 (64 bit only)/Windows Server 2012 (64 bit only)/Windows Server 2012 R2 (64 bit only)/MAC OS (10.7 or higher)

## Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T),  
USB x 3.0 x 2 (Rear x 2), USB x 2.0 x 4 (Rear x 4)

## Network Protocols

TCP/IP (LPR/Port 9100/IPP/SMB/FTP)/DNS

## Fiery Print Controller Features

FIERY COMMAND WORKSTATION 5, PAPER CATALOG,  
FIERY SPOT ON, FIERY REMOTE SCAN

## Fiery Print Controller Options

FIERY IMPOSE, FIERY COMPOSE, FIERY IMPOSE AND  
COMPOSE, Productivity package Web activate (Includes  
Fiery JDF), Hot Folders License

## Dimensions (W x D x H)

11-1/4" x 3-5/8" x 11-5/8" (285 mm x 93 mm x 295 mm)

## Paper Supply Options

### CASSETTE FEEDING UNIT-AM1

Paper 550 Sheets x 2 Cassettes  
Capacity: [20 lb. Bond (80 g/m<sup>2</sup>)]  
Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
Executive, Statement-R, and Custom Size  
[3-7/8" x 7-1/8" to 12" x 18"  
(98.0 x 182.0 to 304.8 x 457.2 mm)]  
Paper Weight: 14 lb. Bond to 140 lb. Index  
(52 to 256 g/m<sup>2</sup>)  
Power Source: From the Main Unit  
Dimensions 24-3/8" x 27-5/8" x 9-7/8"  
(W x D x H): (620 mm x 700 mm x 251 mm)  
Weight: Approx. 49.6 lb. (22.5 kg)

### HIGH-CAPACITY CASSETTE FEEDING UNIT-A1

Paper 2,450 sheets [20 lb. Bond (80 g/m<sup>2</sup>)]  
Capacity:  
Paper Size: Letter  
Paper Weight: 14 lb. Bond to 140 lb. Index  
(52 to 256 g/m<sup>2</sup>)  
Power Source: From the Main Unit  
Dimensions 24-3/8" x 27-5/8" x 9-7/8"  
(W x D x H): (620 mm x 700 mm x 251 mm)  
Weight: 66.1 lb. (30 kg)

### PAPER DECK UNIT-F1

Paper 2,700 Sheets [20 lb. Bond (80 g/m<sup>2</sup>)]  
Capacity:  
Paper Size: Letter  
Paper Weight: 14 lb. Bond to 140 lb. Index  
(52 to 256 g/m<sup>2</sup>)  
Power Source: From the Main Unit  
Dimensions 15-3/4" x 24-7/8" x 17-3/8"  
(W x D x H): (400 mm x 630 mm x 440 mm)  
Weight: 68.3 lb. (31 kg)

## Output Options

### INNER 2-WAY TRAY-J1

Number of Trays: 2  
Total Output Capacity: Upper Tray: 100 Sheets  
Lower Tray: 250 Sheets  
Paper Weight: 14 lb. Bond to 110 lb. Cover  
(52 to 300 g/m<sup>2</sup>)  
Paper Size: Standard size: 12" x 18", 11" x 17", Legal,  
Letter, Letter-R, Executive, Statement,  
Statement-R, Envelope [No.10 (COM10),  
Monarch, DL, ISO-C5], Envelope Custom Size  
(3-7/8" x 3-7/8" to 12-5/8" x 18")  
Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")  
Dimensions (W x D x H): 16-7/8" x 16" x 3"  
(427 mm x 407 mm x 76 mm)  
Weight: Approx. 1.3 lb (0.6 kg)

### INNER FINISHER-H1

Number of Trays: 2  
Top Tray Capacity: Letter/Statement/Statement-R/  
Executive (45 Sheets), 12" x 18"/11" x 17"/  
Legal/Letter-R (45 Sheets)  
Lower Tray Capacity: Letter/Statement/Statement-R/  
Executive (500 Sheets), 12" x 18"/11" x 17"/  
Legal/Letter-R (250 Sheets)  
Paper Weight: 14 lb. Bond to 110 lb. Index  
(52 to 300 g/m<sup>2</sup>)  
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Cover  
(52 to 256 g/m<sup>2</sup>)  
Staple Position: Corner, Double  
Staple Capacity  
Corner Staple and Double Staple  
Letter/  
Executive: 50 Sheets (14 to 24 lb. Bond )  
11" x 17"/  
Legal/  
Letter-R: 30 Sheets (14 to 24 lb. Bond )  
Staple-Free Staple  
11"x17"/  
Letter: 5 Sheets (14 to 17 lb. Bond)  
4 Sheets (17.3 to 21.7 lb. Bond)  
3 Sheets (21.7 to 28 lb. Bond)

Staple On Demand: 40 Sheets [20 lb. Bond (80 g/m<sup>2</sup>)]  
Power Source: From the Main Unit  
Dimensions 29-1/4" x 29-1/4" x 8-7/8"  
(W x D x H): (743 mm x 742 mm x 225 mm)  
Weight: Approx. 19 lb (8.6 kg)

### STAPLE FINISHER-Y1 (External)

Number of Trays: 2  
Top Tray Capacity: Letter/Executive/Statement/  
Statement-R (3,000 Sheets), 12" x 18"/11"  
x 17"/Legal/Letter-R (1,500 Sheets)  
Lower Tray Capacity: Letter/Executive/Statement/  
Statement-R (250 Sheets), 12" x 18"/11"  
x 17"/Legal/Letter-R (125 Sheets)  
Paper Weight  
Top Tray: 14 lb. Bond to 140 lb. Index  
(52 to 256 g/m<sup>2</sup>)  
Lower Tray: 14 lb. Bond to 110 lb. Cover  
(52 to 300 g/m<sup>2</sup>)  
Staple Position: Corner, Double  
Staple Capacity  
Corner Staple and Double Staple  
Letter/  
Executive: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
11" x 17"/  
Legal/  
Letter-R: 30 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Staple-Free Staple:  
11"x17"/  
Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m<sup>2</sup>)  
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m<sup>2</sup>)]  
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m<sup>2</sup>)]

Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Power Source: From the Main Unit  
Dimensions 25-1/8" x 24-1/2" x 45"  
(W x D x H): (637 mm x 623 mm x 1142 mm)  
Weight: Approx. 68.3 lb (31 kg)

### BOOKLET FINISHER-Y1 (External)

Number of Trays: 3  
Top Tray Capacity: Letter/Executive/Statement/  
Statement-R (3,000 Sheets),  
12" x 18"/11" x 17"/Legal/Letter-R  
(1,500 Sheets)  
Lower Tray Capacity: Letter/Executive/Statement/  
Statement-R (250 Sheets),  
12" x 18"/11" x 17"/Legal/Letter-R  
(125 Sheets)  
Paper Weight  
Top Tray: 14 lb. Bond to 140 lb. Index  
(52 to 256 g/m<sup>2</sup>)  
Lower Tray: 14 lb. Bond to 110 lb. Cover  
(52 to 300 g/m<sup>2</sup>)  
Staple Position: Corner, Double  
Staple Capacity  
Corner Staple and Double Staple  
Letter/  
Executive: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
11" x 17"/  
Legal/  
Letter-R: 30 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Staple-Free Staple  
11"x17"/  
Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m<sup>2</sup>)  
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m<sup>2</sup>)]  
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m<sup>2</sup>)]

Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Booklet-Stitch Paper Size: 12" x 18", 11" x 17", Legal, Letter-R,  
Custom Size [7-3/4" x 10-5/8" to 12" x 18"  
(195 mm x 270 mm to 304.8 mm x 457.2 mm)]  
Booklet-Stitch Staple Capacity: 20 Sheets x 10 Sets [22 lb. Bond (81 g/m<sup>2</sup>)  
(including one cover sheet up to 140 lb.)]  
Index (256 g/m<sup>2</sup>)  
Power Source: From the Main Unit/85.6 W  
Dimensions 25-1/8" x 24-1/2" x 45"  
(W x D x H): (637 mm x 623 mm x 1142 mm)  
Weight: Approx. 125.7 lb (57 kg)

### INNER 2/3-HOLE PUNCHER-B1

(Requires the INNER FINISHER-H1)

Acceptable Punch Paper 14 lb. Bond to 110 lb. Cover  
(52 to 300 g/m<sup>2</sup>)  
Weight:

Acceptable Punch Paper Size  
Two Holes: 11" x 17", Legal, Letter, Letter-R, Executive  
Three Holes: 11" x 17", Letter, Executive  
Power Source: From the Main Unit

### 2/3-HOLE PUNCHER-A1

(Requires either the STAPLE FINISHER-Y1 or  
BOOKLET FINISHER-Y1)

Acceptable Punch Paper 14 lb. Bond to 110 lb. Cover  
(52 to 300 g/m<sup>2</sup>)  
Weight: (52 to 300 g/m<sup>2</sup>)  
Acceptable Punch Paper Size  
Two holes: 11" x 17", Legal, Letter, Letter-R, Executive  
Three holes: 11" x 17", Letter, Executive  
Power Source: From the Main Unit

## Hardware Options

### Card Readers

MiCARD PLUS PROXIMITY CARD READER  
COPY CARD READER-F1  
COPY CARD READER ATTACHMENT-B5

### Others

CABINET TYPE-N  
BUFFER PASS UNIT-L1  
COPY TRAY-J2  
UTILITY TRAY-B1  
PLATEN COVER TYPE W  
PRINTER COVER-J1  
TAB FEEDING ATTACHMENT-F1  
USB KEYBOARD

## Security Options

### Document Security

DOCUMENT SCAN LOCK KIT-B1  
SECURE WATERMARK-B1  
ENCRYPTED SECURE PRINT SOFTWARE-D1  
iR-ADV SECURITY KIT-P1 FOR IEEE 2600.1 COMMON  
CRITERIA CERTIFICATION<sup>13</sup>

### Data Security

HDD MIRRORING KIT-J1  
2.5"/250 GB HDD-N1  
2.5"/1 TB HDD-P1  
REMOVABLE HDD KIT-AL1

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1

### Barcode Printing

BARCODE PRINTING KIT-D1

### EFI-Fiery Based Controller

imagePASS-P1  
ColorPASS-GX500  
REMOVABLE HARD DISK DRIVE KIT-B1  
FIERY IMPOSE  
FIERY COMPOSE  
FIERY IMPOSE AND COMPOSE

### System Accessories

COPY CONTROL INTERFACE KIT-A1  
CONNECTION KIT-A1 FOR BLUETOOTH LE  
NFC KIT-C1  
MEAP WEB CONNECTION KIT-G3

### Fax Accessories

SUPER G3 FAX BOARD-AS1  
SUPER G3 2ND LINE FAX BOARD-AS1  
SUPER G3 3RD/4TH LINE FAX BOARD-AS1  
REMOTE FAX KIT-A1  
IP FAX EXPANSION KIT-B1

## Other Options

### Accessibility Accessories

ADF ACCESS HANDLE-A1  
VOICE GUIDANCE KIT-G1  
VOICE OPERATION KIT-D1  
BRAILLE LABEL KIT-F1

### Staples

STAPLE-P1<sup>14</sup>  
STAPLE CARTRIDGE-Y1<sup>15</sup>

## Footnotes

- <sup>1</sup> Some types of tracing paper cannot be used.  
<sup>2</sup> Time from device power-on to when copy jobs can be programmed.  
<sup>3</sup> Includes main unit and either Cassette Feeding Unit-AM1, High Capacity Cassette Feeding Unit-A1, or Cabinet Type-N.  
<sup>4</sup> Includes main unit, consumables, and Cassette Feeding Unit-AM1.  
<sup>5</sup> PDF print from Web sites is supported.  
<sup>6</sup> EPS can be printed directly only from the Remote User Interface.  
<sup>7</sup> Requires the optional PCL International Font Set-A1.  
<sup>8</sup> Requires the optional Barcode Printer Kit-D1.  
<sup>9</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.  
<sup>10</sup> 0.8 W sleep mode not available in all circumstances due to certain settings.  
<sup>11</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit [www.epeat.net](http://www.epeat.net).  
<sup>12</sup> GPR-55L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images.  
<sup>13</sup> Will launch at a later date.  
<sup>14</sup> Used for corner/double stapling only. 2 cartridges per case. 5,000 staples per cartridge.  
<sup>15</sup> Used for booklet finishing only. 3 cartridges per case. 2,000 staples per cartridge.

## Utilize the imageRUNNER ADVANCE to its full potential with professional services from Canon Solutions America

When selecting and implementing new technology, a highly skilled technical team is the difference-maker for a successful deployment. Canon Solutions America has the team of experts you need to help you acquire the right technology, solutions, and services for your organization. Our team of technical professionals draws upon decades of technical expertise and real-world experience to ensure you obtain the maximum benefit from your technology investment.

For more information, call or visit  
1.800.815.4000 CSA.CANON.COM



**Canon**  
CANON SOLUTIONS AMERICA

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. AirPrint and the AirPrint logo are trademarks of Apple Inc. Adobe® and PostScript® 3™ are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft® and PowerPoint® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. PCL® is a registered trademark of Hewlett-Packard Company. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2016 Canon U.S.A., Inc. All rights reserved.

CSA/7-16-263  
0716-CSAIRA55xxSSS-PDF-IH

