

C2230 C2225

Product Specifications



Main Unit

System Type

Color Digital Multifunction Imaging System

Functions

Standard: Copy, Print (UFR II), Scan, Send
Optional: Print (PCL, Adobe® PostScript® 3™), Fax (Up to 2 Lines)

Operation Panel

7" WVGA Full-Color TFT Screen

Memory

Standard: 2GB RAM
Maximum: 2GB RAM

Hard Disk Drive

Standard: 80GB
Maximum: 80GB

Network Interface Connection

Standard: 1000Base-T/100Base-TX/10Base-T
Optional: Wireless LAN (IEEE 803.1x via third-party adapter)

Other Interface

Standard: USB 2.0 (Host) x 2, USB 2.0 (Device)
Optional: Device Port [USB 2.0 (Host) x 2], Copy Control Interface

Copy/Print Speed (BW/Color)

Letter: C2230: Up to 30/30 ppm
C2225: Up to 25/25 ppm
Legal/ 11" x 17": Up to 15 ppm

First-Copy-Out Time (Letter)

BW: 5.9 Seconds, Color: 8.9 Seconds

Paper Sources (20 lb. Bond)

Standard: One 520-sheet Paper Cassette
One 550-sheet Paper Cassette
100-sheet Stack Bypass
Optional: Dual 550-sheet Paper Cassettes
Maximum: 2,270 Sheets

Output Paper Capacity (20 lb. Bond)

Standard: 250 Sheets (Inner Tray)
Maximum: 3,000 Sheets (w/Staple Finisher)

Output Paper Sizes

Cassette 1: 11" x 17", Letter, Executive
Cassettes 2/3/4: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Executive, Custom Size (5-1/2" x 7-1/8" to 12" x 15-3/8")
Bypass: 12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

Paper Deck:

N/A
Other: Envelope Feeder Attachment (COM10 No.10, Monarch, DL, ISO-C5)*

Acceptable Paper Weights

Cassette 1: 17 lb. Bond to 32 lb. Bond (64 to 120g/m²)
Cassettes 2/3/4: 17 lb. Bond to 60 lb. Cover (64 to 163g/m²)
Bypass: 17 lb. Bond to 80 lb. Cover (64 to 220g/m²)

Duplexing

Paper Size: Standard Automatic Trayless Duplexing (Executive to 12" x 18")

Paper Weights: 17 lb. Bond to 32 lb. Bond (120g/m²)

Special Media Support

Tracing, Coated, Labels, Transparency, and Envelopes

Warm-up Time

From Power On: 34 Seconds
From Sleep: 10 Seconds

Quick Startup

Mode: Within 7 Seconds**

Power Requirements/Plug

120V AC, 60Hz, 7.5A/NEMA 5-15P

Power Consumption

Maximum: 1.5kW
Sleep Mode: 0.8W

Dimensions (H x W x D)

36-1/2" x 22-1/4" x 26-3/4" (928mm x 565mm x 680mm)

Installation Space (W x D)

33-3/8" x 26-3/4" (846mm x 680mm)
(when the Multi-purpose Tray is extended.)

Weight

Approx. 198 lb. (90kg)*

Toner (Estimated Yield @ 5% Coverage)

Black: 23,000 Images, Color (C,M,Y): 19,000 Images

Image Reader Unit

Scan Resolution

Up to 600 x 600 dpi

Acceptable Originals (Glass)

Sheet, Book, 3-Dimensional objects [up to 4.4 lb. (2kg)]

Maximum Original Size

Up to 11" x 17"

Document Feeder

Scan Method

Duplex Automatic Document Feeder

Acceptable Originals

Paper Sizes: 11" x 17", Legal, Letter, Letter-R, Statement, or Statement-R

Paper Weights: 1-sided scanning: 11 lb. Bond to 34 lb. Bond (42 to 128g/m²)
2-sided scanning: 13 lb. Bond to 34 lb. Bond (50 to 128g/m²)

Scan Speed (BW/Color; Letter)

Simplex: Up to 51/51 ipm (300 dpi)
Up to 30/30 ipm (600 dpi)
Duplex: Up to 19/19 ipm (300 dpi)
Up to 13/13 ipm (600 dpi)

Paper Capacity (20 lb. Bond)

50 Sheets

Main Unit (continued)

Copy Specifications

Multiple Copies

1 to 999

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25% - 400% (1% Increments) from Platen Glass
25% - 200% (1% Increments) from Document Feeder

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset R/E Ratios by Area, Finishing, Two-Sided, Exposure Adjustment, Original Type Selection, Interrupt Mode, Sample Set, Setting Confirmation/Cancel, Standard Keys, Reset, Guide Display, Job Duration Display, Reserved Copying

Special Copy Features

Two-page Separation, Cover/Sheet Insertion, Booklet, Transparency Interleaving, Shift, Margin, Frame Erase, Image Combination, Different Size Original, Job Build, Job Done Notice, Scan Image Check, Mode Memory, Recall, Negative/Positive Inversion, Image Repeat, Mirror Image, Sharpness, Secure Watermark, Page Numbering, Copy Set Numbering, Watermark and Date

Print Specifications

Processor

Canon Dual Custom Processor (Shared)

Memory

Standard: 2GB RAM
Maximum: 2GB RAM

Hard Disk Drive

Standard: 80GB
Maximum: 80GB

Engine Resolution

1200 x 1200 dpi

PDL Support

Standard: UFR II
Optional: PCL 5c, PCL 6, Adobe PS 3

Print Driver Supported OS

UFR II, Adobe PS 3:
Windows® (Windows 2000/XP/Server 2003/Server 2008/
Windows Vista®/Windows 7), Citrix MetaFrame, Macintosh®
(OS X 10.2.8 or later)
PCL 5c/6:
Windows (Windows 2000/XP/Server 2003/Server 2008/
Windows Vista/Windows 7), Citrix MetaFrame

Direct Print Support

Standard: TIFF, JPEG
Optional: PDF, EPS¹⁾, XPS¹⁾

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Black-and-White Printing, Objective, Color/Black-and-White Auto Detect, Toner Reduction, Poster Printing

Scan Specifications

Network TWAIN Scan

Standard

Network Scan Utility

Color Network ScanGear

Universal Send Specifications

Sending Method

E-Mail, I-Fax, File Server (FTP, SMB, WebDAV), Super G3 Fax (Optional)

Color Mode

Auto Color Select (Color, Gray), Auto Color Select (Color, Black), Full Color, Grayscale, BW

Scan Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

Address Book Capacity

Max. 1,800 Destinations (Incl. 200 One-Touch Buttons)

Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), WebDAV
E-mail/I-Fax: SMTP, POP3, I-FAX (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF, PDF (Compact), PDF (Apply Policy), PDF (Optimize for Web), PDF/XPS (OCR), PDF/A-1b, XPS, XPS (Compact), OOXML (OCR) (.pptx)
Optional: PDF (Trace & Smooth), PDF (Encrypted), PDF/XPS (Digital Signature), PDF (Reader Extensions)

I-Fax Data Format

Color: TIFF (MH, MR, MMR)
BW: TIFF (MH, MR, MMR)

Universal Send Features

Two-Sided Original, Different-size Originals, Original Type Selection, Book to Two Pages, Density Adjustment, Sharpness, Document Name, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, Sender's Name (TTI), E-Mail Priority

Fax Specifications

Maximum Number of Connection Lines

2

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size

Statement to 11" x 17"

Fax Features

Job Forwarding, Different-size Originals, Adjusting Overall Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Selecting the Telephone Line (when sending fax), Delayed Send, Preview, Finished Stamp, Job Done Notice, Original Type Selection, Two-sided Original, Book to Two Pages

Store Specifications

Memory Media

Standard: USB Memory
Optional: SD, SDHC, CompactFlash, Memory Stick, Microdrive

Security Specifications

Standard

Department ID Management, Single Sign-On-H, Access Management System (Device and Function Level Log-in), Secured Print, Trusted Platform Module, IPV6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), SSL Encrypted Communication, SNMPv1/v3, MAC/IP Address Filtering, SMTP Authentication, POP Authentication before SMTP, HDD Format, HDD Initialize (Up to 9x), HDD Erase (Up to 3x), HDD Lock, IPsec, Adobe® LiveCycle® Rights Management ES2.5 Integration

Optional

Removable HDD, HDD Encryption, HDD Mirroring, Encrypted Secure Print, Encrypted PDF, Document Scan Lock, Secure Watermark, IEEE 2600.1 Common Criteria Certification*

Environmental Information

ENERGY STAR® Qualified

EU RoHS Compliant

Ecomark

Blue Angel

WEEE Directive

Optional Accessories

Paper Supply Options

Cassette Feeding Unit-AF1

Paper Capacity: 550 Sheets x 2 Cassettes [20 lb. Bond (80g/m²)]
Acceptable Paper Weight: 17 lb. Bond to 60 lb. Cover (64 to 163g/m²)
Acceptable Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, and Custom Size [5-1/2" x 7-1/8" to 12" x 18" (139.7mm x 182mm to 304.8mm x 457.2mm)]

Power Source/Maximum Power Consumption: From the Main Unit/Approximately 30W
Dimensions (H x W x D): 9-3/4" x 22-1/4" x 25-5/8" (248mm x 565mm x 650mm)
Weight: Approximately 61 lb. (27.5kg)

Envelope Feeder Attachment-D1**

Paper Capacity: 50 Sheets (or 30mm in height)
Acceptable Paper Size: COM10 No.10, Monarch, DL, ISO-C5
Feeding Speed: 10 cpm
Dimensions (H x W x D): 3-1/4" x 17-1/4" x 12-1/8" (81mm x 439mm x 307mm)
Weight: Approximately 2.6 lb. (1.2kg)

Output Options

Inner 2-way Tray-F1

Number of Trays: 2
Total Output Capacity: Top Tray: 250 Sheets (20 lb. Bond)
Lower Tray: 100 Sheets (20 lb. Bond)
Acceptable Paper Weight: 17 lb. Bond to 80 lb. Cover (64 to 220g/m²)
Acceptable Paper Size: 12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-1/2" to 12-5/8" x 18" (99mm x 139.7mm to 320mm x 457.2mm)], and Envelopes
Dimensions (H x W x D): 3" x 16-3/4" x 16" (76mm x 427mm x 407mm)
Weight: Approximately 1.3 lb. (574g)

Optional Accessories (continued)

Output Options (continued)

Inner Finisher-F1

Number of Trays:	Up to 2 Trays (With Inner Finisher Additional Tray-A1)
Total Output Capacity:	Without Inner Finisher Additional Tray-A1 750 Sheets With Inner Finisher Additional Tray-A1 Top Tray: 100 Sheets (Letter) Lower Tray: 350 Sheets (Letter)
Acceptable Paper Weight:	17 lb. Bond to 80 lb. Cover (64 to 220g/m ²)
Acceptable Paper Size:	12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-1/2" to 12-5/8" x 18" (99mm x 139.7mm to 320mm x 457.2mm)], and Envelopes
Staple Positions:	Corner Stapling (11" x 17", Legal, Letter, Letter-R) Double Stapling (11" x 17", Legal, Letter, Letter-R)
Maximum Stapling Capacity:	Letter: 50 Sheets (17 to 21 lb. Bond) 30 Sheets (22 to 28 lb. Bond) 2 Sheets (29 lb. Bond to 80 lb. Cover) 11" x 17", Legal, and Letter-R: 30 Sheets (17 to 21 lb. Bond) 20 Sheets (22 to 28 lb. Bond) 2 Sheets (29 lb. Bond to 80 lb. Cover)
Paper Capacity of Staple Mode:	Top Tray: 15 Sets (or 3/8" in height) Lower Tray: 30 Sets (or 3-3/4" in height)
Type of Staple:	Staple-J1 (5,000 x 3)
Power Source/Maximum Power Consumption:	From the Main Unit/Approximately 40W
Dimensions (H x W x D):	10-1/4" x 27-1/2" x 21-1/4" [260mm x 700mm x 540mm (When the Auxiliary Tray is extended)]
Weight:	Approximately 31 lb. (14kg) (when Inner Finisher Additional Tray-A1 is attached)

Staple Finisher-M1

Number of Trays:	2
Total Output Capacity:	3,000 Sheets (Letter, Statement-R, Executive) Top Tray: 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) Lower Tray: 1,700 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)
Acceptable Paper Weight:	17 lb. Bond to 80 lb. Cover (64 to 220g/m ²)
Acceptable Paper Size:	12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-9/16" to 12-5/8" x 18" (99 x 139.7mm to 320mm x 457.2mm)], and Envelopes
Staple Positions:	Corner Stapling: (11" x 17", Legal, Letter, Letter-R, Executive) Double Stapling: (11" x 17", Legal, Letter, Letter-R, Executive)

Staple Finisher-M1 (continued)

Maximum Stapling Capacity:	Letter and Executive: 50 Sheets (18 to 22 lb. Bond) (64 to 82g/m ²) 30 Sheets (22 to 28 lb. Bond) (83 to 105g/m ²) 2 Sheets (29 lb. Bond to 80 lb. Cover) (106 to 220g/m ²) 11" x 17", Legal, and Letter-R: 30 Sheets (18 to 22 lb. Bond) (64 to 82g/m ²) 20 Sheets (22 to 28 lb. Bond) (83 to 105g/m ²) 2 Sheets (29 lb. Bond to 80 lb. Cover) (106 to 220g/m ²)
Paper Capacity of Staple Mode:	Top Tray: 1,300 Sheets/30 Sets (Letter, Executive), 650 Sheets/30 Sets (11" x 17", Legal, Letter-R) Lower Tray: 1,700 Sheets/30 Sets (Letter, Executive), 650 Sheets/30 Sets (11" x 17", Legal, Letter-R)
Type of Staple:	Staple-J1 (5,000 x 3)
Power Source/Maximum Power Consumption:	From the Main Unit/Approximately 84W
Dimensions (H x W x D):	43-1/4" x 26-1/2" x 25-1/2" [1097mm x 673mm x 647mm (When the Auxiliary Tray is extended)]
Weight:	Approximately 101 lb. (46kg)

Booklet Finisher-M1

Number of Trays:	2
Total Output Capacity:	3,000 sheets (Letter, Statement-R, Executive) Top Tray: 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) Lower Tray: 1,700 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)
Acceptable Paper Weight:	17 lb. Bond to 80 lb. Cover (64 to 220g/m ²)
Acceptable Paper Size:	12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-9/16" to 12-5/8" x 18" (99 x 139.7mm to 320mm x 457.2mm)], and Envelopes
Staple Positions:	Corner/Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-Stitch: 11" x 17", Legal, Letter-R
Maximum Stapling Capacity:	Letter and Executive: 50 Sheets (18 to 22 lb. Bond) (64 to 82g/m ²) 30 Sheets (22 to 28 lb. Bond) (83 to 105g/m ²) 2 Sheets (29 lb. Bond to 80 lb. Cover) (106 to 220g/m ²) 11" x 17", Legal, and Letter-R: 30 Sheets (18 to 22 lb. Bond) 20 Sheets (22 to 28 lb. Bond) 2 Sheets (29 lb. Bond to 80 lb. Cover)
Paper Capacity of Staple Mode:	Top Tray: 1,300 Sheets/30 Sets (Letter, Executive), 650 Sheets/30 Sets (11" x 17", Legal, Letter-R) Lower Tray: 1,700 Sheets/30 Sets (Letter, Executive), 650 Sheets/30 Sets (11" x 17", Legal, Letter-R)

Maximum Saddle-Stitch Capacity:	16 Sheets (14 to 20 lb. Bond) 10 Sheets (22 to 28 lb. Bond)
Paper Capacity of Saddle-Stitch Mode:	25 Booklets (5-sheet Booklets)
Type of Staple:	Staple-J1 (5,000 x 3) Staple Cartridge-D3 (2,000 x 3)
Power Source/Maximum Power Consumption:	From the Main Unit/Approximately 118W
Dimensions (H x W x D):	43-1/4" x 31" x 25-7/8" [1097mm x 786mm x 656mm (When the Auxiliary Tray is extended)]
Weight:	Approximately 165 lb. (75kg)

Other Optional Accessories

• Cabinet Type-D	• Super G3 2nd Line Fax Board-AH1
• Utility Tray-A2	• Remote FAX Kit-A1
• USB Keyboard	• Barcode Printing Kit-D1
• Universal Keyboard Stand-A1	• Web Access Software-H1
• Copy Card Reader-F1	• USB Device Port-E2
• Convenience Stapler-B1	• Multimedia Reader/Writer-A2
• Universal Send Advanced Feature Set-F1	• Copy Control Interface Kit-A1
• Universal Send Security Feature Set-D1	• iR-ADV Security Kit-D1 for IEEE 2600.1 Common Criteria Certification*
• Super G3 FAX Board-AH2	

* Can be set to Cassette 2 only. Can not install Envelope Feeder Attachment and Tab Feeding Attachment at same time.

** If "Quick Startup Settings for Main Power" is set to ON, it takes 7 seconds until the key operation on the touch panel display is available after turning on the main power.

† Includes consumables.

†† EPS cannot be printed directly from the Web Access software.

††† XPS can be printed directly only from Remote User Interface.

• Not available at time of launch.

NOTE: Some accessories require additional equipment or may be prerequisites for other options. Some accessories cannot be installed simultaneously. Check with your Canon Authorized Dealer for details.

Canon
*image*ANYWARE

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, MEAP, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and hereby acknowledged. Specifications and availability subject to change without notice. Some items may not be available at this time; please check for availability. All printer output images are simulated.

©2013 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

