

Semi-Portable Dock Lifts

In the event you find the cost of forming a concrete pit/pad expensive, an economical solution is a LoMaster Semi-Portable Dock Lift. The unit is installed at the dock face and mounted on locating cradles and wear plates. With its extremely low profile, the LoMaster Semi-Portable Dock Lift provides added versatility for ground level loading/unloading operations.

The same high quality construction features found in the stationary models are incorporated into all LoMaster Semi-Portable Dock Lifts. Each lift cylinder is encased in a weather-resistant, all steel housing. Precision velocity fuses on each hydraulic cylinder eliminates platform free-fall. All hard chromed pivot points are fitted with lifetime-lubricated bearings or Teflon coated bronze bushings. Indicator sensing bars and high visibility striping provide four sided toe protection. Sturdy steel handrails with 4" (107 mm) kick plate and barrier chains at both ends provide added operator safety. An 18" (457 mm) long lip with lifting chain on the rolling end is standard.

Minimal maintenance and product longevity - put a LoMaster Semi-Portable Dock Lift to work at your facility.

Options

- Portable dolly.
- 24VAC voltage control.
- Key switch on push button.
- Warning horn with volume control.
- Electric toe guard protection.
- Flashing amber beacon.
- Aluminum lip.
- 3-5 HP remote power pack.



LIFT SPEED CONVERSIONS FOR OPTIONAL POWER PACKS

5 HP to 3 HP	multiply lift speed by 0.4167
5 HP to 7 1/2 HP	multiply lift speed by 1.29

STANDARD POWER PACK	DIMENSION			SHIPPING WEIGHT
	LENGTH	WIDTH	HEIGHT	
3 HP	18" 457mm	15" 381 mm	29" 737 mm	175 lb 80 kg
5 HP	20" 508 mm	20" 508 mm	29" 737 mm	190 lb 86 kg

DECK SIZE (WIDTH x LENGTH)*	LOWERED HEIGHT (nominal)	VERTICAL TRAVEL	RAISED HEIGHT	LIFT SPEED*** by CAPACITY**		
5 HP REMOTE POWER PACK				4,000 lb 1,818 kg	5,000 lb 2,273 kg	6,000 lb 2,727 kg
72" x 96" 1,829 mm x 2,438 mm	5" 127 mm	55" 1,397 mm	60" 1,524 mm	20.1 fpm 6.1 ppm	20.1 fpm 6.1 ppm	14.2 fpm 4.3 ppm
72" x 120" 1,829 mm x 3,048 mm				14.2 fpm 4.3 ppm		-
84" x 96" 2,134 mm x 2,438 mm	5 1/4" 133 mm	55" 1,397 mm	60 1/4" 1,530 mm	20.1 fpm 6.1 ppm		-
84" x 120" 2,134 mm x 3,048 mm				14.2 fpm 4.3 ppm		-
96" x 120" 2,438 mm x 3,048 mm				14.2 fpm 4.3 ppm		-

*Dimension between cylinder posts is 18" (457 mm) less than overall deck width.

Capacities are based on evenly distributed loads. Single axle rolling load capacity is **50% of rated capacity across the ends and **20%** of rated capacity across the sides.

***Nominal lift speeds with rated load - based on factory test conditions.

Note: Overall raised height = lowered height plus vertical travel. All dock lifts come with 18" (457 mm) long x 60" (1,524 mm) wide lip on rolling end.



85 Heart Lake Road South
Brampton, Ontario, Canada L6W 3K2
Phone: 905-457-3900 • Fax: 905-457-2313
www.BlueGiant.com

A U T H O R I Z E D D I S T R I B U T O R

B L U E G I A N T E Q U I P M E N T C O R P O R A T I O N

BLUE GIANT offers a full line of Loading Dock Equipment including Dock Levelers, Vehicle Restraints, Dock Seals and Shelters and Material Handling Solutions. Concurrent with our continuing product improvement program, specifications are subject to change without notice. Please contact BLUE GIANT for latest information. Some features illustrated may be optional in certain market areas.

LoMaster Dock Lift Series

g r o u n d l e v e l h y d r a u l i c l i f t s

BLUE GIANT®



Turn any Ground Level Area into a LoMaster Series Functional Loading Dock

The LoMaster Series Dock Lift from Blue Giant provides a safe and efficient way to handle endless materials handling applications at grocery stores, schools, hospitals, postal services and distribution centers - anywhere a low-profile workhorse is required.

Typically, a dock lift will cost 1/3 the price of a fork truck and will have a quick and favorable payback when compared to the long-term cost associated with operating a forklift and manually loading/off-loading a trailer. A LoMaster Series Dock Lift will also greatly reduce handling costs, cargo damage and employee injury common to vertical transfer operations.

Blue Giant LoMaster Series Dock Lifts are available in many sizes with standard capacities up to 20,000 lb (9,091 kg). No hidden hook-up costs. User ready. Before choosing, compare Blue Giant's standard design features.



Standard Features

- Remote power pack 12' (3,658 mm) hydraulic hose (3 phase, common voltages).
- Push button control on 12' (3,658 mm) straight cord.
- Hydraulic pump with built-in overload relief.
- Hydraulic and oil hoses included.
- Up-travel limit switch.
- Motor, controls, push button factory pre-wired & tested (UL/CSA approved).
- Full length deck beam for maximum support.
- Solid plate steel legs for maximum rigidity.
- 8" (203 mm) tapered toe guard protection on stationary models only.
- Handrails with 4" (102 mm) kick plate and barrier chain across both ends.
- Checkered deck and 18" (457 mm) long lip with lifting chain on rolling end.
- Hard chromed pivot pins at cylinder and center pin.
- All pivot points equipped with maintenance free lifetime lubricated bushings.
- Scissor leg roller bearings maintenance free.
- Precision safety velocity fuses on hydraulic cylinders to prevent platform freefall.
- Mechanical, hinged to frame, flip-down maintenance stop on stationary models only.
- Completely sealed, weather resistant cylinders vented back to hydraulic tank to prevent contaminant entry into cylinder.
- Complies to ANSI MH29.1 standards.
- Backed by an industry leading warranty.



Stationary Dock Lifts

Blue Giant LoMaster Series Stationary Dock Lift models can be mounted in a pit or anchored to a concrete pad.



Options

- 24VAC voltage control.
- Key switch on push button.
- Electric toe guard protection.
- Warning horn with volume control.
- Flashing amber beacon.
- Aluminum lip.
- Spring and hydraulic assisted lips.
- Mechanical pop-up wheel chock.
- Accordion safety skirting.
- Interlock swing gates.
- Low temp oil.
- Submersion heater for oil reservoir.
- 3-10 HP remote power packs.
- Consult factory for additional options.



LIFT SPEED CONVERSIONS FOR OPTIONAL POWER PACKS		
5 HP to 3 HP	multiply lift speed by 0.4167	
5 HP to 7 1/2 HP	multiply lift speed by 1.29	
7 1/2 HP to 10 HP	multiply lift speed by 1.45	

POWER PACK	DIMENSION			SHIPPING WEIGHT
	LENGTH	WIDTH	HEIGHT	
3 HP	18" 457 mm	15" 381 mm	29" 737 mm	175 lb 80 kg
5 HP	20" 508 mm	20" 508 mm	29" 737 mm	190 lb 86 kg
7 1/2 HP	25" 635 mm	20" 508 mm	36Zx" 927 mm	405 lb 184 kg
10 HP	25" 635 mm	29" 737 mm	31" 787 mm	460 lb 209 kg

Note: 3 HP available for 4,000 lb - 6,000 lb (1,818 kg - 2,727 kg) capacity models only

DECK WIDTH	DECK LENGTH	LOWERED HEIGHT	VERTICAL TRAVEL	RAISED HEIGHT	LIFT SPEED** by CAPACITY*		
					5 HP REMOTE POWER PACK	4,000 lb 1,818 kg	5,000 lb 2,273 kg
60" 1,524 mm	96" 2,438 mm	10" 254 mm	59" 1,499 mm	69" 1,753 mm	16.5 fpm 5.0 mph	14.0 fpm 4.3 mph	12.2 fpm 3.7 mph
	108" 2,743 mm				11.5 fpm 3.5 mph	11.5 fpm 3.5 mph	7.6 fpm 2.3 mph
	120" 3,048 mm				10.8 fpm 3.3 mph	7.2 fpm 2.2 mph	7.2 fpm 2.2 mph
	144" 3,658 mm	14" 356 mm	59" 1,499 mm	73" 1,854 mm	10.3 fpm 3.1 mph	6.9 fpm 2.1 mph	6.9 fpm 2.1 mph
72" 1,829 mm	96" 2,438 mm				8,000 lb 3,636 kg	10,000 lb 4,545 kg	12,000 lb 5,454 kg
	108" 2,743 mm				11.8 fpm 3.6 mph	10.8 fpm 3.3 mph	7.7 fpm 2.3 mph
	120" 3,048 mm				11.5 fpm 3.5 mph	7.4 fpm 2.3 mph	7.4 fpm 2.3 mph
	144" 3,658 mm	14" 356 mm	59" 1,499 mm	73" 1,854 mm	11.0 fpm 3.4 mph	7.4 fpm 2.3 mph	7.4 fpm 2.3 mph
84" 2,134 mm	96" 2,438 mm				6.5 fpm 2.0 mph	5.8 fpm 1.8 mph	6.5 fpm 2.0 mph
	108" 2,743 mm				7.4 fpm 2.3 mph	7.4 fpm 2.3 mph	7.4 fpm 2.3 mph
	120" 3,048 mm				6.7 fpm 2.0 mph	6.7 fpm 2.0 mph	6.3 fpm 1.9 mph
	144" 3,658 mm				6.3 fpm 1.9 mph	5.8 fpm 1.8 mph	5.8 fpm 1.8 mph
96" 2,438 mm	96" 2,438 mm				15,000 lb 6,818 kg	20,000 lb 9,091 kg	
	108" 2,743 mm				7.4 fpm 2.3 mph	7.4 fpm 2.3 mph	
	120" 3,048 mm				6.7 fpm 2.0 mph	6.7 fpm 2.0 mph	
	144" 3,658 mm	21" 533 mm	59" 1,499 mm	80" 2,032 mm	6.3 fpm 1.9 mph	5.8 fpm 1.8 mph	5.8 fpm 1.8 mph

*Capacities are based on evenly distributed loads. Single axle rolling load capacity is 80% of rated capacity across the ends and 50% of rated capacity across the sides.

**Nominal lift speeds with rated load - based on factory test conditions.

Note: Consult factory for custom sizes and capacities. All dock lifts come with 18" (457 mm) long x 60" (1,524 mm) wide lip on rolling end.