

SECTION 33 05 13

MANHOLES AND STRUCTURES

PART 1 - GENERAL

1.1 DESCRIPTION

A. Scope:

1. CONTRACTOR shall provide all labor, materials, equipment and incidentals as shown, specified and required to furnish and install all precast, cast-in-place and masonry manholes and structures.

B. General:

1. Manholes and structures shall conform in shape, size, dimensions, material, and other respects to the details shown or as directed by ENGINEER.
2. Cast-iron frames, grates and covers shall be the standard frame and grate or cover unless otherwise shown and shall be as specified in Section 05 56 00, Metal Castings.
3. Concrete for cast-in-place manholes and structures and for inverts in precast and masonry manholes and structures shall be Class "A" and shall conform to the requirements specified under Section 03 30 00, Cast-In-Place Concrete.
4. All manholes and structures shall be precast construction, unless otherwise shown.

C. Related Sections:

1. Section 03 30 00, Cast-In-Place Concrete.
2. Section 05 50 13, Miscellaneous Metal Fabrications.
3. Section 05 56 00, Metal Castings.

1.2 REFERENCES

A. Standards referenced in this Section are listed below:

1. American Society for Testing and Materials, (ASTM).
 - a. ASTM C 32, Specification for Sewer and Manhole Brick (made from Clay or Shale).
 - b. ASTM C 139, Specification for Concrete Masonry Units for Construction of Catch Basins and Manholes.
 - c. ASTM C 140, Test Methods for Sampling and Testing Concrete Masonry Units and Related Units.
 - d. ASTM C 207, Specification for Hydrated Lime for Masonry Purposes.
 - e. ASTM C 478, Specification for Precast Reinforced Concrete Manhole Sections.
2. American Water Works Association, (AWWA).
 - a. AWWA C302, Reinforced Concrete Pressure Pipe, Non-cylinder Type, for Water and Other Liquids.

1.3 SUBMITTALS

- A. Action Submittals: Submit the following:
 - 1. Shop Drawings:
 - a. Submit drawings showing design and construction details of all precast concrete and cast-in-place manholes and structures, including details of joints between the manhole bases and riser sections and stubs or openings for the connections.

PART 2 - PRODUCTS

2.1 PRECAST CONCRETE MANHOLES AND STRUCTURES

- A. Precast manholes and structures shall conform to the details shown. Provide cast-in-place concrete bases where shown.
- B. Except where otherwise specified precast manhole components shall consist of reinforced concrete pipe sections especially designed for manhole construction and manufactured in accordance with ASTM C 478, except as modified herein.
- C. Precast, reinforced concrete manhole bases, riser sections, flat slabs and other components shall be manufactured by wet cast methods only, using forms which will provide smooth surfaces free from irregularities, honeycombing or other imperfections.
- D. Joints between manhole components shall be the tongue and groove type employing a single, continuous rubber O-ring gasket and shall conform to AWWA C302. The circumferential and longitudinal steel reinforcement shall extend into the bell and spigot ends of the joint without breaking the continuity of the steel. Joints between the base sections, riser sections and top slabs of manholes 72-inches in diameter and less shall be rubber and concrete joints. Joints for manhole components greater than 72-inches in diameter shall be provided with steel bell and spigot rings.
- E. All precast manhole components shall be of approved design and of sufficient strength to withstand the loads imposed upon them. They shall be designed for a minimum earth cover loading of 130 pounds per cubic foot, an H-20 wheel loading, and an allowance of 30 percent in roadways and 15 percent in rights-of-way for impact. Manhole bases shall have two cages of reinforcing steel in their walls, each of the area equal to that required in the riser sections. Wall thickness shall not be less than 5-inches. Concrete top slabs shall not be less than 8-inches thick.
- F. Lifting holes, if used in manhole components, shall be tapered, and no more than two shall be cast in each section. Tapered, solid rubber plugs shall be furnished to seal the lifting holes. The lifting holes shall be made to be sealed by plugs driven from the outside face of the section only.

- G. The point of intersection (P.I.) of the sewer pipe centerlines shall be marked with 1/4-inch diameter steel pin firmly enclosed in the floor of each manhole base and protruding approximately 1-inch above the finished floor of the base.
- H. Mark date of manufacture and name or trademark of manufacturer on inside of barrel.
- I. The barrel of the manhole shall be constructed of various lengths of riser pipe manufactured in increments of one foot to provide the correct height with the fewest joints. Openings in the barrel of the manholes for sewers or drop connections will not be permitted closer than one foot from the nearest joint. Special manhole base or riser sections shall be furnished as necessary to meet this requirement.
- J. A precast or cast-in-place slab or precast eccentric cone, as shown or approved, shall be provided at the top of the manhole barrel to receive the cast iron frame and cover.

2.2 MASONRY MANHOLES AND STRUCTURES

- A. Masonry manholes and structures, where shown or otherwise approved by ENGINEER, shall conform to the following:
 - 1. Brick: Brick shall conform to the requirements of ASTM C 32, Grade SS for sewer brick and Grade MS for manhole brick.
 - 2. Concrete Blocks: Concrete blocks shall be machine-made, solid segmental blocks not less than 8-inches wide and shaped so that the completed structure in which they are used will conform to the details shown or otherwise approved. Blocks shall be of compact texture and like blocks shall be uniform in shape and size.
 - 3. Concrete blocks shall conform to ASTM C 139. Testing of blocks shall be done in accordance with the requirements of ASTM C 140.
 - 4. Mortar: The mortar shall be composed of portland cement, hydrated lime, and sand, in which the volume of sand shall not exceed three times the sum of the volumes of cement and lime.
 - 5. Cement shall be Type II portland cement as specified for concrete masonry.
 - 6. Hydrated lime shall be Type S conforming to ASTM C 207.
 - 7. The sand shall comply with the Specifications for "Fine Aggregate" for concrete, except that all of the sand shall pass a No. 8 sieve.

2.3 MISCELLANEOUS METALS

- A. Metal frames and covers and similar required items shall be provided as shown and in accordance with Division 05, Metals.

PART 3 - EXECUTION

3.1 LAYING MASONRY

- A. Brick shall be satisfactorily wet when being laid and each brick shall be laid in mortar so as to form full bed, end and side joints in one operation. The joints shall not be wider than 3/8-inch, except when the bricks are laid radially, in which case the narrowest part of the joint shall not exceed 1/4-inch. Masonry work shall be kept moist for a period of three days after completion, and precautions shall be taken to prevent freezing during cold weather.
- B. For concrete block, the vertical keyways shall be completely filled with mortar.
- C. Each grading ring shall be laid in a full bed of mortar and shall be thoroughly bonded.

3.2 PLASTERING

- A. The outside of brick manholes and structures, brick stacks and grading rings shall be neatly plastered with 1/2-inch of cement mortar as the Work progresses.

3.3 MANHOLE BASES

- A. Precast bases shall be set on a crushed stone or crushed gravel or concrete foundation as shown. Precast bases shall be set at the proper grade and carefully leveled and aligned.

3.4 PRECAST MANHOLE SECTIONS

- A. Set sections vertical with steps and sections in true alignment. The base of the bell or groove end at joints between components shall be buttered with 1:2 cement-sand mortar to provide a uniform bearing between components. All joints shall be sealed with cement mortar inside and out and troweled smooth to the contour of the wall surface. Raised or rough joint finishes will not be accepted.
- B. Install sections, joints and gaskets in accordance with manufacturers recommendations.
- C. Lifting holes shall be sealed tight with a solid rubber plug driven into the hole from the outside of the barrel and the remaining void filled with 1 to 2 cement-sand mortar.

3.5 MANHOLE CHANNELS

- A. All invert channels through manholes and structures shall be constructed of Class "A" concrete. Channels shall be properly formed to the sizes, cross sections, grades and shapes shown or as ordered. Benches shall be built up to the heights shown or as directed by the ENGINEER and given a uniform wood float finish. Care shall be taken to slope all benches for proper drainage to the invert channel.

3.6 GRADING RINGS

- A. Grading rings or brick stacks shall be used for all precast and masonry manholes and structures, where required. Stacks or grade rings shall be a maximum of 12-inches in height, constructed on the roof slab or cone section on which the manhole frame and cover shall be placed. The height of the stack or grade rings shall be such as required to bring the manhole frame to the proper grade.
- B. Each grade ring shall be laid in a full bed of mortar and shall be thoroughly bonded.
- C. Brick work shall be as specified in Article 2.2 and Article 3.1, above.

3.7 STUBS FOR FUTURE CONNECTIONS

- A. As shown or required for connections, cast iron sleeves, bell end tile, ductile iron or reinforced concrete pipe stubs with approved watertight plugs shall be installed in manholes and structures. Where pipe stubs, sleeves or couplings for future connections are shown or directed by the ENGINEER, CONTRACTOR shall provide all materials and labor in order to complete the Work.

3.8 GRADING AT MANHOLES AND STRUCTURES

- A. All manholes and structures in unpaved areas shall be built, as shown or directed by the ENGINEER, to an elevation higher than the original ground. The ground surface shall be graded to drain away from the manhole. Fill shall be placed around manholes to the level of the upper rim of the manhole frame, and the surface evenly graded on a 1 to 5 slope to the existing surrounding ground, unless otherwise shown or directed by the ENGINEER. The slope shall be covered with 4-inches of topsoil, seeded and maintained until a satisfactory growth of grass is obtained.
- B. Manholes and structures in paved areas shall be constructed to meet the final surface grade. In paved areas on State Highways, all manholes and structures shall be 1/2-inch below final wearing surfaces. Manholes and structures shall not project above finished roadway pavements to prevent damage from snowplows.
- C. CONTRACTOR shall be solely responsible for the proper height of all manholes and structures necessary to reach the final grade at all locations. CONTRACTOR is cautioned that ENGINEER'S review of Shop Drawings for manhole components will be general in nature and CONTRACTOR shall provide an adequate supply of random length precast manhole riser sections to adjust any manhole to meet field conditions for final grading.

3.9 MANHOLE WATERTIGHTNESS

- A. All manholes and structures shall be free of visible leakage. Each manhole shall be tested for leaks and inspected, and all leaks shall be repaired in a manner subject to ENGINEER'S approval. Manhole testing shall conform to the requirements of Section 33 05 05, Buried Piping Installation.

3.10 FLEXIBLE PIPE JOINT AT MANHOLE BASE

- A. An approved flexible joint shall be provided between each pipe entering and exiting the manhole. This may be accomplished by the installation in the manhole base of the bell end of a pipe or by other means subject to approval of ENGINEER. Joints shall be similar to the approved pipe joints. The joint into the manhole base shall be completely watertight.

+ + END OF SECTION + +