Universal Power Supply 3 x 1A Outputs

EASYIO-FG-PWR72



A high quality DIN Rail Mounted isolated 3 x 24VDC, 1 amp each, BMS Power Supply. The first output can also provide 15V DC using a jumper setting.

EasyIO need to have a high quality 24V DC regulated and isolated, 3 x 1A Power Supplies, in one sturdy UL plastic approved DIN rail casing. Ideal for Power EasyIO's in panels and also powering the Area controller, where applicable. The overall power rating of the FG-PWR72 is 72W and it accepts mains power of 110/120V AC and 220/240 AC, 50/60Hz.

This product has features such as high efficiency and high reliability, and it also has the protection function such as short-circuit protection, and over current protection.



Specification:

Power supply Consumption Operating temp Storage temp Operating humidity Storage humidity

Output voltage Max output current Output ripple Total output power Efficiency Short circuit protection Over current protection Dimensions Material

90VAC to 275VAC, 50Hz/60Hz 2.5A @ 230VAC, 3A @ 24V 0 to 50 °C (32 to 122 °F) -25 to 75 °C (-13 to 167 °F) 25% to 90% relative humidity non-condensing 10% to 90% relative humidity non-condensing +15VDC or +24VDC ± 5%, 1A max +24VDC ± 5%, 1A max +24VDC ± 5%, 1A max 1A for all the outputs 240mVp-p @ 25 °C for all the outputs 72W Greater than 82% Yes Yes 110 x 96 x 40 mm UL Approved Plastic 500g

Features:

Weight

- 3x dedicated 24V DC regulated 1A Power Supplier, all in one unit
- 72W power and supports universal AC mains power 110/120V and 220/240V AC
- High efficiency and high reliability, and it also has the protection function such as short-circuit protection, over current protection
- First output can be set to 15V/24V DC by changing the internal jumper under the cover
- Compact size



All specifications subject to change without notice or liability to provide changes to prior purchasers, information and specifications published here are current as of the date of publication of this document. EasyIO. reserves the right to change or modify specifications without prior notice. The latest product specifications can be found by contacting us.

CE