

## R410A SERVICE TOOL KIT

#TLB410KIT

Everything you need to service ductless mini-split and central A/C systems with 1/4" & 5/16" service ports.



TLB410KIT shown above. Details on back.

### **R410A SERVICE** TOOL KIT

#TLB410KIT





#### **Pro-Set® Premium Piston** Series Manifold #MT2HP

- 2 valve anodized aluminum block body
- 1/4" SAE 45° fittings
- Triple Seal piston valves
- Sure grip rubber over metal valve handles
- 3 1/8" (80 mm) Class 1.0 accuracy gauges
- Protective gauge boots
- Extra access port in center with Schrader valve and hanging hook



### 5' Premium Charging Hoses

#HP5BE-Blue, HP5RE-Red,

- HP5YE- Yellow
  1/4" hoses with SAE fittings, 45° ball valve on one end
- 800PSI working pressure
- 4000PSI burst pressure
- Leak-proof 8-sided crimp
- Extra deep knurling
- Adjustable valve core depressor
- Blow off grooves preventing spray back

**Hex Key Sets** (1) Imperial #TLSWH 5/<sub>64</sub>", 3/<sub>52</sub>", 7/<sub>64</sub>", 1/<sub>8</sub>", 9/<sub>64</sub>", 5/<sub>52</sub>", 3/<sub>16</sub>", 7/<sub>52</sub>", 1/<sub>4</sub>"



(1) Metric #TLSWHM 1.5, 2, 2.5, 3, 4, 5, 6, 8mm





Valve Core Tool #TLVCS410A Unique configuration of tool enables use of standard 1/4" SAE manifold/hose sets with R-410A systems incorporating 5/16" (1/2"-20UNF) service ports.

- Designed to remove and install valve core without losing system charge
- Increases evacuation and charging speed by creating unrestricted access



#### **Brass Adapters and Caps**

- (10) 1/2"-20 UNF Caps #AVC410
- (2) Male: 1/4" SAE 55D; Female; ½"-20 UNF SWVL, #AD87\$ **and**
- (2) Male: 1/4" SAE Female; 1/2"-20 UNF #AD87



# **Large, 16" Rubber Bottom Tool Organizer** #TLBAG2

- Separate compartments for quick, easy-access
- Molded handle for durability and comfort
- Rubber bottom



#### **R410A Flare Size Gauge** #FTXSG

- 6.4 mm, 1/4"
- 9.5 mm, 3/8"
- 12.7 mm, 1/2"
- 15.9 mm, 5/8"
- 19.1 mm, 3/4"



#### BlackMAX® Tube Cutter 1/8" to 1-1/4" #BTC300

- Two quick-change, chromed, hardened cutting wheels
- Enclosed feed screw eliminates clogging, jamming SetNCut™ spring-loaded cutting
- wheel for a perfect cut every time



#### **BlackMAX® Tube Flaring** Tool #BFT850

- Aluminum body is 50% lighter than steel designs
- Internal clutch indicates when formed flare is complete
- Eccentric cone forms precise 45° flared ends
- Creates perfect, strong flares For 3/16", 1/4" 5/16", 3/8", 1/2", 5/8", 3/4" O.D. soft copper, aluminum tube



**Torque Wrench Set with (1)** Universal Handle #TLTWSAE and (6) Imperial and (6) Metric wrenches

(part numbers below)

neaus			
Metric		Imperial	
17 <sub>mm</sub>	#TLXTVM17	5/8"	#TLXTW58
22 <sub>mm</sub>	#TLXTVMM22	11/16"	#TLXTW1116
24 <sub>mm</sub>	#TLXTVMM24	<sup>13</sup> / <sub>16</sub> "	#TLXTW1316
26 <sub>mm</sub>	#TLXTVM26	<sup>15</sup> / <sub>16</sub> "	#TLXTW1516
27mm	#TLXTVMM27	<b>1</b> 1/16"	#TLXTW1L116
29 <sub>mm</sub>	#TLXTVMM29	1 <sup>5</sup> / <sub>16</sub> "	#TLXTW1L516



BlackMAX® Deburring Tool with extra blade #RTI DR3