Issue date: 06.02.2017

Last Revision: 06.02.2017

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Product name: Engine Treatment

• Part number: 206220

· Application of the substance / the mixture Engine oil additive

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Terraclean, division of, CPS Products Canada Ltd. 1324 Blundell Road Mississauga, ON L4Y 1M5 Canada Tel: (905) 615-8620 • email of person responsible: customerservice@terraclean.net

• 1.4 Emergency telephone number: CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

		• •	•	•
Eye Irrit. 2	H319	Causes serious	eye	irritation.
Carc. 1B	H350	May cause cand	cer.	

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts

- Hazard statements
 H319 Causes serious eye irritation.
- H350 May cause cancer.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P201 Obtain special instructions before use.

- P264 Wash thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents in accordance with local regulations.

(Contd. on page 2)

Issue date: 06.02.2017

Version 2

Last Revision: 06.02.2017

Product name: Engine Treatment

(Contd. of page 1)

• Additional information: Restricted to professional users.

· 2.3 Other hazards

- Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
 - · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description:

Mixture: consisting of the following components.

· Chemical compo	onents:	
CAS: 72623-86-0 EINECS: 276-737-9	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based Carc. 1B, H350	10-25%
CAS: 84605-29-8 EINECS: 283-392-8	Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts Acute Tox. 3, H331; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315	0.25-<2.5%
CAS: 64742-65-0 EINECS: 265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic Carc. 1B, H350	0.1-≤2.5%
CAS: 64742-54-7 EINECS: 265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic Carc. 1B, H350	0.1-≤2.5%
CAS: 122-39-4 EINECS: 204-539-4	diphenylamine Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.1-<0.25%
· Additional inform	nation: For the wording of the listed hazard phrases refer to section 1	6.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

• After swallowing: Rinse out mouth. Do not induce vomiting. If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

See section 11.

· Information for doctor: Treat Symptomatically

(Contd. on page 3)

Issue date: 06.02.2017

Version 2

Last Revision: 06.02.2017

Product name: Engine Treatment

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture See section 10 for additional information.
- 5.3 Advice for firefighters • Protective equipment:

Recommend wearing self-contained breathing apparatus. Water may cause splattering.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Personal protective equipment must be worn. Avoid contact with skin, eyes or clothing. Ventilate area if spilled in a confined space or other poorly ventilated area.

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. 6.3 Methods and material for containment and cleaning up:

6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Material can accumulate static charges which may cause an electrical spark.

Maximum Handling Temperature: 70 °C, 158 °F

· Information about fire - and explosion protection: Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

(Contd. on page 4)

GB —

Issue date: 06.02.2017

Version 2

Last Revision: 06.02.2017

Product name: Engine Treatment

(Contd. of page 3)

Take precautions to avoid release to the environment. Store in a cool, dry, well-ventilated area. Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113 deg F (45 deg C) for extended periods of time or if heat sources in excess of 250 deg F (121 deg C) are used. Store separately from incompatible materials. Keep container closed when not in use. Do not store in open, unlabeled or mislabeled containers. See section 10 for incompatible materials. **Storage:**

- · Requirements to be met by storerooms and receptacles:
- See section 10 for incompatible materials.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Maximum Storage Temperature: 45 °C, 113 °F
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

122-39-4 diphenylamine (0.1-<0.2%)

- WEL Short-term value: 20 mg/m³
 - Long-term value: 10 mg/m³

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- Store protective clothing separately.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Chemical resistant protective gloves (EN 374)

· Eye protection:



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

(Contd. on page 5)

GE

Issue date: 06.02.2017

Version 2

Last Revision: 06.02.2017

Product name: Engine Treatment

(Contd. of page 4)

· Form: Fluid · Colour: Yellow-brown		
Mild		
Not determined.		
Not determined.		
Undetermined.		
ange: Undetermined.		
Not applicable.		
Not applicable.		
Not determined.		
Product is not selfigniting.		
Product does not present an explosion hazard.		
Not determined.		
0.83-1.01		
Not determined.		
Not determined.		
Not miscible or difficult to mix.		
er: Not determined.		
Not determined.		
Not determined. No further relevant information available.		

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

GB

Issue date: 06.02.2017

Version 2

Last Revision: 06.02.2017

Product name: Engine Treatment

(Contd. of page 5)

- 10.4 Conditions to avoid Heat, open flames, sparks.
- **10.5 Incompatible materials:** Oxidizing agents. Halogens and halogenated compounds.

· 10.6 Hazardous decomposition products:

Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released. Under combustion conditions, oxides of the following elements will be formed: calcium, sulfur.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

· LD/	LC50 values relev	vant for classification:
84605-29-	8 Phosphorodith salts	nioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc
Oral	LD50	4468 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h (vapor)	>2.3 mg/L (rat)
122-39-4 (diphenylamine	
Oral	LD50	>800 mg/kg (rat)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h (vapor)	3 mg/L (ATE)
	nary irritant effec	
- 9	Skin corrosion/irr Serious eye dama Causes serious ey	
· Res	piratory or skin s	sensitisation
		ta, the classification criteria are not met.
·CM	R effects (carcino	ogenity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity
- May cause cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: Harmful to aquatic life with long lasting effects.

· 12.2 Persistence and degradability

84605-29-8 Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts

Persistance and Degradability 1.5%, 28 d ({ATE}) (Sturm test)

(Contd. on page 7)

GB

Issue	date.	06.02.2017
12206	uale.	00.02.2017

Version 2

Last Revision: 06.02.2017

Product name: Engine Treatment

(Contd. of page 6) 12.3 Bioaccumulative potential 84605-29-8 Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts Bioaccumulation BCF 0.6 ({ATE}) (Octanol-Water Coefficient) 122-39-4 diphenylamine Bioaccumulation BCF 3.4 ({ATE}) (Octanol-Water Coefficient) · 12.4 Mobility in soil No further relevant information available. **Ecotoxical effects:** · Remark: Harmful to fish · Additional ecological information: · General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms 12.5 Results of PBT and vPvB assessment · **PBT:** Not applicable. • **vPvB**: Not applicable. · 12.6 Other adverse effects Avoid release to the environment. **SECTION 13: Disposal considerations** · 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

14.1 UN-Number		
· ADR, ADN, IMDG, IATA	Not Regulated	
· 14.2 UN proper shipping name		
· ADR, ADN, IMDG, IATA	Not Regulated	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
Class	Not Regulated	
14.4 Packing group		
· ADR, IMDG, IATA	Not Regulated	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	

(Contd. of page 7)

Safety data sheet

Issue date: 06.02.2017	Version 2	Last Revision: 06.02.2017

Product name: Engine Treatment

· 14.6 Special precautions for user

 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

· UN "Model Regulation":

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable.

Not applicable.

Not Regulated

No REACH Annex XVII restrictions Contains no REACH candidate substance

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 28

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Issue Date: 06/FEB/2017

· Contact:

Engineering Department

· Revision Changes:

v 1.0 - original release (26/JUN/2015) v 2.0 - revised section 2&3 (06/FEB/2017)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity - Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Carc. 1B: Carcinogenicity - Category 1B

(Contd. on page 9)

GP

Safety data sheet

Issue date: 06.02.2017	Version 2	Last Revision: 06.02.2017
Product name: Engine Treatment		
		(Contd. of page 8)

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

 $\label{eq:aquatic chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2$

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3