data: 07/06/2015 Issue

Issue date: 07/06/2015	v 1	Revision Date: 07/06/2015
1 Identification		
· Product identifier		
· Trade name: Terr	aclean Fuel Injector Cleaner	
 Part number: 20 Application of t 	01210X he substance / the mixture Engine an	nd Fuel System Cleaner
• Manufacturer/Sup Terraclean, division 1324 Blundell Road Mississauga, ON, L Canada Phone: (905) 615-8	of, CPS Products Canada Ltd. 4Y 1M5 620	
Emergency teleph CHEMTREC International	ational +1 (703) 527-3887 (outside the L	US), 1-800-424-9300 (in the US) 24 hr
2 Hozard(a) identifi	action	
2 Hazard(s) identifie		
Acute Tox. 4 H332 Skin Irrit. 2 H315 Eye Irrit. 2A H319 Muta. 1B H340 Carc. 1B H350 Asp. Tox. 1 H304 • Label elements • GHS label element The product is class • Hazard pictogra	Flammable aerosol. Contains gas under pressure; may exp Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. May be fatal if swallowed and enters a sified and labeled according to the Globa	irways.
GHS02 GHS0	4 GHS07 GHS08	
· Signal word Da		
Naphtha (petrole 2-butoxyethanol Solvent naphtha Distillates (petrol Hazard stateme Flammable aero Contains gas un Harmful if inhale Causes skin irrit Causes serious May cause gene May cause canc	sol. der pressure; may explode if heated. d. ation. eye irritation. tic defects.	(Contd. on page 2) US

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

Trade name: Terraclean Fuel Injector Cleaner (Contd. of page 1) · Precautionary statements Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/sprav Wear protective gloves/protective clothing/eve protection/face protection. Keep container tightly closed. IF SWALLOWED: Immediately call a poison center/doctor. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: For Professional Use Only · Classification system: · NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 1· HMIS-ratings (scale 0 - 4) HEALTH *1 Health = *1 FIRE 3 Fire = 3Reactivity = 1REACTIVITY 1 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients · Chemical characterization: Mixtures · Description: Mixture: consisting of the following hazardous components. · Chemical components: 64741-66-8 Naphtha (petroleum), light alkylate 25-50%

111-76-2	2-butoxyethanol	≤10%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤10%
108-11-2	4-methylpentan-2-ol	2.5-<10%
112-80-1	oleic acid, pure	2.5-<10%
	Distillates (petroleum), sweetened middle	1-≤2.5%
	Solvent naphtha (petroleum), heavy arom.	1-≤2.5%
1336-21-6	ammonia	0.1-<1%
	(C	ontd. on page 3)

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

(Contd. of page 2)

0.1-<0.25%

Trade name: Terraclean Fuel Injector Cleaner

91-20-3 naphthalene

4 First-aid measures

· Description of first aid measures

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately rinse with water. Immediately remove all contaminated clothing. If skin irritation occurs, get medical attention. Launder contaminated clothing before reuse.

· After eye contact:

Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

After swallowing:

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

- · Information for doctor:
 - \cdot Most important symptoms and effects, both acute and delayed
 - Headache
 - Dizziness

May cause nose, throat, and lung irritation.

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

- Irritating to skin and eyes. Could cause dermititus. Will cause nausea and vomiting.
- Indication of any immediate medical attention and special treatment needed
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
 - Treat Symptomatically

5 Fire-fighting measures

- · Extinguishing media
 - Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
 - · For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture See section 10 for additional information.
- · Advice for firefighters
 - · Protective equipment:
 - Recommend wearing self-contained breathing apparatus. Water may cause splattering.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Particular danger of slipping on leaked/spilled product.
 Environmental precautions:
 Inform respective authorities in case of seepage into water course or sewage system.
 Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No
- smoking. • Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

US

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

Trade name: Terraclean Fuel Injector Cleaner

(Contd. of page 3)

Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

•	Hand	ling:
---	------	-------

· Precautions for safe handling

Open and handle receptacle with care.

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

Avoid contact with clothing.

Avoid splashes or spray in enclosed areas.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers. See section 10 for incompatible materials.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Engineering Controls Ensure adequate ventilation in the workplace.

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-7	76-2 2-butoxyethanol (≤10%)
PEL	TWA: 240 mg/m³, 50 ppm Skin
REL	TWA: 24 mg/m³, 5 ppm Skin
TLV	TWA: 97 mg/m³, 20 ppm BEI
108-1	11-2 4-methylpentan-2-ol (2.5-<10%)
PEL	TWA: 100 mg/m³, 25 ppm Skin
	PEL REL TLV 108- 2

(Contd. on page 5)

⁰⁵

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

Trade name: Terraclean Fuel Injector Cleaner

(Contd. of page 4)

TWA: 100 mg/m³, 25 ppm Skin TLV STEL: 167 mg/m³, 40 ppm TWA: 104 mg/m³, 25 ppm Skin

REL STEL: 165 mg/m³, 40 ppm

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol (≤10%)

BEI 200 mg/g creatinine

- Medium: urine
- Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Store protective clothing separately.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Chemical resistant protective gloves

· Eye protection:



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

· Body protection: Protective work clothing

Information on basic physical and che · General Information	emical properties	
· Appearance:		
· Form:	Fluid	
· Color:	Yellow	
· Odor:	Characteristic	
 Odour threshold: 	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
 Melting point/Melting range: 	Undetermined.	
 Boiling point/Boiling range: 	Not applicable, as aerosol.	
· Flash point:	45 °C	

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

Trade name: Terraclean Fuel Injector Cleaner

	(Contd. of page 5)
 Flammability (solid, gaseous): 	Not applicable.
· Ignition temperature:	450 °C
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	0.7 Vol %
· Upper:	7.5 Vol %
 Vapor pressure at 20 °C: 	5 hPa
· Density at 20 °C:	0.817 g/cm ³
 Relative density 	Not determined.
 Vapour density 	Not determined.
 Evaporation rate 	Not applicable.
 Solubility in / Miscibility with 	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	iter): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
Solvent content:	
 Organic solvents: 	95.0 %
· VOC content:	95.0 %
 Other information 	No further relevant information available.

10 Stability and reactivity

• Reactivity No further relevant information available.

- · Chemical stability
 - Thermal decomposition / conditions to be avoided:
- Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, open flames, sparks.
- Incompatible materials: Strong Oxidizers
- · Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· LD/	LC50 valu	es that are relevant for classification:
ATE (Acu	te Toxicity	/ Estimates)
Oral	LD50	4040 mg/kg (rat)
Dermal	LD50	3279 mg/kg
Inhalative	LC50/4 h	16.5 mg/l (rat)

(Contd. on page 7)

US

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

Trade name: Terraclean Fuel Injector Cleaner

(Contd. of page 6)

111-76-2	2-butoxye	thanol	
Oral	LD50	470 mg/kg (rat)	
Dermal	LD50	400 mg/kg (rab)	
Inhalative	+ LC50/4 h	2.2 mg/l (rat)	
64742-95	-6 Solvent	naphtha (petroleum), light arom.	
Oral	LD50	>6800 mg/kg (rat)	
Dermal	LD50	>3400 mg/kg (rab)	
Inhalative	+ LC50/4 h	>10.2 mg/l (rat)	
108-11-2	4-methylp		
Oral	LD50	2590 mg/kg (rat)	
Dermal	LD50	3560 mg/kg (rabbit)	
112-80-1	oleic acid,	pure	
Oral	LD50	74000 mg/kg (rat)	
		es (petroleum), sweetened middle	
		4.6 mg/l (rat)	
	naphthalen		
Oral	LD50	490 mg/kg (rat)	
Dermal	LD50 mary irrita	5000 mg/kg (rat)	
· Se · Route · Additi The p for pre	Inhalation Ingestion: nsitization of Exposu ional toxice	 n: Irritant to skin and mucous membranes. Do not inhale, can cause respiratory system irritation. May be fatal if swallowed and enter airways. No sensitizing effects known. ure skin, eye contact, dermal, inhalative ological information: ws the following dangers according to internally approved calculation mether 	nods
· Ca	rcinogenic	categories	
	•	rnational Agency for Research on Cancer)	
111-76-2	2-butoxyet		3
	naphthale		2B
91-20-3	· ·		20
102-71-6	2,2',2"-nitr		3
102-71-6	2,2',2"-nitr	onal Toxicology Program)	3
102-71-6	2,2',2"-nitr	onal Toxicology Program)	
102-71-6 91-20-3	2,2',2"-nitr NTP (Nation naphthalen OSHA-Ca	onal Toxicology Program)	3

12 Ecological information

· Toxicity

111 76 9.9 but avviet hand	
111-76-2 2-butoxyethanol	
EC50 (48 h) >1000 mg/L (daphnia)	
LC50 (96 h) (static) 1490 mg/l (Lepomis macrochirus)	

(Contd. on page 8)

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

Trade name: Terraclean Fuel Injector Cleaner

(Contd. of page 7)

112-80-1 oleic acid, pure LC50 (96 h) 205 mg/l (fish)

• Persistence and degradability No further relevant information available.

\cdot Behavior in environmental systems:

Bioaccumulative potential

108-11-2 4-methylpentan-2-ol

Bioaccumulation LogPow 1.43 (-) (potential low)

112-80-1 oleic acid, pure

Bioaccumulation LogPow 7.73 (-) (potential high)

• Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

\cdot Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

 \cdot Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, IMDG, IATA	UN1950	
· UN proper shipping name		
DOT	Aerosols	
· IMDG, IATA	AEROSOLS	
· Transport hazard class(es)		
· DOT, IMDG, IATA · Class	2.1	
· Environmental hazards:		
Marine pollutant:	No	
 Special precautions for user 	Not applicable.	
· Transport in bulk according to Annex	ll of	
MARPOL73/78 and the IBC Code	Not applicable.	
		(Contd. on page

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

(Contd. of page 8)

Trade name: Terraclean Fuel Injector Cleaner

· UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Sara	1	
. 5	Section 355 (extremely hazardous substances):	
None of th	e ingredients is listed.	
. 5	Section 313 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	
1336-21-6	ammonia	
91-20-3	naphthalene	
· TSC	A (Toxic Substances Control Act):	
All ingredie	ents are listed.	
· Proj	position 65	
· (Chemicals known to cause cancer:	
91-20-3 na	aphthalene	
· (Chemicals known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
. (Chemicals known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
. (Chemicals known to cause developmental toxicity:	
None of th	e ingredients is listed.	
· Car	cinogenic categories	
· E	EPA (Environmental Protection Agency)	
111-76-2	2-butoxyethanol	NL
91-20-3	naphthalene	C, CBD
·]	LV (Threshold Limit Value established by ACGIH)	
111-76-2	2-butoxyethanol	A3
91-20-3	naphthalene	A4
· N	NOSH-Ca (National Institute for Occupational Safety and Health)	
None of th	e ingredients is listed.	
The pro	bel elements oduct is classified and labeled according to the Globally Harmonized System (GH ard pictograms	IS).
GH	S02 GHS04 GHS07 GHS08	

· Signal word Danger

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

Trade name: Terraclean Fuel Injector Cleaner (Contd. of page 9) · Hazard-determining components of labeling: Naphtha (petroleum), light alkylate 2-butoxyethanol Solvent naphtha (petroleum), light arom. Distillates (petroleum), sweetened middle Hazard statements Flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. May be fatal if swallowed and enters airways. Precautionary statements Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray Wear protective gloves/protective clothing/eye protection/face protection. Keep container tightly closed. IF SWALLOWED: Immediately call a poison center/doctor. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/international regulations. · National regulations: · Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases. **16 Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Contact: Engineering Department Issue Date July 6, 2015 • Revision Changes: v 1.0 - original release (July 6, 2015)

- · Abbreviations and acronyms:
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - ACGIH: American Conference of Governmental Industrial Hygienists
 - EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

⁻ U

Issue date: 07/06/2015

v 1

Revision Date: 07/06/2015

Trade name: Terraclean Fuel Injector Cleaner

(Contd. of page 10) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Aerosol 2: Flammable aerosols, Hazard Category 2 Press. Gas: Gases under pressure: Compressed gas Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 1B Carc. 1B: Carcinogenicity, Hazard Category 1 Asp. Tox. 1: Aspiration hazard, Hazard Category 1