

Maximum reliability. Minimum fuss.



Safety Data Sheet

Roof Repair Paint

Sealing Products

Section 1: Identification of the article and the company

- 1.1. Identification:** Aquapol
- 1.2. Use:** PC9a: Coatings and paints, thinners, paint removers.
- 1.3. Details of the supplier of the safety data sheet:**

Fixfast Ltd
Merlin House
Seven Mile Lane
Borough Green
Sevenoaks
Kent
TN15 8QY

Email of Competent person responsible for SDS: quality@fixfast.com

- 1.4. Emergency telephone:** +44 (0) 800 304 7616 (Monday - Friday, normal office hours only)

Section 2: Hazards identification

- 2.1 Classification under CHIP:**
R10; N: R51/53; -: R66; -: R67

Classification under CLP:
STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335

Most important adverse effects

Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- 2.2 Label elements**
Regulation EC 1272/2008 (CLP)

Hazardous statements:

H226: Flammable liquid and vapour.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

Signal words: warning

Hazard pictograms

GHS02: Flame
GHS07: Exclamation mark
GHS09: Environmental

Section 2: Hazards identification - continued



Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P261: Avoid breathing vapours.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/DO NOT INDUCE VOMITING.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+378: In case of fire: Use powder, foam, carbon dioxide to extinguish.

Label elements under CHIP:

Hazard symbols: Dangerous for the environment.



Risk phrases:

R10: Flammable

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases

S2: Keep out of the reach of children.

S29: Do not empty into drains.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.23 Other hazards:

In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1 Substance: Not applicable.

3.2 Mixtures:

WHITE SPIRITS

EINECS	CAS	CHIP Classification	CLP Classification	%
-	-	-: R10; N: R51/53; -: R66; Xn: R65; -: R67	Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; -: EUH066	10 - 30

1-METHOXY-2-PROPYL ACETATE

EINECS	CAS	CHIP Classification	CLP Classification	%
-	108-65-6	-: R10	-	10 - 30

Section 4: First aid measures

4.1 Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2 Most important symptoms and effects both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

- 5.1 Extinguishing Media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.
- 5.2 Special Hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.
- 5.3 Advice for firefighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

- 6.1: Personal precautions** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.
- 6.2: Environmental precautions** Do not discharge into drains or rivers. Contain the spillage using bunding.
- 6.3: Clean up procedures** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.
- 6.4: Reference to other sections** Refer to section 8 of SDS.

Section 7: Handling and storage

- 7.1. Precautions for safe handling:
Handling requirements** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.
- 7.2. Conditions for safe storage, including any incompatibilities:
Storage conditions** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.
- Suitable packaging** Must only be kept in original packaging.
- 7.3. Specific end use(s):** PC9a: Coatings and paints, thinners, paint removers.

Section 8: Exposure controls/personal protection

- 8.1. Workplace exposure limits:** No data available.
- 8.2. Exposure controls:
Engineering Measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
- Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.
- Hand protection:** Protective gloves.
- Eye protection:** Safety glasses. Ensure eye bath is to hand.
- Skin protection:** Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties:

State	Liquid
colour	Grey
odour	Aromatic
Viscosity	Viscous
Flash point °C	23 - 60

9.2. Other information:

No additional information available.

Section 10: Stability and reactivity

10.1. Reactivity:	Stable under recommended transport or storage conditions.
10.2 Chemical stability:	Stable under normal conditions. Stable at room temperature.
10.3 Possibility of Hazardous reactions:	Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.
10.4 Conditions to avoid:	Heat. Hot surfaces. Sources of ignition. Flames.
10.5 Incompatible materials:	Strong oxidising agents. Strong acids.
10.6 Hazardous decomposition products:	In combustion emits toxic fumes.

Section 11: Toxicological information

11.1 Information on Toxicological effects.

Acute toxicity (oral):	Not classified
Acute toxicity (dermal):	Not classified
Acute toxicity (inhalation):	Not classified
Skin contact:	There may be irritation and redness at the site of contact.
Eye contact:	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.
Delayed/immediate effects :	Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Eco toxicity:	No data available
12.2. Persistence and degradability:	No data available
12.3. Bio accumulative potential:	No data available
12.4. Mobility:	No data available
12.5. Results of PBT & vPvB assessment:	This product is not identified as a PBT/vPvB substance.
12.6. Other adverse effects:	No data available

Section 13: Disposal considerations

13.1 Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal company
Disposal of packaging	Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

Section 14: Transport information

In accordance with ADR

14.1 UN number:	UN1263
14.2 Proper shipping name:	PAINT RELATED MATERIAL (WHITE SPIRITS; 1-METHOXY-2-PROPYL ACETATE mixture)
14.3 Transport class:	3
14.4 Packing group:	III
14.5 Environmental hazards:	Yes
14.6 Special precautions for users:	No special precautions. Tunnel code: D/E Transport category: 3

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable

15.2 Chemical safety assessment No additional information available

Section 16: Other information

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3:

EUH066:	Repeated exposure may cause skin dryness or cracking.
H226:	Flammable liquid and vapour.
H304:	May be fatal if swallowed and enters airways.
H335:	May cause respiratory irritation.
H336:	May cause drowsiness or dizziness.
H411:	Toxic to aquatic life with long lasting effects.
R10:	Flammable.
R51/53:	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65:	Harmful: may cause lung damage if swallowed.
R66:	Repeated exposure may cause skin dryness or cracking.
R67:	Vapours may cause drowsiness and dizziness.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



Merlin House
Seven Mile Lane
Borough Green
Sevenoaks
Kent
TN15 8QY

Enquiries

0800 304 7616

International

+44 (0) 1732 882387

Fax

0845 450 7486

Email

info@fixfast.com



Certificate number 10905
ISO 9001, ISO 14001
OHSAS 18001