

## PRODUCT DATA SHEET

EVERBUILD TECNIC<sup>®</sup> Sealant Primer NP2

SOLVENT BASED, POLYORGANOSILOXANE SEALANT PRIMER

**PRODUCT DESCRIPTION**

EVERBUILD TECNIC<sup>®</sup> Sealant Primer NP2 is a solvent based, polyorganosiloxane primer for use on non-porous surfaces prior to applying all common types of silicone polyurethane and hybrid sealants.

**USES**

- Glass
- uPVC
- Aluminium
- Steel
- Ceramics

**CHARACTERISTICS / ADVANTAGES**

- Works on most common non-porous building materials.
- Works with all common silicone types.
- Can also be used with PU and hybrid based sealants.

<b>Boiling Point</b>	116-142°C
<b>Odour</b>	Slight

**PRODUCT INFORMATION**

<b>Packaging</b>	1L tin
<b>Appearance / Colour</b>	Yellow liquid
<b>Shelf Life</b>	12 months from date of manufacture in original, unopened containers.
<b>Storage Conditions</b>	Store in cool, dry conditions between +5°C and +25°C. Ensure good ventilation. Storage outside these parameters will dramatically reduce shelf life. Opened tins must be closed airtight and used up as soon as possible (within 1 month).
<b>Density</b>	0.7 - 0.8 g/cm <sup>3</sup>
<b>Flash Point</b>	9°C (closed cap)
<b>Service Temperature</b>	Working temperature 5°C to 40°C

**APPLICATION INFORMATION**

<b>Curing Time</b>	Drying time @ 20°C - approx 30 minutes
--------------------	--

## APPLICATION INSTRUCTIONS

Coverage will vary according to type and porosity of substrate. As a guide, a 1L tin will cover approx 2.5m<sup>2</sup>.

### APPLICATION METHOD / TOOLS

Apply by brush in one coat and allow to dry.

### LIMITATIONS

- Do not use over bitumen or substrates that bleed oil or plasticizers.
- Do not use below +5°C.
- Do not apply to damp or wet surfaces.

### VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

### ECOLOGY, HEALTH AND SAFETY

Data sheet available to professional user upon request.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

#### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

#### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland

EVERBUILDTECNICSealantPrimerNP2-en-GBEVER-(05-2018)-1-1.pdf