

Godfrey Hirst

TEST REPORT

SCOPE OF WORK

GH Engineered Timber 14/3mm -Pioneer

REPORT NUMBER

190725010SHF-001-R1

TEST DATE(S)

2019-07-25 - 2019-08-15

ISSUE DATE

REVISED DATE

2019-08-15


2019-08-16

PAGES

7

DOCUMENT CONTROL NUMBER

LFT-APAC-SHF-OP-10k(May 1, 2019) © 2019 INTERTEK



Intertek Testing Services Shenzhen Ltd. Shanghai Fengxian Branch



Intertek Testing Services Shenzhen Ltd. Shanghai Fengxian Branch
Plant 5, No. 6958 Daye Road, Fengxian District, Shanghai, China
Tel: 021-61136116 Fax: 021-61189921

Website: www.intertek.com

Test Report

Statement

- 1. This report is invalid without company's special seal for testing on assigned page.
- 2. This report is invalid without authorized person's signature.
- 3. This report is invalid where any unauthorized modification indicated.
- 4.Don't copy this report in partial (except full copy) without any official approval in written by our company. This report is invalid without re-stamping the special seal for testing in copying report.

5.Any holder of this document is advised that this report is for the exclusive use of Intertek's Customer and is provided pursuant to the agreement between Intertek and its Customer. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. This report was made with due care within the limitation of a defined scope of work and on the basis of information, materials and instructions received from the Customer or its nominated third parties. Intertek is under no obligation to refer to or report upon any facts or circumstances which are outside the specific instructions received and accepts no responsibility to any parties whatsoever, following the issue of the report, for any matters arising outside the agreed scope of the works. The tests results are not intended to be a recommendation for any particular course of action. Customer is responsible for acting as it sees fit on the basis of such results.

6.Intertek's written consent is required to use Intertek's name or logo on the object, product or service being tested. The observations and test results in this report relate only to the sample under test. This report alone does not indicate that the item, product or service has passed any Intertek certification program.



Intertek Testing Services Shenzhen Ltd. Shanghai Fengxian Branch Plant 5, No. 6958 Daye Road, Fengxian District, Shanghai, China Tel: 021-61136116 Fax: 021-61189921

Website: www.intertek.com

Test Report

Issue Date: 2019-08-16 Intertek Report No. 190725010SHF-001-R1

Applicant: Godfrey Hirst

Address: 7 Factories Road South Geelong Victoria Australia 3220

Attn: Mandy Chandley

Test Type: Performance test, samples provided by the applicant.

Product Information

| Product Name | GH Engineered Timber 14/3mm -Pioneer | | Brand | / |
|---------------------|--------------------------------------|----------------|----------------------------------|------------------------|
| Sample | | Good Condition | Sample Amount | 15 m ² |
| Description | | good Condition | Received Date | 2019-07-23; 2019-07-25 |
| Sample ID | | Model | Specification | |
| S190725010SHF.001 | | / | Engineered Timber: 1820x136x14mm | |
| S190725010SHF.002 | | / | Foam (| underlay: 2mm |

Test Methods And Standards

| Test Standard | ISO 10140-3:2010+A1-2015 |
|---------------------------|--|
| Specification Standard | ISO 717-2:2013 |
| Test Conclusion | The samples were tested according to the above standards, and the results are shown in the following page. |

Note:

Report Authorized

Name: Jodie Zhou

Title: Reviewer

Version: 1 May 2019

Nicole Shi Title: Project Engineer

Page 3 of 7 LFT-APAC-SHF-OP-10k

^{1.} This report relates specifically to the sample(s) that were drawn and provided by the applicant or their nominated third party. The reported result(s) provide no warranty or verification on the sample(s) representing any specific goods and/or shipment and only relate to the sample(s) as received and tested.



Issue Date: 2019-08-16 Intertek Report No. 190725010SHF-001-R1

Test Items, Method and Results:

Test method: ISO 10140-3:2010+A1-2015

Temperature: 29 °C Relative Humidity: 90 % Volume of the receiving room: 112 m^3


Volume of the source room: 77 m^3 $\frac{\text{Volume of the receiving room}}{\text{(Length × Width × Height)}}$ $\frac{122 \text{ m}}{\text{(5.7m × 4.9m × 4.0m)}}$

Specimen area: 12.4 m² Static pressure: 101.3 kPa

Floor assembly: The system consisted of 150mm thick concrete slab and 14.3mm GH Engineered

Timber with 1.95mm foam (density: 0.28kg/m²) underlay.

| Frequency (Hz) | Ln,0 (dB) | ΔL (dB) |
|-------------------|--------------|------------|
| 100 | 63.0 | 3.0 |
| 125 | 66.0 | 4.0 |
| 160 | 63.8 | 4.4 |
| 200 | 64.2 | 4.6 |
| 250 | 64.3 | 4.8 |
| 315 | 65.1 | 4.9 |
| 400 | 63.8 | 6.4 |
| 500 | 65.1 | 9.7 |
| 630 | 64.9 | 13.1 |
| 800 | 65.1 | 14.6 |
| 1000 | 64.6 | 15.8 |
| 1250 | 64.3 | 17.3 |
| 1600 | 64.0 | 20.8 |
| 2000 | 63.7 | 23.0 |
| 2500 | 62.1 | 25.0 |
| 3150 | 60.7 | 26.8 |



Rating according to ISO 717-2:2013, the ΔLw was shown below.

| Weighted improvement of impact sound insulation | ΔLw= | 18 | dB | |
|---|-------------------|----|----|--|
| Spectrum adaptation | C _{I∆} = | -8 | dB | |

Note:

- 1. These results are based on test made with an artificial source under laboratory conditions .
- 2. Ln,0 = Normalized Sound Pressure Level for Bare standard concrete floor

 ΔL = Reduction of impact sound pressure level after floor covering

 Δ Lw = Weighted reduction of impact sound pressure level

 $C_{I\Delta}$ = Spectrum adaptation term

3. The result was for the laminate floor with foam underlay assembly. The floor and the foam underlay were supplied by the applicant.



Issue Date: 2019-08-16 Intertek Report No. 190725010SHF-001

Test Items, Method and Results:

Test method: ISO 10140-3:2010+A1-2015

Temperature: 29 °C Relative Humidity: 90 %


Volume of the source room: 77 m^3 Volume of the receiving room: 112 m^3 (Length × Width × Height) (5.7m × 4.9m)

(Length × Width × Height) (5.7m × 4.9m × 4.0m) Specimen area: 12.4 m^2 Static pressure: 101.3 kPa

Floor assembly: The system consisted of 150mm thick concrete slab and 14.3mm GH Engineered

Timber with 1.95mm foam (density: 0.28kg/m²) underlay.

| Frequency (Hz) | Ln (dB) |
|-------------------|------------|
| 100 | 60.0 |
| 125 | 62.0 |
| 160 | 59.4 |
| 200 | 59.6 |
| 250 | 59.5 |
| 315 | 60.2 |
| 400 | 57.4 |
| 500 | 55.4 |
| 630 | 51.8 |
| 800 | 50.5 |
| 1000 | 48.8 |
| 1250 | 47.0 |
| 1600 | 43.2 |
| 2000 | 40.7 |
| 2500 | 37.1 |
| 3150 | 33.9 |



Rating according to ISO 717-2:2013, the Ln,w was shown below.

| Weighted normalized impact sound pressure level | Ln,w= | 54 | dB | |
|---|------------------|----|----|--|
| Spectrum adaptation | C _I = | 0 | dB | |

Note:

- 1. These results are based on test made with an artificial source under laboratory conditions .
- 2. Ln = Normalized Sound Pressure Level for Covering over Floor System

Ln,w = Weighted normalized impact sound pressure level

C_I = Spectrum adaptation

3. The result was for the whole floor assembly. The floor and the foam underlay was supplied by the applicant.



Issue Date: 2019-08-16 Intertek Report No. 190725010SHF-001-R1

Test Photo:



Test Set Up



Issue Date: 2019-08-16 Intertek Report No. 190725010SHF-001-R1

Appendix A: Sample Received Photo



Revision:

| NO. | Date | Changes | Author | Reviewer |
|---------------------|------------|-----------------------------------|------------|------------|
| 190725010SHF-001 | 2019-08-15 | First issue | Nicole Shi | Jodie Zhou |
| 190725010SHF-001-R1 | 2019-08-16 | Modify specification description. | Nicole Shi | Jodie Zhou |