

Technical Data **wood Parquet "Basics III Standard"****Specifications**

construction	multilayer parquet, 1-strip plank WICANDERS® „Loc&Fold system“, bevel 4 sides
according standard	DIN EN 13489   2023-09
species	Oak
hardness (Brinell)	approx. 38 N/mm <sup>2</sup>
moisture content	7 % (± 2 %)
heat transmission resistance	approx. 0,10 m <sup>2</sup> K/W suitable for floor heating systems max. 26° C
fire resistance class	Dfl - s1 (normally inflammable)
emission of formaldehyde	class E1 (<0,1 ppm)

**Dimensions**

length	1900 mm
width	190 mm
thickness	14 mm
wear layer	2,5 mm , several renovations of the wear layer are possible
quantity pack	8 layers / pack = 2,888 m <sup>2</sup> occasionally, short lengths are possible
quantity pallet	40 packs / pallet = 115,520 m <sup>2</sup>

**Products**

82000340 "Hadsund"	rustic grading, whitel lacquered, brushed; black putty
82000342 "Copenhagen"	rustic grading, neutral lacquered, brushed; black putty
82001396 "Oldenburg"	wild country grading, natural oiled, brushed; dark brown putty
82001405 "Emden"	wild country grading, white oiled, brushed; dark brown putty
82001454 "Hannover"	wild country grading, natural oiled, brushed; dark brown putty
82001455 "Flensburg"	wild country grading, white oiled, brushed; dark brown putty

**WICANDERS**