

SAFETY DATA SHEET
SOLITHANE® S 113

Version: 1.6

Revision Date: 09/04/2018

Print Date: 06/21/2019

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: SOLITHANE® S 113

Product Use Description: Polymer

Synonyms: Polyurethane prepolymer

 Company: LANXESS Solutions US Inc.
 2 Armstrong Road
 Shelton, Ct
 06484
 United States of America (USA)
 Telephone: (US) +1 866-430-2775

 Emergency telephone number: CHEMTREC: (24 hours) 800-424-9300
 : US : 800-292-5898 (Technical Inquiries)

For additional emergency telephone numbers see section 16 of the Safety Data Sheet.

 Prepared by: Product Safety Department
 (US) +1 866-430-2775
 MSDSRequest@lanxess.com

Recommended use of the chemical and restrictions on use

Recommended use : Polymer

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

Form	liquid
Colour	light yellow
Odour	pungent

GHS Classification

 Acute toxicity (Inhalation) : Category 2
 Respiratory sensitisation : Category 1
 Skin sensitisation : Category 1
 Carcinogenicity : Category 2

SAFETY DATA SHEET
SOLITHANE® S 113

Version: 1.6

Revision Date: 09/04/2018

Print Date: 06/21/2019

GHS label elements

 Signal word : **Danger**

Hazard pictograms :


 Hazard statements : H317 May cause an allergic skin reaction.
 H330 Fatal if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H351 Suspected of causing cancer.

Other hazards : None

 Precautionary statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P284 Wear respiratory protection.
Response:
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P363 Wash contaminated clothing before reuse.
Storage:
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:

SAFETY DATA SHEET



SOLITHANE® S 113

Version: 1.6 Revision Date: 09/04/2018 Print Date: 06/21/2019

IARC Group 2B: Possibly carcinogenic to humans
m-tolylidene diisocyanate 26471-62-5
OSHA No component of this product present at levels greater than or
equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP Reasonably anticipated to be a human carcinogen
m-tolylidene diisocyanate 26471-62-5

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
m-tolylidene diisocyanate	26471-62-5	>= 5 - < 10 %

SECTION 4. FIRST AID MEASURES

- If inhaled
: Remove to fresh air.
: Give oxygen or artificial respiration if needed.
: Get medical attention immediately.
- In case of skin contact
: Remove contaminated clothing and shoes.
: Wash off with soap and plenty of water.
: Obtain medical attention.
- In case of eye contact
: Rinse immediately with plenty of water, also under the eyelids,
for at least 15 minutes.
: If symptoms persist, call a physician.
- If swallowed
: Get medical attention immediately.
- Most important symptoms and effects, both acute and delayed
: Lachrymation
: Breathing difficulties
: Sensitising effects
- Notes to physician
: Oxygen, if needed.
: For specialist advice physicians should contact the Poisons Information Service.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media
: Water spray
: Dry chemical

MAY 6.0 SDS 2013-2 NA G108

3 / 13

SDS Number: 40000002731

SAFETY DATA SHEET



SOLITHANE® S 113

Version: 1.6 Revision Date: 09/04/2018 Print Date: 06/21/2019

- Specific hazards during firefighting
: Burning produces irritant fumes.
: Exposure to decomposition products may be a hazard to health.
- Specific extinguishing methods
: Fight fire with normal precautions from a reasonable distance.
: If water is used, fog nozzles are preferable.
: Keep away from fire, sparks and heated surfaces.
: Use water spray to cool unopened containers.
: Do not discharge extinguishing waters into streams, rivers and lakes.
- Special protective equipment for firefighters
: In the event of fire, wear self-contained breathing apparatus.
: Body covering protective clothing, full "turn-out" gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures
: Evacuate personnel to safe areas.
: Wear suitable protective equipment.
- Environmental precautions
: Do not allow contact with soil, surface or ground water.
: Do not flush into surface water or sanitary sewer system.
- Methods and materials for containment and cleaning up
: Prevent further leakage or spillage if safe to do so. Ventilate the area. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Flush with plenty of water. Do not flush into surface water or sanitary sewer system.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling
: Handle in accordance with good industrial hygiene and safety practice.
: Handle and open container with care.
: Do not puncture.
: Slacken off drum bungs before heating to prevent any pressure build up.
: Use only with adequate ventilation.
: Avoid inhalation, ingestion and contact with skin and eyes.
: Wear suitable protective equipment.
: Wash thoroughly after handling.
: Do not eat, drink or smoke when using this product.
: Keep container closed when not in use.
: Allergic reactions may develop after inhalation of low concentrations, also several hours after exposure. Regular

MAY 6.0 SDS 2013-2 NA G108

4 / 13

SDS Number: 40000002731

SAFETY DATA SHEET

SOLITHANE® S 113

Version: 1.6
Revision Date: 09/04/2018
Print Date: 06/21/2019

medical checks, including lung function, are recommended for long term and repeated use of isocyanates.

- Conditions for safe storage : Keep container tightly closed.
Keep in a dry, cool and well-ventilated place.
Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.
- Materials to avoid : Alcohols, Strong oxidizing agents, Water

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
m-tolylidene diisocyanate	26471-82-5	C	0.02 ppm 0.14 mg/m ³	OSHA Z-1
		TWA	0.005 ppm	ACGIH
		STEL	0.02 ppm	ACGIH
		C	0.02 ppm 0.14 mg/m ³	OSHA Z-1
		TWA	0.005 ppm	OSHA P0
		STEL	0.02 ppm	OSHA P0
		TWA	0.02 ppm 0.15 mg/m ³	OSHA P0
		STEL	0.04 mg/m ³	OSHA P0
		TWA	0.02 ppm	OSHA P0
		STEL	0.02 ppm	CAL PEL
		C	0.02 ppm 0.15 mg/m ³	CAL PEL
		PEL	0.02 ppm	CAL PEL
		TWA (Inhalable fraction and vapor)	0.005 ppm 0.04 mg/m ³	ACGIH
		STEL (Inhalable fraction and vapor)	0.001 ppm	ACGIH
			0.005 ppm	ACGIH

Biological occupational exposure limits

949 6.0 808 2013-2 NA G18
5 / 13
SDS Number: 4000000731

SAFETY DATA SHEET

SOLITHANE® S 113

Version: 1.6
Revision Date: 09/04/2018
Print Date: 06/21/2019

Component	CAS-No.	Control parameters	Sampling time	Sampling time	Permissible concentration	Basis
-----------	---------	--------------------	---------------	---------------	---------------------------	-------

Engineering measures : Maintain air concentrations below occupational exposure standards.
Ensure that extracted air cannot be returned to the workplace through the ventilation system.
Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Respirator with combination filter for vapour/particulate

Hand protection

Remarks : Before removing gloves clean them with soap and water.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Material

: Nitrile rubber

Break through time

: > 480 min

Glove thickness

: 0.4 - 0.8 mm

Eye protection

: Safety glasses with side-shields or
Safety goggles

Skin and body protection

: Impervious clothing

Hygiene measures

: Purge open drums with nitrogen before resealing.
Allergic reactions may develop after inhalation of low concentrations, also several hours after exposure. Regular medical checks, including lung function, are recommended for long term and repeated use of isocyanates.
Wash hands before breaks and at the end of workday.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

949 6.0 808 2013-2 NA G18
6 / 13
SDS Number: 4000000731

SAFETY DATA SHEET

SOLITHANE® S 113

Version: 1.6 Revision Date: 09/04/2018 Print Date: 06/21/2019

Appearance : liquid
Color : light yellow
Odor : pungent
Odour Threshold : No data available
pH : Not applicable
Melting point/range : Not applicable
Boiling point/boiling range : No data available
Evaporation rate : No data available
Flash point : 150 - 175 °C
Method: closed cup

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Relative density : 1.073
Density : No data available
Solubility(ies)
Water solubility : No data available
Solubility in other solvents : soluble
Solvent: Tetrahydrofuran

soluble
Solvent: Dimethylformamide

Partition coefficient: n-octanol/water : No data available
Auto-ignition temperature : No data available
Thermal decomposition : No data available
Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : No data available

Molecular weight : No data available

SAFETY DATA SHEET

SOLITHANE® S 113

Version: 1.6 Revision Date: 09/04/2018 Print Date: 06/21/2019

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Hazardous polymerisation does not occur.
Conditions to avoid : Exposure to moisture
Incompatible materials : Alcohols
Strong oxidizing agents
Water
Hazardous decomposition products : Carbon oxides
Nitrogen oxides (NO_x)
Hydrocarbons
Isocyanates

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate: 1.11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

m-tolylidene diisocyanate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity

LD50 (Rat): 0.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity

LD50 (Rabbit): > 9,400 mg/kg

Skin corrosion/irritation

Components:

m-tolylidene diisocyanate:

Species: Rabbit
Result: Severe skin irritation

SAFETY DATA SHEET



SOLITHANE® S 113

Version: 1.6 Revision Date: 09/04/2018 Print Date: 06/21/2019

Serious eye damage/eye irritation

Components:

m-tolylidene diisocyanate:

Species: Rabbit

Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Components:

m-tolylidene diisocyanate:

Species: Guinea pig

Assessment: May cause sensitisation by skin contact.

Result: Causes sensitisation.

Carcinogenicity

IARC

Group 2B: Possibly carcinogenic to humans

m-tolylidene diisocyanate

26471-62-5

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reasonably anticipated to be a human carcinogen

m-tolylidene diisocyanate

26471-62-5

Further information

Product:

Remarks: The product itself has not been tested.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

m-tolylidene diisocyanate:

Toxicity to fish

LC50 (Pimephales promelas (fathead minnow)): 147 mg/l
Exposure time: 48 hLC50 (Oncorhynchus mykiss (rainbow trout)): 133 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates

LC50 (Grass shrimp (Palaeomonetes pugio)): > 508 mg/l
Exposure time: 48 h

EC50 (Daphnia magna (Water flea)): 12.5 mg/l

NAF 6.0 RHM 2012-2 NA G109

9 / 13

SDS Number: 40000002731



SAFETY DATA SHEET

SOLITHANE® S 113

Version: 1.6 Revision Date: 09/04/2018 Print Date: 06/21/2019

Exposure time: 48 h

Toxicity to algae

EC50 Chlorella vulgaris (Fresh water algae): 4,300 mg/l
Exposure time: 96 h

Persistence and degradability

Product:

Biodegradability

Result: No data available

Bioaccumulative potential

Product:

Bioaccumulation

Remarks: No data available

Mobility in soil

Product:

Mobility

Remarks: No data available

Other adverse effects

Product:

Results of PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

Additional ecological information

There is no data available for this product.

The product itself has not been tested.
The following information is applicable to a component of this material:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

Waste must be classified and labelled prior to recycling or disposal.
In well ventilated area, fill drums with several centimeters of water. Leave drum open and slowly shake and roll to allow water contact. Leave open to air for sufficient time to cure. Dispose of waste product or used containers according to local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.

NAF 6.0 RHM 2012-2 NA G109

10 / 13

SDS Number: 40000002731

SAFETY DATA SHEET



SAFETY DATA SHEET

SOLITHANE® S 113

Version: 1.6
Revision Date: 09/04/2018
Print Date: 06/21/2019

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR	
UNID No.	
Proper shipping name	: UN 2206
	: Isocyanates, toxic, n.o.s.
	: (m-tolylidene diisocyanate)
Class	: 6.1
Packing group	: III
Labels	: Toxic
IMDG-Code	
UN number	: UN 2206
Proper shipping name	: ISOCYANATES, TOXIC, N.O.S.
	: (m-tolylidene diisocyanate)
Class	: 6.1
Packing group	: III
Labels	: 6.1
EmS Code	: F-A, S-A
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

National Regulations

49 CFR	:	UN 2206
UN/NA number	:	ISOCYANATES, TOXIC, N.O.S.
Proper shipping name	:	(m-tylilidene diisocyanate)
	:	6.1
Class	:	III
Packing group	:	TOXIC
Labels	:	155
ERG Code	:	no
Marine pollutant	:	

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
m-tolylidene diisocyanate	26471-62-5	100	1414

8AP 6.0 SDS 2012-2 NA GH3 11/13 RIDG Number: 40000002711

SAP 6.0 808 2012-7 N4 GHS

12/13

SDS Number: 400000002731

Version: 1.6
Revision Date: 09/04/2018
Print Date: 06/21/2019

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313
: The following components are subject to reporting levels established by SARA Title III, Section 313:
m-tolylidene diisocyanate 26471-62-5

US State Regulations

California Prop. 65

WARNING: This product can expose you to chemicals including m-tolylidene diisocyanate, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Please note that Section 3 of this document lists only the hazardous components required by the specific country or region hazard communication regulations. The chemical identifiers listed in Section 3 are used globally for hazard communication purposes and may not reflect those used for chemical inventory coverage in a particular country or region. The chemical inventory information given in Section 15 of this document applies to the product as a whole and should be used when evaluating inventory compliance.

The components of this product are reported in the following inventories:

DSL	All components of this product are in compliance with the inventory
ACS	On the inventory, or in compliance with the inventory
NZRoC	Not in compliance with the inventory
ENCS	Not in compliance with the inventory
KECI	On the inventory, or in compliance with the inventory
PICCS	Not in compliance with the inventory
IECCS	On the inventory, or in compliance with the inventory
TCsl	On the inventory, or in compliance with the inventory
US.TSCA	On TSCA inventory

SECTION 16. OTHER INFORMATION

Further Information

Other Emergency Phone Number

SAP 6.0 SDS 2012-2 NA GH9

SAP 6.0 808 2012-7 N4 GHS

12/13

SDS Number: 400000002731

SAFETY DATA SHEET



SOLITHANE® S 113

Version: 1.8	Revision Date: 09/04/2018	Print Date: 06/21/2019
Latin America:	Brazil	+55 113 711 9144
	All other countries	+44 (0) 1235 239 670
Mexico:		+52 555 004 8763

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: SOLITHANE® C 113 300

Product Use Description: Used in polyurethane manufacturing.

Synonyms: Castor oil

Company: LANXESS Solutions US Inc.
2 Armstrong Road
Shelton, CT 06484
United States of America (USA)
Telephone: (US) +1 866-430-2775

Emergency telephone number: CHEMTREC: (24 hours) 800-424-9300
US: 800-292-5888 (Technical inquiries)

Prepared by: For additional emergency telephone numbers see section 18 of the Safety Data Sheet.

Product Safety Department (US) +1 866-430-2775
MSDSRequest@lanxess.com

Recommended use of the chemical and restrictions on use
Recommended use: Used in polyurethane manufacturing.
Restrictions on use: Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

Form	oil liquid
Colour	light yellow
Odour	slight

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

Other hazards: None

Not a hazardous substance or mixture.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Castor oil	8001-79-4	>= 90 <= 100 %

SECTION 4. FIRST AID MEASURES

- If inhaled: Remove to fresh air. If symptoms persist, call a physician.
- In case of skin contact: Wash off with warm water and soap.
- In case of eye contact: Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.
- If swallowed: Do NOT induce vomiting. Rinse mouth with water. Obtain medical attention.
- Most important symptoms and effects, both acute and delayed: No information available.
- Notes to physician: No information available.

SECTION 5. FIREFIGHTING MEASURES

SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

Suitable extinguishing media : Extinguishing media - large fires
Alcohol-resistant foam
(on small fires)
Carbon dioxide (CO₂)
Dry chemical
Water spray

Unsuitable extinguishing media : Water spray jet

Specific hazards during firefighting : Burning produces irritant fumes.
Exposure to decomposition products may be a hazard to health.

Specific extinguishing methods : Prevent fire extinguishing water from contaminating surface water or the ground water system.

Special protective equipment for firefighters : Body covering protective clothing, full "turn-out" gear.
Self-contained breathing apparatus (EN 133)

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Wear suitable protective equipment.

Environmental precautions : Do not allow contact with soil, surface or ground water.
Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Large spills should be collected mechanically (remove by pumping) for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice.
Avoid contact with skin, eyes and clothing.
Use with adequate ventilation.

Conditions for safe storage : Keep in a dry, cool place.

SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Castor oil	8001-79-4	TWA (mist - total)	10 mg/m ³	NIOSH REL
		TWA (mist - respirable)	5 mg/m ³	NIOSH REL

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection : Impervious gloves

Eye protection : Safety glasses with side-shields

Skin and body protection : Preventive skin protection

Hygiene measures : Use with adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : oily liquid

Color : light yellow

Odor : slight

Odour Threshold : No data available

pH : Not applicable

Melting point/range : Not applicable

Boiling point/boiling range : No data available

Evaporation rate : No data available

Flash point : 200 - < 250 °C
Method: closed cup

Upper explosion limit : No data available

SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

Lower explosion limit : No data available
 Vapour pressure : No data available
 Relative vapour density : No data available
 Relative density : 0.96
 Density : No data available
Solubility(ies)
 Water solubility : Insoluble
 Solubility in other solvents : No data available
 Partition coefficient: n-octanol/water : No data available
 Auto-ignition temperature : No data available
 Thermal decomposition : No data available
 Viscosity :
 Viscosity, kinematic : No data available
 Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.
 Chemical stability : Stable under normal conditions.
 Possibility of hazardous reactions : Hazardous polymerisation does not occur.
 Conditions to avoid : Extremes of temperature and direct sunlight.
 Incompatible materials : Strong oxidizing agents
 Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Germ cell mutagenicity

Components:
 Castor oil:

NAF 6.0 308 2012-2 NA G188

5 / 9

SDS Number: 40000002727

SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

Genotoxicity in vitro : Test Type: Ames test
 Result: negative
 : Test Type: Chinese Hamster Ovary (CHO)
 Result: negative
 Genotoxicity in vivo : Test Type: In vivo micronucleus test
 Result: negative
 Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.
 Carcinogenicity
 IARC : No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
 OSHA : No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
 NTP : No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

STOT - repeated exposure

Components:

Castor oil:
 Exposure routes: Oral
 Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity

Product:

No aspiration toxicity classification

Further information

Product:

Remarks: There is no data available for this product.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

NAF 6.0 308 2012-2 NA G188

6 / 9

SDS Number: 40000002727



SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

Remarks: No data available

Persistence and degradability

Product:

Biodegradability

: Remarks: No data available

Product:

Bioaccumulative potential

Biocumulation

: Remarks: No data available

Mobility in soil

Product:

Mobility

: Remarks: No data available

Other adverse effects

Product:

Results of PBT and vPvB assessment

: This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

Additional ecological information

: There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Dispose of waste material in compliance with all federal, state, and local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SAF 6.0 SDS 2012-2 NA GHS SDS Number: 4000000727 7 / 9



SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

WHMIS Classification

: Not Rated

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: No SARA Hazards

SARA 302

: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Please note that Section 3 of this document lists only the hazardous components required by the specific country or region hazard communication regulations. The chemical identifiers listed in Section 3 are used globally for hazard communication purposes and may not reflect those used for chemical inventory coverage in a particular country or region. The chemical inventory information given in Section 15 of this document applies to the product as a whole and should be used when evaluating inventory compliance.

The components of this product are reported in the following inventories:
DSL

All components of this product are on the Canadian DSL

SAF 6.0 SDS 2012-2 NA GHS SDS Number: 4000000727 8 / 9

SAFETY DATA SHEET

SOLITHANE® C 113 300

Version: 1.5 Revision Date: 09/04/2018 Print Date: 06/21/2019

AICS	On the inventory, or in compliance with the inventory
NZIoC	Not in compliance with the inventory
ENCS	On the inventory, or in compliance with the inventory
KECI	On the inventory, or in compliance with the inventory
PICCS	On the inventory, or in compliance with the inventory
IECSC	On the inventory, or in compliance with the inventory
TCSI	On the inventory, or in compliance with the inventory
US.TSCA	On TSCA inventory

SECTION 16. OTHER INFORMATION

Further information

Other Emergency Phone Number

Latin America:	Brazil	+55 113 711 9144
	All other countries	+44 (0) 1235 239 670
Mexico:		+52 555 004 8763

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.