

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) Q4-2817 FLUOROSILICONE SEALANT

Product code : 000000000001666789

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Construction materials and additives

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Skin corrosion : Category 1C

Serious eye damage : Category 1

Reproductive toxicity : Category 2

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version 1.0	Revision Date: 02/09/2015	MSDS Number: 971236-00001	Date of last issue: - Date of first issue: 02/09/2015
----------------	------------------------------	------------------------------	--

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P261 In case of fire: Avoid breathing fume.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture
Chemical nature	: Fluorosilicone elastomer

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Hexamethyldisilazane reaction with Silica	68909-20-6	>= 5 - < 10
Ethyltriacetoxysilane	17689-77-9	>= 1 - < 5
Methyltriacetoxysilane	4253-34-3	>= 1 - < 5
Trifluoropropylmethyl cyclotrisiloxane	2374-14-3	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version 1.0	Revision Date: 02/09/2015	MSDS Number: 971236-00001	Date of last issue: - Date of first issue: 02/09/2015
----------------	------------------------------	------------------------------	--

- | | |
|---|--|
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention immediately.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, both acute and delayed | : Causes digestive tract burns.
Causes serious eye damage.
Suspected of damaging fertility or the unborn child.
Causes severe burns. |
| Protection of first-aiders | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists. |
| Notes to physician | : Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | |
|---------------------------------------|---|
| Suitable extinguishing media | : Water spray
Alcohol-resistant foam
Dry chemical
Carbon dioxide (CO ₂) |
| Unsuitable extinguishing media | : None known. |
| Specific hazards during fire fighting | : Very toxic vapors are evolved.
Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : Carbon oxides
Silicon oxides
Fluorine compounds
Formaldehyde
Nitrogen oxides (NO _x)
Metal oxides |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers. |

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version 1.0 Revision Date: 02/09/2015 MSDS Number: 971236-00001 Date of last issue: -
Date of first issue: 02/09/2015

Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Organic peroxides
Explosives

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hexamethyldisilazane reaction with Silica	68909-20-6	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
Trifluoropropylmethyl cyclotrisiloxane	2374-14-3	TWA	5 ppb	DCC OEL
Further information: Skin				

Hazardous components without workplace control parameters

Ingredients	CAS-No.
Ethyltriacetoxysilane	17689-77-9
Methyltriacetoxysilane	4253-34-3

Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetic acid	64-19-7	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		ST	15 ppm 37 mg/m ³	NIOSH REL
		TWA	10 ppm 25 mg/m ³	NIOSH REL
		TWA	10 ppm 25 mg/m ³	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
Use with local exhaust ventilation.
Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at work-

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version 1.0	Revision Date: 02/09/2015	MSDS Number: 971236-00001	Date of last issue: - Date of first issue: 02/09/2015
----------------	------------------------------	------------------------------	--

places have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material

: Rubber or plastic gloves

Remarks

: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection

: Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection

: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures

: Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Color	: red
Odor	: Acetic acid
Odor Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: > 101.1 °C Method: closed cup
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: No data available
Relative density	: 1.8
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	: Exposure to moisture.
Incompatible materials	: Oxidizing agents Water
Hazardous decomposition products	
Contact with water or humid air	: Acetic acid
Thermal decomposition	: Formaldehyde Trifluoropropionaldehyde Hydrogen fluoride

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

Ingredients:

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

Hexamethyldisilazane reaction with Silica:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Ethyltriacetoxysilane:

Acute oral toxicity : LD50 (Rat): 380 mg/kg
Remarks: Based on test data

Methyltriacetoxysilane:

Acute oral toxicity : LD50 (Rat): 1,550 mg/kg
Remarks: Based on test data

Trifluoropropylmethyl cyclotrisiloxane:

Acute oral toxicity : LD50 (Rat): 4,650 mg/kg
Remarks: Based on test data

Acute inhalation toxicity : LC50 (Rat): > 13.44 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on test data

Skin corrosion/irritation

Causes severe burns.

Ingredients:**Hexamethyldisilazane reaction with Silica:**

Assessment: Repeated exposure may cause skin dryness or cracking.

Ethyltriacetoxysilane:

Species: Rabbit
Result: Corrosive after 3 minutes to 1 hour of exposure
Remarks: Information taken from reference works and the literature.

Methyltriacetoxysilane:

Species: Rabbit
Result: Corrosive after 1 to 4 hours of exposure
Remarks: Based on test data

Trifluoropropylmethyl cyclotrisiloxane:

Species: Rabbit
Result: No skin irritation
Remarks: Based on test data

Serious eye damage/eye irritation

Causes serious eye damage.

Ingredients:**Hexamethyldisilazane reaction with Silica:**

Species: Rabbit

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version 1.0	Revision Date: 02/09/2015	MSDS Number: 971236-00001	Date of last issue: - Date of first issue: 02/09/2015
----------------	------------------------------	------------------------------	--

Result: No eye irritation
Remarks: Based on data from similar materials

Ethyltriacetoxysilane:

Result: Irreversible effects on the eye
Remarks: Expert judgment

Methyltriacetoxysilane:

Species: Rat
Result: Irreversible effects on the eye
Remarks: Based on test data

Trifluoropropylmethyl cyclotrisiloxane:

Species: Rabbit
Result: No eye irritation
Remarks: Based on test data

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.
Respiratory sensitization: Not classified based on available information.

Ingredients:**Trifluoropropylmethyl cyclotrisiloxane:**

Assessment: Does not cause skin sensitization.

Test Type: Buehler Test

Species: Guinea pig

Remarks: No known sensitising effect.

Based on test data

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Hexamethyldisilazane reaction with Silica:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Trifluoropropylmethyl cyclotrisiloxane:

Genotoxicity in vitro : Test Type: Mutagenicity (in vitro mammalian cytogenetic test)
Result: negative
Remarks: Based on test data

: Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on test data

Carcinogenicity

Not classified based on available information.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version 1.0	Revision Date: 02/09/2015	MSDS Number: 971236-00001	Date of last issue: - Date of first issue: 02/09/2015
----------------	------------------------------	------------------------------	--

human carcinogen by IARC.

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Ingredients:**Trifluoropropylmethyl cyclotrisiloxane:**

Effects on fertility : Application Route: Skin contact
Symptoms: Effects on fertility.
Remarks: Based on test data

Application Route: Ingestion
Symptoms: Effects on fertility.
Remarks: Based on test data

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**Trifluoropropylmethyl cyclotrisiloxane:**

Routes of exposure: Ingestion
Target Organs: Heart, Musculo-skeletal system
Assessment: Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

Routes of exposure: Skin contact
Target Organs: Liver
Assessment: Shown to produce significant health effects in animals at concentrations of >20 to 200 mg/kg bw.

Repeated dose toxicity**Ingredients:****Trifluoropropylmethyl cyclotrisiloxane:**

Species: Rat
Application Route: Ingestion
Target Organs: Heart, Musculo-skeletal system
Remarks: Based on test data

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

Species: Rat
Application Route: Skin contact
Target Organs: Liver
Remarks: Based on test data

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Ethyltriacetoxysilane:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 251 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp.): 62 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to bacteria : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Methyltriacetoxysilane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 122 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 120 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to bacteria : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

Persistence and degradability**Ingredients:****Ethyltriacetoxysilane:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74 %
Exposure time: 21 d

Stability in water : Degradation half life: < 13 s pH: 7

Methyltriacetoxysilane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74 %
Exposure time: 21 d
Method: C.4-A of the COUNCIL REGULATION (EC) No 440/2008
Remarks: Based on data from similar materials

Stability in water : Degradation half life: < 12 s pH: 7
Remarks: Based on test data

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International Regulation**

UNRTDG

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

UN number : UN 1759
Proper shipping name : CORROSIVE SOLID, N.O.S.
(Ethyltriacetoxysilane, Methyltriacetoxysilane)
Class : 8
Packing group : III
Labels : 8

IATA-DGR

UN/ID No. : UN 1759
Proper shipping name : Corrosive solid, n.o.s.
(Ethyltriacetoxysilane, Methyltriacetoxysilane)
Class : 8
Packing group : III
Labels : Corrosive
Packing instruction (cargo aircraft) : 864
Packing instruction (passenger aircraft) : 860

IMDG-Code

UN number : UN 1759
Proper shipping name : CORROSIVE SOLID, N.O.S.
(Ethyltriacetoxysilane, Methyltriacetoxysilane)
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number : UN 1759
Proper shipping name : CORROSIVE SOLIDS, N.O.S.
(Ethyltriacetoxysilane, Methyltriacetoxysilane)
Class : 8
Packing group : III
Labels : CORROSIVE
ERG Code : 154
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version 1.0	Revision Date: 02/09/2015	MSDS Number: 971236-00001	Date of last issue: - Date of first issue: 02/09/2015
----------------	------------------------------	------------------------------	--

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations**Pennsylvania Right To Know**

Trifluoropropylmethyl siloxane, hydroxy-terminated	68607-77-2	50 - 70 %
Iron oxide	1332-37-2	30 - 50 %
Hexamethyldisilazane reaction with Silica	68909-20-6	5 - 10 %
Ethyltriacetoxysilane	17689-77-9	1 - 5 %

New Jersey Right To Know

Trifluoropropylmethyl siloxane, hydroxy-terminated	68607-77-2	50 - 70 %
Iron oxide	1332-37-2	30 - 50 %
Hexamethyldisilazane reaction with Silica	68909-20-6	5 - 10 %
Ethyltriacetoxysilane	17689-77-9	1 - 5 %
Methyltriacetoxysilane	4253-34-3	1 - 5 %

California Prop 65 : This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

REACH	: All ingredients (pre-)registered or exempt.
TSCA	: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
NZIoC	: All ingredients listed or exempt.

Inventories

DOW CORNING(R) Q4-2817 FLUOROSILICONE SEALANT


Version 1.0 Revision Date: 02/09/2015 MSDS Number: 971236-00001 Date of last issue: -
Date of first issue: 02/09/2015

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
DCC OEL	: Dow Corning Guide
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
DCC OEL / TWA	: Time weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 02/09/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid

**DOW CORNING(R) Q4-2817
FLUOROSILICONE SEALANT**

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	02/09/2015	971236-00001	Date of first issue: 02/09/2015

when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8