

# CIM 1061

## HIGH PERFORMANCE COATINGS AND LININGS

### OVERVIEW

**DESCRIPTION** CIM 1061 is a tough, abrasion, corrosion and chemical resistant, liquid applied coating specifically for use in water and wastewater applications including those which require ANSI/NSF 61 potable water certification. Typical applications for this two component elastomeric urethane coating include tank and reservoir liners, joint seals, tank repairs, and chemical containment.

**ADVANTAGES** CIM 1061 is one of the toughest coatings available, specifically formulated to meet the demanding needs of the water/wastewater industries:

- Ideal for coating concrete.
- ANSI/NSF 61 certified for potable water contact up to 180°F.
- Tested to ANSI 118.10-199, "Standard Specification for Load Bearing, Bonded, Waterproof Membrane for Thin-Set Ceramic Tile and Dimension Stone Installation".
- Forms a tough elastomeric coating able to bridge cracks and joints.
- Meets the most demanding health and safety requirements for drinking water, fish hatcheries, and food processing plants.
- Adheres to and bridges between common construction materials such as concrete, steel, glass, wood, and most coatings.
- Environmentally sound, complying with the toughest VOC standards.
- Can be repaired when damaged or when new tank penetrations are installed.
- Excellent wear and abrasion service.
- UV stable.
- Liquid, two-component urethane can be applied to complex tanks with multiple penetrations, and irregular shapes.

### SURFACE PREPARATION

- GENERAL:** Substrates must be **clean and dry** with no oils, grease or loose debris. CIM Bonding Agent is recommended on all non-porous substrates. Perform adhesion tests to confirm adequacy of surface preparation. See C.I.M. Industries' specific substrate Instruction Guide for specific guidelines.
- CONCRETE:** ICRI-CSP 4-6 concrete surface profile exposing aggregate. Concrete must exhibit minimum 3,000 psi compressive strength and be free of release agents and curing compounds. The substrate must be clean and dry (see CIM Instruction Guide IG-2), and free of contaminants.
- STEEL:** Minimum 3 mil profile.  
Immersion service – SSPC-SP10 / NACE No. 2 Near White Blast.  
Non-Immersion service – SSPC-SP6 / NACE No. 3 Commercial Blast.  
Use CIM Bonding Agent for greater adhesion.
- OTHER METALS:** SSPC-SP1 solvent clean and abrasive blast to roughen and degloss the surface. Use CIM Bonding Agent for greater adhesion.
- GLASS:** Thoroughly clean. CIM Bonding Agent must be used for increased adhesion. For immersion service roughen the surface.
- WOOD:** Substrate must be clean, dry and free of surface contamination.
- PREVIOUS COATINGS AND LININGS:** CIM 1061 may be applied over some existing coatings and linings and achieve acceptable performance. CIM Bonding Agent is recommended for greater adhesion. Finished system results vary due to a variety of project specific factors, including the service conditions to which the system is exposed. Therefore, C.I.M. Industries does not accept responsibility for determining the suitability of an existing coating or lining as a substrate for CIM products. Owner shall perform adhesion tests on any existing coating or lining to determine suitability.
- EARTH:** Use CIM Scrim.
- COLOR** CIM 1061 is initially shiny black, turning dull over 3 to 6 months when exposed to direct sunlight. For a colored or reflecting surface finish, see C.I.M. Industries' Instruction Guide, "Topcoats" (IG-7) for further instructions.
- SOLIDS BY VOLUME** 88% (1416 dry mills x sq. ft./gal.)
- VOC** 90 g/l (0.75 lb./gal.). CIM 1061 complies with the toughest VOC regulations.



# CIM 1061

## HIGH PERFORMANCE COATINGS AND LININGS

All information presented in this publication is believed to be accurate, but it is not to be construed as a guarantee of minimum performance. Test performance results are obtained in a controlled laboratory environment using procedures that may not represent actual operating environments.

### TYPICAL PROPERTIES

Abrasion Resistance - Wt. Loss Taber Abraser CS-17 Wheel 1000 gr./1000 rev. ASTM D4060	1.2 mg. Loss	Liner Weight (60 mils wet film thickness)	31 lbs./100 sq. ft.
Adhesion to concrete (dry) Elcometer	350 psi	Mix Ratio Weight Volume	6.2:1 7.8:1
Deflection Temperature ASTM D648	below -60°F	Mullen Burst Strength, ASTM D751, 50 mil	150 psi
Density (Approx.) Premix Activator Mixed & Cured	8.0 lbs./gal. 10.1 lbs./gal. 8.3 lbs./gal.	Permeability to Water Vapor ASTM E96 Method E, 100°F, 100 mil sheet	0.03 perms
Elastomeric Waterproofing ASTM C836 ASTM C957	exceeds all criteria exceeds all criteria	Potable Water Service ANSI/NSF 61 to 180°F UL File Number - MH17445 WQA Certified	
Extension to Break, ASTM D412	300%	Recovery from 100% extension: after 5 minutes after 24 hours	98% 100%
Flooring and Shower Lining UPC/IBC ANSI 118.10	Pass	Service Temperature	-60°F to 220°F
Green Roof Membrane/Root Barrier FLL, 2002	Pass	Softening Point, Ring & Ball ASTM D36	>325°F
Hardness, Shore A ASTM D2240 @ 77°F	65	Tear Strength ASTM D624 (Die C)	180 lbs./in.
Liner Performance Crack Bridging 10 cycles @ -15°F After heat aging	greater than 1/8" greater than 1/4"	Tensile Strength, ASTM D412, 100 mil sheet Weathering ASTM D822	1000 psi 5000 hrs.

### CHEMICAL RESISTANCE

CIM 1061 is resistant to a broad range of acids and alkalis. Consult C.I.M. Industries for additional information regarding chemical resistance after reviewing CIM 1061 Chemical Resistance Chart.

**THE INFORMATION PRESENTED IN THIS PUBLICATION IS SUBJECT TO CHANGE WITHOUT NOTICE.**

**CONTACT C.I.M. INDUSTRIES FOR CURRENT INFORMATION.**

[www.cimindustries.com](http://www.cimindustries.com)

---

### GENERAL APPLICATION INFORMATION

---

#### FOR PROFESSIONAL USE ONLY.

- PRECAUTIONS** Avoid contamination with water or moisture. Keep all pails and jugs tightly closed until ready for use. All equipment, air supplies, and application substrates must be **ABSOLUTELY DRY**. Do not apply in wet weather or when rain is imminent or when the CIM 1061 or the substrate may become wet within 4 hours after coating. Use caution when applying CIM 1061 in confined spaces. See C.I.M. Industries' Instruction Guide, "Applying CIM Within Confined Spaces" (IG-9).
- TEMPERATURE** Surface should be at least 50°F (10°C) and must be 5°F (3°C) above the dew point. **DO NOT APPLY WHEN THE SUBSTRATE OR AMBIENT TEMPERATURE IS RISING OR COATING IS IN DIRECT SUNLIGHT.** CIM 1061 should be at least 60°F (15°C) when mixed and applied. CIM 1061 may be preheated to facilitate application at low temperatures, but working time will be reduced. See C.I.M. Industries' Instruction Guide "Applying CIM Coatings in Cold Weather" (IG-11).
- EQUIPMENT** Spray equipment requires large diameter hose and air supplied mastic gun or plural component spray equipment. See "Spray Application of CIM" (IG-12) or contact C.I.M. Industries for specific recommendations. Roller, squeegee, and trowel may also be used.
- POT LIFE** About 30 minutes. Working time depends on temperature and method of application. Working time for spray applications will be significantly shorter.
- PRIMING** Porous substrates such as wood and concrete may be primed with CIM Epoxy Primer to minimize outgassing. The maximum recoat window for CIM Epoxy Primer is 48 hours. See the CIM Epoxy Primer Technical Data Sheet for additional information. Perform adhesion tests to confirm adequacy of adhesion to primer.
- MIXING** **DO NOT THIN. DO NOT HAND MIX.** Begin mixing each pail (4.4 gal.) of CIM 1061 Premix using a power mixer (e.g. ½" drill and an eight inch mud mixer). Do not draw air into the mix. While mixing, slowly add one jug (0.6 gal.) of CIM 1061 Activator to the pail and mix thoroughly for **3 FULL MINUTES**. The proportions are premeasured; **DO NOT ESTIMATE**. Mixing Jigs and Timers from C.I.M. Industries help eliminate mixing errors and increase productivity on the job. See C.I.M. Industries' Instruction Guide, "Mixing CIM Premix and Activator" (IG-8).
- APPLICATION** Apply CIM 1061 directly to a clean and dry substrate. Vertical surfaces will require multiple coats. See C.I.M. Industries' specific substrate Instruction Guide for additional guidelines.
- RECOATING** CIM 1061 may be recoated in 1 hour and must be recoated soon after the coating no longer comes off on polyethylene (typically within 4 hours of mixing). If the coating has cured longer than this time, the surface must be severely abraded using surface grinder or other mechanical means, and be free of dust and debris. Use CIM Bonding Agent for better adhesion. For immersion conditions, all coats shall be applied within four hours of each other, except at joint lines.
- RECOMMENDED MINIMUM THICKNESS** Recommended minimum thickness of the coating is 60 wet mils. Additional thickness may be specified, but extended time is required to insure proper solvent release prior to placing the liner in service. Contact C.I.M. Industries for detailed cure time information. Refer to CIM 1061 Coverage Chart for coverage rates.
- CURING TIME** Before placing the coating into potable water service or similar applications, allow sufficient time for solvents to release from the coating. The required time for a 60 wet mil coating is two weeks at 60°F (15°C) and varies depending upon coating thickness and substrate temperature. For many other applications, CIM 1061 may be placed into service in 24 hours. Contact C.I.M. Industries for specific recommendations.
- DISINFECTION** CIM 1061 coating must be washed, rinsed, and disinfected in accordance with C.I.M. Industries Instruction Guide "Decontamination or Washing Procedures for Potable Water Tank and Fish Pond Service" (IG-10).
- CLEAN-UP** Use mineral spirits for clean-up of uncured material. Spray equipment must be flushed regularly during application to prevent material from setting up in the hose and pump. Cured material is very difficult to remove. Soaking in solvent will soften the material and may assist in its removal.

**CONTACT C.I.M. INDUSTRIES FOR SPECIFIC RECOMMENDATIONS AND INSTRUCTION GUIDES.**

# CIM 1061

## HIGH PERFORMANCE COATINGS AND LININGS

---

### SHIPPING, STORAGE AND SAFETY DATA

---

<b>WARNING</b>	<b>Flammable. Use only in well ventilated areas. Do not store or use near open flame, sparks or hot surfaces. Keep tightly closed. Avoid contact with moisture or water. Keep out of reach of children.</b>		
<b>SAFETY INFORMATION</b>	This product contains petroleum asphalt, petroleum distillates, amine compounds and/or other chemical ingredients. Adequate health and safety precautions should be observed during the storage, handling, application and curing. Refer to C.I.M. Industries' Material Safety Data Sheets for further details regarding the safe use of this product.		
<b>PACKAGING</b>	CIM 1061 is available in mixed units of 0.8 gallons and 5 gallons. Each unit consists of a container of premix and a smaller container of activator. Quantities have been premeasured to provide the proper mixing ratio, leaving sufficient room in the premix container to facilitate adequate mixing. <b>Do not estimate proportions.</b>		
<b>SHIPPING</b>	<b>Premix</b>	<b>Activator</b>	
	<b>Weights</b>		
	0.8 gallon kits	6.6 lb/can (26 lb/box of 4)	1 lb/bottle (13 lb/carton of 12)
	5.0 gallon units	40 lb/pail	6.0 lb/jug (36 lb/case of 6)
	<b>Properties</b>		
	Flash Point	101°F	>400°F
	Shipping Name	Not Regulated*	Not Regulated
	DOT Class	Not Regulated*	Not Regulated
<b>STORAGE</b>			
	Temperature	20°F to 110°F	70°F to 95°F
	Shelf Life	2 years	1 year
	NFPA	Class II	Class III B

\* Reclassed based on container size and physical properties, see SDS for additional detail

#### WARRANTY & LIMITATION OF SELLER'S LIABILITY

C.I.M. Industries Inc. (C.I.M.) warrants that for a period of five (5) years from the date of shipment to the initial purchaser the products, when mixed in proper ratios for the proper length of time, (a) will not become brittle or crack and (b) will provide a water barrier. Due to application variables beyond C.I.M.'s control which may affect results, C.I.M. makes no warranty of any kind, expressed or implied, including that of merchantability, other than that the products conform to C.I.M.'s current quality control standards at time of manufacture. If breach of warranty is established, the buyer's exclusive remedy shall be repayment of the purchase price of the non-conforming CIM membrane product or, at C.I.M.'s option, resupply of conforming product to replace the non-conforming product. The buyer expressly waives any claim to additional damages, including consequential damages.

**THE INFORMATION PRESENTED IN THIS PUBLICATION IS SUBJECT TO CHANGE WITHOUT NOTICE.**

**CONTACT C.I.M. INDUSTRIES FOR CURRENT INFORMATION.**

**FOR PROFESSIONAL USE ONLY.**

**[www.cimindustries.com](http://www.cimindustries.com)**