

Version 1,5

Revision Date: 10/26/2017

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name** 

Isopropanol TT-I-735A NOT.3 Grade A

Recommended use of the chemical and restrictions on use

Recommended use

Alcohol solvent

Manufacturer or supplier's details

Company **Address** 

Nexeo Solutions, LLC.

3 Waterway Square Place Suite 1000

The Woodlands, TX. 77380 United States of America

Cage Code:

4N760

NSN

6810-00-543-7915, 6810-00-983-8551, 6810-00-286-5435,

6810-01-454-9527

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648) Health International: 1-855-NEXEO4U (1-855-639-3648) Transport North America: CHEMTREC (1-800-424-9300)

Additional Information:

Responsible Party: Product Safety Group

E-Mail: msds@nexeosolutions.com SDS Requests: 1-855-429-2661 SDS Requests Fax: 1-281-500-2370 Website: www.nexeosolutions.com

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids

: Category 2

Eye irritation

: Category 2A

Specific target organ toxicity

- single exposure

: Category 3 (Central nervous system)

**GHS Label element** 

Hazard pictograms





Signal word

: Danger

Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

: Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

SDS Number: 100000007753



Version 1.5

Revision Date: 10/26/2017

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Substance

# Hazardous components

CAS-No.	Chemical Name	Weight %
67-63-0	Isopropyl alcohol	90 - 100

Any Concentration shown as a range is due to batch variation.

**Synonyms** 

: Isopropyl alcohol,

# **SECTION 4. FIRST AID MEASURES**

General advice

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

SDS Number: 100000007753



Version 1.5

Revision Date: 10/26/2017

Do not leave the victim unattended.

If inhaled Consult a physician after significant exposure.

If unconscious place in recovery position and seek medical

advice.

In case of skin contact !! If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Do not induce vomiting without medical advice.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

: Carbon oxides

formaldehyde corrosive vapors

Nitrogen oxides (NOx)

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if nec-

essarv

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

SDS Number: 100000007753 3 / 12 Isopropanol TT-I-735A NOT.3 Grade A



Version 1.5

Revision Date: 10/26/2017

Personal precautions, protective equipment. tive equipment and emergency procedures

Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

**Environmental precautions** 

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Advice on safe handling

: Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes, For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood.

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

SDS Number: 100000007753



Version 1.5

CAS-No.	Components	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
67 <b>-</b> 63-0	Isopropyl alcohol	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0

# Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Revision Date: 10/26/2017

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance

; liquid

Colour

: Clear, Colorless

SDS Number: 100000007753



Version 1.5

Revision Date: 10/26/2017

Odour

: alcohol-like, characteristic

Odour Threshold

: 200 ppm

pН

: No data available

Freezing Point (Melting point/freezing point)

: -88 °C (-126 °F)

pointinecezing pointy

Boiling Point (Boiling point/boiling range)

82 - 83 °C (180 - 181 °F)

(1013 hPa)

Flash point

: 12 °C (54 °F)

Method: Tag closed cup

Evaporation rate

: < 3.9

(Butyl Acetate = 1)

Flammability (solid, gas)

: No data available

Upper explosion limit

: 13 %(V)

Lower explosion limit

: 2 %(V)

Vapour pressure

: 33 mmHg @ 20 °C (68 °F)

Relative vapour density

: < 2.1 @ 15 - 20 °C (59 - 68 °F)

(Air = 1.0)

Relative density

: 0.78 - 0.79 @ 20 °C (68 °F)

Reference substance: (water = 1)

Density

: 0.78 - 0.79 g/cm3 @ 20 °C (68 °F)

Solubility(ies)

Water solubility

: completely miscible

Solubility in other solvents

: No data available

Partition coefficient: n-

octanol/water

: log Pow: 0.05 @ 25 °C (77 °F)

Auto-ignition temperature

: 399 - 425 °C

Thermal decomposition

: No data available

Viscosity

Viscosity, dynamic

: 2.4 mPa.s @ 20 °C (68 °F)

Viscosity, kinematic

: 2.66 mm2/s @ 25 °C (77 °F)

Surface tension

: 22,7 mN/m, 20 °C



Version 1.5 Revision Date: 10/26/2017

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity 5 No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

Incompatible materials

tions

: Vapours may form explosive mixture with air.

Conditions to avoid Keep away from heat, flame, sparks and other ignition

sources.

Sources.

Strong acids
 Aldehydes
 Oxidizing agents

Rubber Oils Plastics Amines Metals

Halogenated compounds

Peroxides Bases

Hazardous decomposition

products

Carbon oxides

Sulphur oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

# Skin corrosion/irritation

# Components:

67-63-0:

Species: Rabbit

Result: Irritating to skin.

# Serious eye damage/eye irritation

## Components:

67-63-0:

Species: Rabbit

Result: Irritating to eyes.

## Carcinogenicity

**IARC** 

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

SDS Number: 100000007753 7 / 12 Isopropanol TT-I-735A NOT.3 Grade A



Version 1.5

Revision Date: 10/26/2017

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH Confirmed animal carcinogen with unknown relevance to hu-

mans

64-17-5 Ethanol

STOT - single exposure

Components:

67-63-0:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

**Further information** 

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

## **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

**Bioaccumulative potential** 

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential

: Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances



Version 1.5

Revision Date: 10/26/2017

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## Disposal methods

Contaminated packaging

: Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

## **DOT (Department of Transportation):**

UN1219, ISOPROPANOL, 3, II

#### IATA (International Air Transport Association):

UN1219, ISOPROPANOL, 3, II

## IMDG (International Maritime Dangerous Goods):

UN1219, ISOPROPANOL, 3, II, Flash Point:12 °C(54 °F)

## **SECTION 15. REGULATORY INFORMATION**

WHMIS Classification

: B2: Flammable liquid

D2B: Toxic Material Causing Other Toxic Effects

# **EPCRA - Emergency Planning and Community Right-to-Know Act**

# **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: Fire Hazard

Immediate (Acute) Health Hazard

**SARA 302** 

No chemicals in this material are subject to the reporting re-

quirements of SARA Title III, Section 302.

**SARA 313** 

The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

67-63-0

Isopropyl alcohol

SDS Number: 100000007753 9 / 12 Isopropanol TT-I-735A NOT.3 Grade A



Version 1.5 Revision Date: 10/26/2017

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

67-63-0

Isopropyl alcohol

#### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

## **US State Regulations**

## Massachusetts Right To Know

67-63-0 Isopropyl alcohol 90 - 100 %

Pennsylvania Right To Know

67-63-0 Isopropyl alcohol 90 - 100 %

**New Jersey Right To Know** 

67-63-0 Isopropyl alcohol 90 - 100 % 64-17-5 Ethanol 0.1 - 1 %

California Prop 65

SDS Number: 100000007753

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

productive narm.

#### The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PHIL : On the inventory, or in compliance with the inventory


IECSC : On the inventory, or in compliance with the inventory



Version 1.5 Revision Date: 10/26/2017

#### **SECTION16. OTHER INFORMATION**

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 =Extreme, \* = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

**Revision Date** 

: 10/26/2017

#### Material number:

16056247, 16056246, 16056245, 16056244, 16056243, 16056242, 16056241

Key or leg	end to abbreviations and acronym	s used in the	safety data sheet
ACGIH	American Conference of Gov- ernment Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Sub- stances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Sce- nario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentra- tion Values	PRNT	Presumed Not Toxic



SDS Number: 10000007753

# Safety Data Sheet Isopropanol TT-I-735A NOT.3 Grade A

Version 1.5 Revision Date: 10/26/2017

GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Infor- mation System
LC50		Lethal Con-	centration 50%