

Port-A-Cool Cyclone™ 2000



**Centrifugal Air Supply,
1/3 h.p. Two-Speed Motor
Cools 500 sq. ft.**

- Adjustable Louvers
- Quieter Running Centrifugal Fan
- Smaller Footprint

- Lowers temperatures up to 30 degrees F
- Energy efficient 2.5 amps for pump and motor
- Water level sight tube and sump drain
- 3/4" garden hose connection for longer running
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability—near maintenance-free operation
- Shipped completely assembled— ready to operate out of the box
- UL Listed (electric models) in U.S. and Canada



Port-A-Cool Cyclone™ 3000

Speeds	Two
Air Delivery CFM	1,600 / 2,000
Total Amps	2.5
Water reservoir	10 gallons
Dimensions	31"h x 24"w x 25"d
Unit weight	61 lbs.
Shipping weight	72 lbs.
Box Size	37"h x 25"w x 27"d
Cooling Capacity	500 sq.

**STOCK NUMBER PACCYC02 (BLACK)
STOCK NUMBER PACCYC02A (SIENNA)**

Port-A-Cool, LLC

936-598-5651 • 1-800-695-2942 • FAX 936-598-8901