

MRO ^{February} 2020 Solutions

Smart Maintenance

Increase operational efficiency while predicting and preventing breakdowns with our range of smart products and solutions



New Product Highlights Page 06

How Smart are vour Sensors? Page 20







We're the people engineers turn to for help and advice.



We carry more than 600,000 industrial and electronics products from over 2,500 leading suppliers. From the niche specialists to the big global brands, we stock every brand you're likely to have heard of, and many more besides. This includes our own-brand RS PRO, which offers more than 50,000 products.

With fast and easy access to a broad range of products, reliable delivery, expert technical advice and solutions to streamline your processes, we'll help you keep things running smoothly.



Customer Service

Take advantage of our customer support, technical advice & dedicated account managers.



Competitive Quotes

Local team dedicated to quoting you the best price possible for all your orders.



Flexible Delivery

Free next-working-day, scheduled deliveries, or plan ahead with advance orders.



Easy Ordering

Order online, by phone, by fax, or on your mobile phone via our easy-touse website.

From same day delivery to procurement solutions, visit RS Online to connect to a wide range of helpful services to increase productivity, save you time and money.

How can we help you today?

Order Your Way!

- Online at nz.rs-online.com
- On the go with the RS Online mobile site
- On the phone at 0800 888 780
- Email ordersNZ@rs-components.com

Customer Services & Technical Support

Mon - Fri 9am - 5pm T: 0800 888 780 | F: 0800 888 700 Email quotes: quotesnz@rs-components.com



Welcome

We are proud to bring you our new series of magazines, MRO Solutions. Through these magazines, we aim to deliver you relevant industry articles and showcase our wide range products as part of our service to you.

This month's issue focuses on a critical subject for a large number of our customers. The continuous need for maintenance of production lines and machinery will never disappear, however, new approaches and technologies can help you maintain smarter. Educating yourself on how to drive efficiency from your maintenance activities and maximising uptime is crucial.

In this guide we provide insight on products and technologies which can help you work smarter, avoid unforeseen downtime and work more effectively. Smart can refer to anything from using wireless technologies to easily access data to using predictive tools in identifying problems before they cause a breakdown.

We hope that by investing a little time looking at our articles you will discover practical ways to improve your business into the future! **Smart test and measurement** using thermal imaging is discussed on page 25, while on page 20 it is the future for smart, easy sensor connectivity using open standard **IO-Link**. More information on these solutions, featured products and our wider ranges from all the leading brands is available on the RS website, visit nz.rs-online.com/mro-solutions.

Regards,

Cuong Vo

Vice President RS Components ANZ



04	RS eCommerce Solutions
06	Whats New?
80	Spotlight on RS PRO
14	Power Supplies
15	Relays
16	Circuit Breakers
18	Automation & Control
21	Omron
22	Interconnect & Test Solution
26	Tools & Consumables
28	Electronics
30	Offers

Terms & Conditions

To view our latest prices, charges and full terms see RS Conditions of Sale as set out online at nz.rs-online.com. Prices correct at the time of going to print, prices exclude GST. Published by: RS Components Ltd, PO Box 12-127, Penrose, Auckland

RS Components Pty Ltd February 2020 RS are trademarks of RS Components Limited. An Electrocomponents Company.

Take ownership of your procurement costs

You need a supplier you can depend upon, a strategic partner who does more than deliver the right product at the right time.

Not only do we offer more than half a million products. By making MRO procurement easier, faster, and smarter, we can help you save time, effort and money.

Procurement and engineering teams face increasing pressures with the design, build & maintenance of assets and facilities. These issues can stem from a fragmented supply base, multiple product categories, stakeholder management, and a pressure to reduce costs.



RS can offer new platforms and productivity drivers leading towards a more efficient way of working throughout your procure to pay (P2P) process.

Processes are integral into the functioning of any organisation, and the number, and complexity of processes are increasing.

RS is your partner, providing you with solutions to streamline your processes and reduce your hidden costs, generating quantifiable value for your business.

But have you considered the time it takes staff to research products, check availability, negotiate prices and arrange delivery? Then there's seeking internal approval, issuing purchase orders, processing invoices and payments ...It all adds up. In fact, sourcing and processing costs are typically more than twice your product costs.

End inefficient and costly procurement processes

If multiple people across your organisation are placing large numbers of low-value orders and you have little control over who's ordering what, you are almost certainly wasting both resources and money.

You could also be losing valuable production time if the ordering process only starts when a part or item needs replacing. Delays can occur while the purchasing process lumbers into action – meaning costly downtime.

The good news is there's a simple and effective way to cut your company's procurement costs and gain control of your budget spend. By understanding the complex needs of our customers, we have a suite of e-Commerce Solutions to support each individual, by delivering a world-class experience throughout the customer journey, with the target of reducing waste, and streamlining your processes.



Whether it's ordering online or via your procurement system, RS e-Commerce Solutions cater for all business sizes, types, needs, technology and processes to make ordering easier. We are committed to offering you a connected and individual experience that relates to what is at the heart of our Brand, "Let's Make It Happen".

From same day delivery to procurement solutions, visit RS Online to connect to a wide range of helpful services to increase productivity, save you time and money.

"Here at RS, we understand the complex nature of MRO and industrial supplies, So, if you are looking to streamline your procurement process, eliminate wasteful practices and reduce costs, we have a range of e-Commerce and inventory solutions that can be tailored to your business. Reach out to RS today - we are here to help"

> CRAIG MITCHELL Commercial Manager - Value Added Services ANZ



WHATS NEW

Visit nz.rs-online.com/new

Gas Soldering Iron

- Compact and portable gas soldering iron, ideal for soldering work where access is limited and there are no live power sources
- The power range of the soldering iron is equivalent to 25-80 Watt
- The built-in Piezo ignition system allows the iron to be used 30 seconds after ignition



3pc Spindle Mounted Wire Brush Set

- Suitable for use on Rust, Metal & Paint
- Crimped wire for general
- purpose applications • 4,500rpm Maximum safe speed





1884097 6mm Fixing Size

Yellow Push Button Head

- 22mm Diameter
- Spring return head
- Contact block mounting clip included
- Stackable design for contact blocks (max 9)



- Made with durable ABS plastic
- IP66 protection
- Three 22.5 mm cutout diameter for push button
- Supplied with 4 plastic screws



1828657 70 x 180 x 80 mm

High Strength Bopp Backed Tape

- High-strength, polyester backed, fiberglass reinforced mono filament tape
- High tack and high shear resistant adhesive system
- Excellent aging properties and assures clean removal from many substrates







1923668 80W, 185MM

Light Grey Hermetically Sealed Enclosure Ip65, lk08

- Manufactured using ABS offering excellent scratch and chemical corrosion resistance
- Light grey in colour, ideal for general purpose use in a range of environments
- IP65 rating offering protection from water and dust ingress
- IK08 rating offering enhanced shock absorbance





nz.rs-online.com

1881126 22mm Round Flat

3 Piece Shears Set - Left Cut, Straight Cut, Right Cut

- Multi-purpose shears with a straight blade for clean and precise cutting
- Each shear has a sharp, micro-serrated blade for anti-slip operation and easy cutting through fibrous materials
- The high-leverage design requiring minimal cutting effort for the user, especially when the shears are in use for long periods of time



1829988 250 mm Overall Length



1859513 25mm x 50m

53398 38mmx50m

RS PRO 316 Stainless Steel Ball Lock Cable Tie

- Uncoated version, for high temperature applications, quick installation
- · Ideal for petrochemical, food industry, industries, power stations, mining, ship-building, offshore and any other aggressive environments



1834237 200mm x 7.9 mm (Bag of 100)





Ergo[™] Stainless Steel Slotted/Phillips Screwdriver Set

- ERGO[™] stainless steel screwdriver set, 6 pieces
- · For slotted and Phillips head screws
- Comes presented in a cardboard box



BE-98811



H7.2 Led Head Torch

- CREE Power+ LED Light Chip (250 lumens on Boost mode)
- Advanced Focus System[™] Optics.
- Patented reflector and lens combination
- Smart Light Technology(SLT) featuring
- three pre-set light programs utilising five light options (High Power, Low Power, Boost, Dim, Signal)



LEDLENSER.

7924219 250 lm

Fluke Ti300+ Infrared Camera

- 320 x 240 resolution
- 2 meter drop test
- LaserSharp[™] Auto Focus
- Manual or automatic focus
- Measure up to 650 °C

Raspberry Pi 4 Model B Sbc

- The Raspberry Pi 4 has received a performance boost with an upgraded processor giving it similar power to an entry level PC
- There is now a choice of memory size; 2GB and 4GB to enable more complicated processes to run efficiently
- Dual micro-HDMI ports enables a dual screen set-up - previous versions featured 1 standard HDMI port
- Up to 4K video decoding



1822095	2GB	Raspberry Pi 4 2G Model B
1822096	4GB	Raspberry Pi 4 4G Model B

Raspberry Pi 4 Power Supplies

- An OKdo high quality and reliable plug-in AC-DC adapter for converting AC mains current into a 3A, 5.1V power using a USB-C type connector
- With a power rating of 15.3W, this power supply comes with four regional interchangeable heads



1871381	T7715DV
1871380 (Pack of	60) T7715DV_Bulk

Leavyseal Housing For **Female Terminals**

- IP67 sealing provides brilliant protection
- Strong a rugged durability, designed
- for use in pressuring scenarios
- Operating temperatures of -40°C to +140°C





1935400 9Hz

FLK-TI300+ 9HZ

7297 - H7.2





1642895 4 mm, 5 mm Pitch, 62 Way, 7 Row (2-1418883-1 Box of 117)

Xinabox Stem Micro:Bit Kit

• The XinaBox STEM micro:bit Kit (XK04) is a great way to upgrade your BBC micro:bit and unlock some exciting opportunities for learning and fun







1918680 STEM Micro Bit Kit

XK04

D-Sub 25-Pin To D-Sub 25-Pin Male Cable & Connector

- Assembled, shielded, halogen-
- free round cable
- Connection 1: D-SUB pin strip (1x 25-position), Connection 2: D-SUB pin strip (1x 25-position)
- Cable length: 3 m



1914350 25 V ac, 60 V dc

1066671



SPOTLIGHT ON RS PRO







RS PRO is the only global brand that gives you every part you need across all industries at the quality and price you expect

LED Machine Light

- Low Voltage Power
- Reinforced Lens for high resistance
 Furnished with 1.8 meters
- Furnished with 1.8 cord without plug



7777974 24 V, 12 W, Adjustable Arm

R5

Sealed Lead-Acid Battery

- 5 years standby design Float Standby use
- Low gas emissions 99% plus recombination
- Excellent recovery from deep discharge





88 Piece VDE Approved Electricians Tool Kit

- Ergonomic multi-component handles
- Optimum balance of torque and control
- High quality and professional tools





7348885 88pc ½in. Socket & Vde Tool Kit

Air Duster

- Inert, pure compressed
- gas for dust removal
- Ideal for removing particulates from inaccessible areas on delicate equipment



E PRO

1681644 400 ml 1681646 200ml

Digital Caliper

- Clear LCD display
- Stainless Steel construction
- Origin settingSwitchable On/Off
- Switchable On/O



2061 Piece Brass Screw/ Bolt, Nut & Washer Kit

- A range of slotted pan head brass
- metric screws, nuts and washers

 Supplied in a storage case





Multi-Purpose Cabinet Key

- Four position arm tool, offering five differing drive possibilities
- This universal cross key is made of alloy
- with excellent workmanship and durability
- Key holes with square, triangle and circle shapes suitable for many especially radiators and electric control cabinet





4393025 Matt Finish

9V Alkaline Batteries

• For general purpose applications







Precision crimp tool for insulated terminals

- A range of crimp tools for insulated terminals, ferrules and splices
- Options include low-cost tools for occasional use and high reliability, production-ready tooling

15pc Briteguard Hex Key Set

- 15 piece ballpoint L wrench set with
- an excellent variety of key sizes.
- Lengths of keys are fully hardened
- Ball-Plus[™] hex keys permit an entry angle up to 25° to work in hard-to-reach areas

SPOTLIGHT ON RS PRO

SR44 Silver Oxide Button Cell

- Superior discharge characteristics in comparison to alkaline cells
- Good low temperature performance characteristics
- · Good resistance to shock,
- vibration and acceleration





533279 For 0.5 mm² to 6.0 mm²

Silicone Grease

- Water repellent with excellent
- lubrication properties
- Non-toxic and safe on most plastics
- High dielectric strength



5423509 Long Arm, Metric

- **1.5V AA Alkaline Batteries**
- Long life alkaline batteries suitable for a wide range of applications
- Non- rechargeable





593423 SR44 (pack of 5)

White PTFE Foam Sealing Tape

- · Chemically inert material meaning it does not react with other elements • Suitable for aggressive environments where acids, gases and solvents are present
- Non-adhesive
- Prevents fluid/pressure loss when used correctly





Type K Green Miniature In-Line Plug Connector

- Pins made from true thermocouple alloys or compensating material for accurate signal transmission
- IEC colour coding for quick and easy identification
- Polarised flat pin contacts for an accurate connection





4559764 Plug

R5

R5

R۵

7892828 AA (pack of 100)

8 Level Temperature Sensitive Strip

- Suitable for use in high voltage switching, motors, cable overheat detection and wave soldering
- Marked in °F and °C







R۵

SPOTLIGHT ON RS PRO



- HSCo (5%) jobber drills for use on alloy steel, hardened steel, stainless steel, cast iron and titanium
- 135° split point





216690 1mm to 13mm

Black 8mm Crimp Bootlace Ferrule

- Made from bright tinned copper
- with polypropylene insulation .
- Suitable for tri-rated and 2491X cables
- Ensure a positive connection when used with terminal blocks and captive terminals



458718 8mm pin, 1.5 mm² wire (Pack of 100)

Absorbent Standard Weight Maintenance Pad

- Standard Weight Maintenance pad with open back for quick wicking
- High tensile strength spun bond cover stock prevents lint sticking to machine parts and tools
- Absorbency 0.9 litres per sheet
- Size 48 x 38 cm





7716377 Oil Only Pad 90 L Cap (Pack of 100)

ATEX Intrinsically Safe Torch, Zone 0

- For use in hazardous locations
- Light modes: High / Low / Flash
- IP67 rated with a tough and durable casing

8903001 3xAAA

Unit

RS Proximity Switch Test

· Designed to test 3-wire DC proximity

Capable of testing inductive (metal sensing), capacitive, photoelectric

Supplied ready to use with a 9V PP3 battery fitted, a great addition to any industrial toolbox!

switches - either NPN or PNP

or ultrasonic sensors

High Impact lens and non-slip handle

Hydraulic Crimping Tool

- Robust hydraulic crimping tool with spring loaded handles
- Single hand operations, letting the other
- hand free to position the connector
- Replacement die sets are also available separately





6241285 For Tubular Cable Lug

Isolpropyl Alcohol Cleaner

- An alternative to CFC-based solvents which are said to destroy the earth's ozone layer
- Leaves no residue meaning you are left with a smooth surface
- Non-aggressive so does not
- destroy your parts





8399875 Hand Held Proximity Switch Tester

Fibreglass Bristle PCB and Flux Brush

- Easy to use for cleaning and preparing
- Retractable brush













839-9875

2274427 11 Tin

General Purpose Foot Switch

- Single pedal foot operated switches
- Durable and reliable with steel
- housing for long life
- Rated 250Vac/30Vdc at 3 A



- Optional refill



Compact Digital Multimeter

- 2000 Counts LCD backlit display
- Voltage 600V ac/dc •
- Current 10Aac/dc
- Resistance • Temperature measurement (RS14)
- Continuity
- EN61010-1 CAT III 600 V





1231938 RS14 Autoranging

Black Polyolefin Heat Shrink Tubing 3:1 (Reels)

- Tough, flexible, general purpose
- polyolefin tubing
- Excellent physical and electrical performance
- Very good chemical and solvent resistance





7004535 6/2mm i/d (Reel of 7m)

Heatshrink Tubing Kit

- 170 mixed heat-shrink pieces
- Sizes range from 2.4 mm to 12.7mm
- Available in adhesive lined 3:1, and non-adhesive lined 2:1 shrink ratios
- Flame retardant
- Supplied with useful storage box



Lead Free Solder

- Leaves low level of clear flux residue which can be left safely on the PCB Wets well to all PCB and component finishes
- · Ideal for all lead-free applications
- Spreads like a RA flux
- · Available in different wire diameters





7568884 0.7mm, 250g reel

94-Piece Mechanics Tool Kit

- Large tool kit for automotive work comprising of a comprehensive socket and bit, spanner and precision screwdriver sets
- Chrome Vanadium construction with
- Chrome Molybdenum Steel sockets



Black Nylon cable ties

- Ideal for bundling and organising cables and wires
- Suitable for a multitude of uses
- Black and natural colours
- available in a range of sizes
- Self-extinguishing to rating UL94V-2





233487 300 x 4.8mm (Pack 100)

SPOTLIGHT ON RS PRO

Lockout Starter Kit

- Portable electrical department
- lockout tag out kit Provides all the basic Lockout for
- valves and electrical panels
- Comprises of around 24 different products Supplied in a tough LOTO caring bag
- (with handle and shoulder carrier)





De-Ionised Water For Circuit Boards

• De-ionised water suitable for the final rinse or "polish" to circuit boards cleaned with Safewash





Ľ

7348889 94pc Mechanics Tool Kit

Do you know enough about your processes to optimise them fully?

Data never sleeps; as many manufacturing, logistics and processing industries operate in a 24/7 environment, while being commercially challenged from all directions.

A key element of making fast, incisive operational decisions is having the right information available. And being able to measure, monitor and extract information to make more informed decisions should be top of the agenda – but is it?

lloT and M2M - what does it all mean?

The Industrial Internet of Things (IIoT) and machineto-machine (M2M) communication are transforming industrial processes by enabling networked devices to exchange information and carry out more tasks than ever, often without human involvement. These increased levels of machine connectivity and diagnostic data allow for smarter working, through more informed predictive maintenance, greater process flexibility and access to increased levels of operational data.

Think and sync - using smart devices

The majority of new devices offer connectivity in the form of Wi-Fi, Bluetooth, Near-Field Communication (NFC) and Ethernet – and with this level of connectivity, more data is available in the workplace. This can include anything from simple communication, to accessing machinery controls or building systems from anywhere onsite using a laptop, tablet or smartphone. Going forward, technologies such as vision systems, thermal imaging and cloud services will become more prevalent to create smarter solutions.

Harness the benefits for increased productivity

Technology is becoming increasingly more affordable and accessible; with developments making it easier to upgrade or monitor existing machinery, companies are continually becoming more connected. This enables more work to be done, using the same amount of machines and people –

What business wouldn't want that?



RS Sponsors the Smart Manufacturing and Industry 4.0 Forum

RS Components was pleased to be the Gold Sponsor for The Smart Manufacturing and Industry 4.0 Forum and adjoining Digital Supply Chain Forum held at the Langham Hotel in Melbourne.

The 3 day event included a key note address by Scott Philbrook - Head of Corporate Accounts and RS Components hosted round table discussions in both the Smart Manufacturing Forum and Digital Supply Chain Forum.

Thank you to all the participants that met with us over the event. There were over 150 attendees that enjoyed;

- On site tours of installations with technologies demonstrating the advantages of IIoT.
- Key note addresses covering best practice sharing and thought leadership on challenges faced with the development of IIoT in manufacturing environments
- Round table discussions on various topics around the importance of data driven decision making and developing partnerships to manage all components of lloT

Representatives from a variety of Industries such as Automotive, Food & Beverage, Defence, Education and Manufacturing were present and senior level participants shared their knowledge and experience from their roles including operations managers, procurement, engineering, technology leads and CEO's. The key note address that was presented by Scott Philbrook was titled "Ecosystem for the Data Age". The presentation covered the key elements of the IIoT Framework, Data Acquisition through the three streams of untapped data, stranded data and new data, the challenge of navigating the Information Technology / Operational Technology divide, understanding cloud architecture and the strategy RS Components is developing to deliver IIoT as a service.

Vice President of RS Components Cuong Vo along with Craig Mitchell and Scott Philbrook hosted roundtables across the two events where participants shared some of the real-life examples from their IIoT journey and some of the challenges they have faced in developing their own IIoT strategy.

General consensus was that their environments were "data rich" however it was hard to understand exactly what data should be accessed to derive a return on their investment for the new technologies. It was highlighted that there is a talent gap in the manufacturing industry as they moved from Industry 3 to Industry 4.0.

Participants also shared that their businesses were hesitant to collaborate across other businesses as it involved disclosing their intellectual property and everyone was on different stages of their IIOT journey and Cyber Security was critical.

Get in touch today to see how RS Components can support your lloT strategy!



INSPIRING INNOVATION

QUINT Switch Mode DIN Rail Panel Mount Power Supplies

- Selective Fusebreaking Technology (CRC Technology)
- Worldwide use through wide-range input for DC and AC networks
 Reliable start difficult loads with static
 power reserve POWER BOOST



540779	18V dc to 29.5V dc, 5A	2866776
6657823	18V dc to 29.5V dc, 40A	1027952
540769	18V dc to 29.5V dc, 10A	2866763
540725	18V dc to 29.5V dc, 3.5A	2866747

QUINT UPS Power Supply

- Maximum service life
- Gives early warning of failures
- Easy handling
- Shuts down before the battery voltage runs out



739	7869	24V dc Output	2902689
739	7865	24V dc Output	2902686
751	2581	18V dc to 30V dc, 5A	2903223

TRIO POWER DIN Rail Power Supply

- Robust design
- Available in single and three phase
- Tool free push in connection
- High MTBF (Mean Time Between Failure) values of over 1 million hours



8837352 24V dc to 28V dc, 5A

2907306

STEP POWER Single Phase Power Supplies

- Easy mounting on the rail and wall
- Maximum energy efficiency through small losses
- Fast commissioning with LED function monitoring
- High operational safety by long
 power failure under full load



7080444	24V dc, 500mA	2901131
540735	24V dc, 750mA	2868635
6657826	5V dc , 6.5A	2868541
540763	12V dc , 3A	5531354

TRIO-PS-2G/1AC/24DC/3/C2LPS PSU,

- Robust design
- Available in single and three phase
- Tool free push in connection
- High MTBF (Mean Time Between Failure) values of over 1 million hours



8837374	24V dc, 3A	2903147
8837361	24V dc, 10A	2903149
8837364	24V dc, 20A	2907308

TRIO-PS-2G/3AC/24DC/5 PSU,

- Active function monitoring with DC OK LED
- Floating signal contact to ensure the safe supply of all connected 24 V DC loads
- + Temperature range from -25°C to +70°C



8837368	24V dc, 5A	2903153
8837377	24V dc, 10A	2907310
8837370	24V dc, 20A	2903155



INSPIRING INNOVATION

SPNO Non-Latching Relay DIN Rail

- Easy wiring due to push in connection technology
- Easy handling and extension of range
- Plug in display/suppressor module



7943765 12V dc Coil, 6 A	2903362
7943761 24V dc Coil, 6 A	2905411
7943768 12V dc Coil, 50 mA	2903360
7943759 24V dc Coil, 50 mA	2905409

DPDT Non-Latching Relay DIN Rail

- DPDT (Double pole, double throw)
- Coil power is 400 mWBase has IP20 protection
- Relay has RT III protection



7943721 24V dc Coil, 2 A	2905399
7943727 24V ac Coil, 12 A	2905398
7943724 120V ac Coil, 12 A	2903332
7943715 230V ac Coil, 12 A	2905396

4PDT Non-Latching Relay DIN Rail

- AC and DC versions
- 2 and 4 contact options
- Yellow LED indicator
- Varistor or damping diode protective circuit



7943686 24V dc Coil, 6 A	2903308
7943682 24V ac Coil, 16 A	2903306
7943689 120V ac Coil, 16 A	2903305
7943670 230V ac Coil, 5 A	2905383

3PDT Non-Latching Relay DIN Rail

- Easy wiring due to push in connection technology
- Easy handling and extension of range
- Plug in display/suppressor module



7943660 24V dc Coil, 2 A

2903294

PHENIX

CONTACT

PLC-RSC Series DIN Rail Interface Relay Modules

- Saves space on the DIN rail
- Cost-effective
- Use the same electromechanical relay module design for both AC and DC switching voltage
- DIN rail mounting



3588301	24V dc	5521348
3528832	24V ac/dc	5521351
3588339	230V ac/dc	5521377

PLC-RPT Series DIN Rail Interface Relay Modules

- Efficient connection to system cabling using V8 adapter
- Safe isolation according to DIN EN 50178 between
- coil and contact
- Functional plug-in bridges



7112630 24V dc	2901214
7112683 12V dc	2901229
7112642 48V dc	2900301



INSPIRING INNOVATION

Quickon Series Conductor Connector

- Convenient: quick and easy assembly without special tools Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications •
- Safer connection thanks to polarization against mismatching and touch-proof protection according to DIN EN 0105 •

C-RCI Insulated Crimp Ring Terminal

M4 Stud Size, 0.5mm² to 1.5mm², Red (Pack of 100)

• Material: Copper

8046953

Mounting Base

technology as well as process control Using SFB Technology (Selective Fuse • Breaking) the circuit breakers can be • used in a wide range of applications

Sleeves are conically tapered to facilitate easy and correct insertion of the conductor



7158597	3+PE, 690 V, 20 A,

1582214

Motor Protection Circuit Breaker

- Compact design, only 12.3 mm wide
- Large-surface marking possibilities, 1 per connection point and 1 on top of the device
- Double plug-in bridge shaft
- Available in current ranges 0.5 A to 16 A



6843594 240 V ac, 28 V dc 916605

Subcon-Plus Wire Strippers

- Quick wire stripping tool for the SUBCON-PLUS-PROFIBUS cable
- Strips cables and single wires



8018967 6 - 8mm 2744623



7117552 Male CSA2.5 - 6mm², Rated At 40A, 1100 V 1774687





3240018

1-DE

7680880 1-pos., M1 (medium-blow), 1 PDT contact 2800848

- **Cable Mount Solar Connector Plugs**
- Can be unlocked with a screwdriverDegree of protection: II



Push-in Technology

Device circuit breakers for even greater system availability

Maximum functionality, minimum overall width, high level of safety

Protect your circuits in the event of overload and short-circuit current with the multi-channel electronic device circuit breakers. The four and eight-channel devices can now be installed quickly and toolfree and can be easily set.



When timing and quality matters, our top brands put you in control.

Our comprehensive portfolio covers a wide range of technologies from Process Controls to Machine Guarding & Safety and much more.

IOT 2020 & 2040 Intelligent Gateways

- The SIMATIC IOT2020/40 intelligent gateways are reliable open platforms for collecting, processing and transferring the data from one network to another
- The SIMATIC IOT series is able to support industrial engineers, makers and designers in creating a IOT gateway between the cloud or site wide network and individual fieldbus and devices within the production environment
- Based on the Arduino platform, powered by the Intel Quark x1020 with Ethernet and optional RS232/485 interfaces
- Supports Yocto Linux and other high level languages
- Expandable & extra connectivity via mPCle cards & Arduino shields

MICA Industrial Edge Computing IOT Kit

- The MICA[®] CISS Industrial IoT Kit offers the ease of 'plug & play' operation with open-source computing & integrated Node-RED dashboard
- Kit combines a CISS multi-sensor unit by Bosch and the HARTING MICA[®] Edge Computer creating the ideal platform for development of a condition monitoring or predictive maintenance solution
- The sensor can monitor 8 characteristics including acceleration, temperature, humidity, light, force and pressure with all data is provided in MQTT format

1762224 GPIO, USB 2.0

Source IPC

REVOLUTION PI Open-

An open-source industral PC powered

by the Raspberry Pi Compute module housed in a 22.5mm wide DIN Rail module with 12-24Vdc supply

 The open-source nature of the PiRev means it can run CODESYS, Node-RED and other

IEC 61131-3 compliant platforms as well as accessing the KUNBUS Cloud service

2095000001630



- Stainless steel housing LED status indicator
- Shock resistant up to 150 g
- IO-Link communication



SICK 1347808 M12 x 1

IMB12-08NPPVC0S

Acti9 ARA iC60 Remote Auxiliary

- Programme selector: Four predefined and easy-to-set programmes on front face
- Status indicator in the front face for quick status check
- Integrated padlocking device
- Manual on-site inhibition for maintenance



18111141 RevPi Core, Single Core 700MHz, PR100102 512Mb RAM

1811142	RevPi Core 3, Quad Core, 1200MHz, 1GB RAM	PR100257

IO-Link Smart Sensor

- Analog/digital interface
- Small size
- Easy clip and/or screw fixing
- Quick connection (M12 plug-in connector)





SIEMENS

 124-4038
 IOT2040 Industrial Intelligent Gateway - 2 x E/ Net + 2 x RS232/485

 124-4037
 IOT2020 Educational Gateway - Ethernet Only

1890174 18-30v DC

01411.2-00

Schneider

7907359 4P

A9C70134





Mains Plug Type I

- Grey and clear moulded 3 flat pin 240V 10A and 15A plug tops suitable for Australia or New Zealand
- Supplied with cable clamp
- 10A versions suitable for cable diameters of up to 8mm, 15A version suitable for cable diameters of up to 10mm





780403	10A	CD100LCL
780419	15A	CD100L15GY

DIMENSION O DIN Rail Panel Mount Power Supply

- Single-phase or three-phase units from 80 to 960W
- Active power factor correction
- · Minimal inrush current
- 50% power reserves for typ. 4s controlled by an intelligent power manager .



PULS

7115985 3 PHASE, DIN RAIL PSU, 24V, 40A QT40.241

Grid Feed Voltage Monitoring Relay

- Monitoring of voltage and frequency in single and three-phase mains (2-wire, 3-wire, or 4-wire AC systems)
- 0-minutes average value monitoring
- Rate of change of frequency
- monitoring configurable
- Vector shift detection configurable





Barrel Style Ultrasonic Sensor

- Stainless steel body
- Adjustable switched outputs
- Synchronisation feature
- Hysteresis and window modes



PEPPERL+FUCHS

3995484 M30 2 PNP O/P 2000MM

OUINT DC to DC Converter

- Power Boost allows reliable starting of difficult loads
- Preventive function monitoring indicates
- critical operating errors before they occur
- Output voltage regenerated even at the end of long cables
- Support conversion to various voltage levels

PHŒNIX CONTACT

Kit with HMI

Input simulator

• KTP400 basic

7512608 DIN RAIL 24DC/24DC/20

• Profibus, Profinet Networking

Ethernet, USB Interface

· CPU 1212C AC/DC/RLY

S7-1200 PLC CPU Starter

• SIMATIC STEP 7 basic in the TIA portal



6 Pole Panel Mount Switch Disconnector

- IP65 Rated
- Flush or Surface Mouniting
- Red rotaru handle
- Lockable in the OFF position



FAT-N

1038447 6NO, 63 A, 22 kW, IP65 T5B-3-8342/EA/SVB

IP69K Steel Wall Box

- Material: Stainless steel
- IP69K rating
- Lockable
- Double lipped edge to ensure higher strength and ease of installation
- Easy to use, including removal of the door



7587034 200mm x 300 mm x 300 mm

QUINT POWER 24V series Power supplies

- Wide range input for global use
- Primary switched
- Adjustable output voltage



SIEMENS

6AV6651-7DA01-3AA4

5055471 120W, 24V dc/ 5A

2938581

19













UC2000-30GM-E6R2-V15



2320102









8643999 24 V dc

IO-Link



The future for smart, easy sensor connectivity and communication which can be used on existing machinery and systems now!

Sensors have long been the eyes & ears of the control system, in direct contact with the process and therefore exposed to potential damage. Since their introduction the vast majority of presence and proximity sensors only provide a simple digital on/off

IO-Link enables fast, foolproof maintenance

With IO-Link the last meter between the field level of automation and the sensor/actuator level becomes communication-capable. This means that in addition to the process variables, information about identification, parameters and the status of the device can also be sent. This helps avoid replacement with the wrong device model and sensor parameters can be stored in the controller and automatically transferred when the unit is replaced. IO-Link simplifies equipment replacement, reduces the level of training required, reduces maintenance costs through better diagnostics and prevents downtimes.

IO-Link reduces maintenance costs while increasing equipment uptime

IO-Link devices can provide information about their basic status. For example, the increasing contamination level of an optical sensor can be reported and maintenance requested. These self-diagnosis functions and the ability to convey information back to the control system enables greater levels of predictive maintenance, less preventative maintenance and uptimes are increased.

Previously

- Replacement of sensors and actuators having parameters only possible using special programming device or in situ on the unit itself
- Simple diagnostics possible on additional cable lines Mix-up of model types not detected, since the devices
- cannot be identified by the host system
- No early warning for compromised operation possible
- Failure of digital sensors or actuators not generally detected Often a need for different models due to differing
- measuring ranges and function variants

output. However IO-Link is set to change all that and unlock information about the status of the sensor and it's environment which was previously unknown - all via the same wiring that the sensors have previously used.

Upgrade existing equipment and designs with minimal cost

One of the biggest benefits of IO-Link technology is its use of existing wiring. It transmits the additional information via the 3-wire connection used by the sensor or actuator without affecting its basic operation. This means IO-Link is invisible to the system unless a gateway is used to interface with this data, which allows IO-Link enabled sensors to be implemented into existing machines or designs with minimal re-work.



With IO-Link

- Device parameters can be stored in the host automation system and automatically downloaded reducing documentation or expert knowledge requirements
- Conveniently run diagnostics information is sent over the same line as the process data
- Devices can be identified and replaced with no risk of inserting the wrong type
- Status- and need-based maintenance is possible
- Operating status information supports need-based
- maintenance reducing reactive maintenance
- Monitoring of communication and diagnostics indicate availability
- Spare parts inventory costs are reduced
- thanks to parameter setting capability

So what does this mean to the industrial end user?

IO-Link technology has been rapidly gaining acceptance since its launch in 2009, with over 160 manufacturers now supporting the technology. IO-Link is an open-standard, and has been adopt¬ed as an international I/O standard (IEC 61131-9) allowing different brands of actuators and sensors on a machine to communicate with the control system via the same gateway.

This high level of manufacturer support, openness and ability to retro-fit IO-Link to existing processes and designs means you should be demanding IO-Link support from machine builders and integration partners now to ensure you gain the operational benefits.

We've been expanding our IO-Link range and now have nearly 400 enabled products in stock, giving you the opportunity to design or upgrade machines with this game changing I/O technology.

OMRON

Sysmac Automation Platform

Sysmac is the latest machine automation platform from Omron with integration throughout, offering one control solution for the entire machine or production cell.



NX1 Machine Controller

- The NX1 completes the NX/NJ machine controllers family offering same functionality in a compact design
- It provides synchronized machine
- control across motion, I/O, safety and vision within one Integrated Development Environment • Logic sequence and Motion control in single CPU
- with up to 8 axes (4 synchronized axes)
- Built-in I/O: 40 or 24 I/O points extendable
- EtherCAT and EtherNet/IP ports as standard
- NX-ILM400 NX IO-Link 4-channel master allows easy integration of IO-Link enable sensors at process level



1362770	CPU, 4 Axes, 114 / O10	NX1P29024DT1
1362767	CPU, 10 Axes, I24 / O16	NX1P21040DT1
1362768	CPU, 12 Axes, I24 / O16	NX1P21140DT1
1362772	RS422/485 option board	NX1WCIF11
1362774	Analog I/O option board	NX1WADB21
1362790	EtherCAT Coupler - 2ports - 63 I/O	NXECC203
1362791	4 Digital Inputs, PNP 24VDC	NXID3417
1362792	8 Digital Inputs, PNP 24VDC	NXID4442
1362793	8 Digital Outputs, Relay 2A/250V	NXOC4633
1362794	4 Digital Outputs, PNP 24VDC	NXOD3256
1362796	2 Analog Input, 4 to 20mA	NXAD2203
1362798	2 Analog Input, -10 to 10V	NXAD2603
1362801	2 Analog Outputs,4 - 20mA	NXDA2203
1362802	2 Analog Outputs,-10 to 10V	NXDA2603
1362806	I/O power feed unit, 5-24Vdc DC	NXPF0630
1362808	NX IO-Link master, 4 channels	NXILM400
1362762	NX1 Controller Starter Kit - 4 x Axes	NX1POSITIONSTARTKIT

FQ Vision Sensing Solutions

- The FQ2 combines an advanced image processor, with high-power LED illumination and adjustable lens to create the perfect visual inspection solution
- With 1/3" CMOS sensor, 350,000 pixels, real colour and Ethernet communication the FQ2 is compact and high performance
- The FQ2-D30 Touchfinder simplifies setup and allows configuration in process without the
- need for software Ideal for edge, area, colour, position, label, and shape detection applications



1466117	Inspection, Colour, NPN o/p	FQ2-S20050F
1466119	Inspection, Colour, PNP o/p	FQ2-S25050F
1466122	Inspection/ID, Colour, PNP o/p	FQ2-S45050F
1466112	Vision Sensor - DC power supply	FQ2-D30
1466115	IO cable 3m	FQ-WD003-E
1466113	Ethernet cable 3m	FQ-WN003-E

1S Servo Drives with EtherCAT

- 1S Sysmac general purpose servo drive &
- matched motor solution with safety built-in • 23-bit resolution encoder
- for precise control

 Screw-less for pluggable
- connections for simple & quick wiring
- Embedded relay for direct
- motor brake control • Network Safe Torque Off to PLd EN13849-1, SIL2 (IEC61508)
- EN13849-1, SIL2 (IEC61508) - Hardwired Ple/SIL3

1362811	200W servo drive	R88D1SN02HECT
1362812	400W servo drive	R88D1SN04HECT
1362813	800W servo drive	R88D1SN08HECT
1362814	Servo motor,200W,3000rpm	R88M1M20030TS2
1362816	Servo motor,400W,3000rpm	R88M1M40030TS2
1362818	Servo encoder cable, 5m	R88ACR1A005CFE
1362819	Servo motor power cable, 5 m	R88ACA1A005SFE
1362820	RFI filter; single-phase	R88AFI1S103SE
1362822	RFI filter; single-phase	R88AFI1S108SE

E3Z Photoelectric sensors with IO-Link

- Omron's popular E3Z series of photoelectric sensors with IO-Link connectivity built-in
- IO-Link connectivity makes sensor level information visible and notifies of faults and problems
- in the sensor in real time Retro-reflective versions have
- polarised light source for shiny object detection



1244436	Retro-reflective, Sr 4m, M8	E3ZR86IL3OMS
1244437	Diffuse, Sr 1m, M8	E3ZD87IL3OMS
1244438	Diffuse, Sr 90mm narrow, M8.	E3ZL86IL3OMS
1244435	Thru-beam, Sr 15m, M8,	E3ZT86IL3OMS

E2E Inductive sensors with IO-Link

- Based on the existing E2E series nickelplated brass IP67 threaded inductive sensors but with IO-Link capability
- The sensors still operate inthe traditional way with a PNP NO/NC switched
- output, with the added benefit of IO-Link status data being accessible
- via a gateway over the same wiring



1244439	M12, Sr 3mm, NO/ NC, M12	E2EX3B4M1TJIL303OMS
1244440	M18, Sr 7mm, NO/ NC, M12,	E2EX7B4M1TJIL303MOMS
1244441	M30, Sr 10mm, NO/ NC, M12,	E2EX10B4M1TJIL303OMS

Colour Mark Detection Sensor with IO-Link

- The E3S-DC colour mark photoelectric sensor offers reliable detection of colour markings on any type
- of packaging even glossy
- High luminance, three-element (RGB) LED light source for greater light intensity
- Highly efficient optics technology
- enables stable detection even of subtle colour differences • Narrow beam and
- Narrow beam and large lens, NC/NO
- configurable push-pull output, full IO-Link V1.1 capability built-in



1244428 E3S-DC Colour Mark Sesnor

E3SDCP21IL3OMS

INTERCONNECT & TEST SOLUTIONS

We remain committed to solving the industry's most demanding interconnect and testing challenges with high-quality and innovative products for the broadest applications.

Magnetic Field Detector

- Responds to all kinds of magnetic fields from alternating current to direct current and permanent strong magnets
- A small test magnet is housed in the cap of the Magnet Stick to check that it is working correctly

RS5500 Insulation & Continuity Testers

- Triple insulation voltage Test Ranges: 250V; 500V; 1000V (RS5505 adds 125V range)
- 200mA short current continuity range
- Test Hold function for easy operation
- Over range indication
- + 1 mA test current for $M\Omega$ range at
- rated voltage Meets IEC 10101, CAT III 1000 V

1231931 RS5500

RS51 Series Thermometer • A range of thermometers offering a choice of number of inputs, thermocouple type and with or without datalogging • K or J-Type - thermocouple input depending on model • Real-time stamp (RS53 / RS55) Data logging up to 16000 records (RS53 / RS55) • °C, °F or °K display

Fluke 719 Pro Pressure Calibrator

- Unique integrated electric pump for one handed pressure calibration
- Precision pressure adjust vernier for easy and accurate pressure calibration
- 30 PSI, 150 PSI and 300 PSI (2, 10 and 20 bar) measurement range



3755422 0.3mT, 1000V ac

Fused Test Leads 600v Cat lii

- A 500mA, 50kA breaking capacity fuse is fitted to provide protection against electrical arcing being sustained through the test leads
- Probe tips are shrouded leaving only 2mm of exposed metal to prevent inadvertent bridging of live conductors
- Double insulated silicon rubber cable indicates wear and damage to the leads via white inner layer of insulation
- Safety crocodile clips with finger guards are available with certain kits



1233215 RS51 Type-K One Input

Fluke 117 Multimeter

- VoltAlert[™] Technology for intergrated non-contact voltage detection
- AutoVolt feature for automatic AC/DC voltage selection
- LoZ: Low input impedance to eliminate stray voltage
- Large white LED backlight True RMS



BITTE MAKE TOP







FLUKE.

6161460 10A ac 600V ac 10A dc 600V dc FLUKE 117 EUR

1232216 +500 °C



FLUKE. 7999140 30 PSIG (2 bar)

Fluke-719Pro-30G

RS PRO Infrared Thermometer

• Built-in laser sighting

- Backlit LCD display
- Auto HOLD
- MAX / MIN reading
- Adjustable emissivity



Infiniivision EDUX1002A Oscilloscope

- Sampling rate is 1GSa/s
- Maximum memory depth of 100kpts •
- Display of 7in TFT LCD WVGA
- Intuitive GUI and built-in help available in 15 different languages
- Six-in-one instrument integration

Megger PAT420 Portable **Appliance Tester**

- Large 5.7in. VGA backlit colour screen for
- clear & easily understandable results
- 5 user defined soft-keys for direct access to frequently used functions
- Full QWERTY keypad for easy and precise data entry

INTERCONNECT & TEST

8 Pole M12 Socket To 8 **Pole Socket Adapter**

• Right Angle 8 Pole M12 Socket to 8 Pole Socket Adapter, 21.5mm



Megger.

7212465 Class I, Class II Test Type PAT420-AU

S-Force 2200 FTD Series **Compact DC Axial Fan**

- 3-Phase fan for efficient running
- Compact design for space saving
- Low operating noise at high back pressure
- Protected against reverse
- polarity and locking
- Fitted with speed signal and control as standard





21033814800

Permasleeve[™] Wire Marker **Sleeve Cartridge Labels**

- Heat-shrinkable
- Self-extinguishing
- Meets MIL-M-81531, MIL-STD-202F, Method 215 & UL 224

KEYSIGHT

1346146 50MHz

EDUX1002A

Megger MFT1815 Electrical Tester

- Simple colour-coded test selection and
- large clear backlit display for ease of use
- Two and three wire non-trip loop testing for RCD protected circuits
- Internal memory and Bluetooth® communications



ebmpapst

7406382 1220m³/h, 103W, 48 V dc 2218F/2TDH4P

Four Pole Double Throw (4pdt) Toggle Switch

- Toggle switch with silver plated contacts sealed to prevent the ingress of dust or liquids
- Connection via 250in. (¼in.)
- receptacles or soldering For biased operation '(on)' refers
- to momentary on position Brass actuator and Glass Filled

Polyester case





legrand

7048668 Black, IP68 (Box of 5)

0 979 63

2662212 ON-ON, 20A

A4TN15W04









O-BRADY.

6949128 4.75mm X 2.13m

M21-187-C-342

M20 Cable Gland

 Anti-vibration tightening rated as IP68 • The blocking part of the cable glands is made up of flexible flaps which exert a strong pressure on the cable and conferring on the product an optimal resistance to traction

Megger. 9011321 2 Wire, 3 Wire

MFT1815-AU

INTERCONNECT & TEST



Testo 868 Thermal Imaging Camera

- Superior image quality
- Integrated digital camera
- 19200 temperature measurement points ensure accurate thermography



1252266 -30 → +100 °C, 0 → +650 °C

Be sure. teste

Fluke Ti480 PRO Thermal Imaging Camera

- The Ti480 is a rugged and superbly engineered 640 x 480 thermal imaging camera
- Users can now perform thermal imaging inspections with more confidence and faster results than ever before all with
- the ruggedness and ease of use expected from Fluke
- Meet the rigorous demands of thermal inspections



FLUKE.

1716857 -20→+800 °C

FLIR C2 Thermal Imaging Camera

- Easily affordable
- Light, slim profile
- Contains a built-in LED spotlight that can be used
 as a flashlight and for photo illumination
- Auto orientation
- Touch screen



FLK-Ti480 PRO 9HZ

\$FLIR

8668124 -10→+150 °C

72001-0101



FLIR TG297 Industrial High Temp Thermal **Imaging Camera**

- The FLIR TG297 is a one-of-a-kind industrial diagnostic tool that combines accurate temperature measures with the ability to image up to 1030°C (1886°F)
- Patented FLIR MSX® (Multi-Spectral Dynamic Imaging) enhancement improves image clarity by embossing visual scene details on full thermal images



\$FLIR

1764816 +1886°C

TG297

Fluke Pti120 Pocket Thermal Camera

- Automatically organize and file thermal images with Fluke Connect Asset Tagging
- Fully radiometric thermal imager gives you measurement data to the pixel with 120 x 90 infrared resolution (10,800 pixels)
- 3.5" LCD touchscreen display for easy troubleshooting -20 °C to +150 °C temperature measurement range
- Six color palettes
- · Can withstand drop up to 1 meter



PTi120

FLUKE.

1864695 -20→+150 °C

FLIR ONE Pro iOS Thermal Imaging Camera

- Pixel size 12um (con), 8-14um spectal range
- Higher Resolution Thermal Sensor
- Advanced Diagnostics
- One-Touch Reporting
- Enhanced FLIR ONE App



SFLIR 1368284 -20→+400 °C

435-0006-03



Work smart solving electrical problems with thermal imaging

Today's thermal imagers are rugged, easy to use, and much more affordable than even just a few years ago. They have become a realistic solution for everyday electrical maintenance.

To use, a qualified technician or electrician points the thermal imager at the equipment in question and scans the immediate area, looking for unexpected hot spots. The imager produces a live image of the heat emitted from the equipment and with the quick squeeze of the trigger, a thermal image is captured.

Point one: loading

The electrical equipment being inspected must be under at least 40 % of nominal load in order to detect problems with a thermal imager. Maximum load conditions are ideal, if possible.

Point two: emissivity

Emissivity describes how well an object emits infrared energy, or heat. This affects how well a thermal imager can accurately measure the object's surface temperature. Different materials emit infrared energy in different ways.

Troubleshooting electrical systems Three-phase imbalance

Capture thermal images of all electrical panels and other highload connection points such as drives, disconnects, controls, and so on. Wherever you discover higher temperatures, follow that circuit and examine associated branches and loads. Compare all three phases side-by-side and check for temperature differences. A cooler-than-normal circuit or leg might signal a failed component. More heavily loaded phases will appear warmer. Hot conductors may be under-sized or overloaded. However, an unbalanced load, an overload, a bad connection, and harmonics can all create a similar pattern, so follow up with electrical or power quality measurements to diagnose the problem.

Connections and wiring

Look for connections that have higher temperatures than other similar connections under similar loads. That could indicate a loose, over tightened, or corroded connection with increased resistance. Connection-related hot spots usually but not always, appear warmest at the spot of resistance, cooling with distance from that spot. In some cases a cold component is abnormal due to the current being shunted away from the high-resistance connection. You may also find broken or undersized wires or defective insulation.

Fuses

If a fuse shows up hot on a thermal scan, it may be at or near its current capacity. However, not all problems are hot. A blown fuse, for example, would produce a cooler than normal temperature.

Motor control centers (MCC)

To evaluate an MCC under load, compare the relative temperatures of key components: bus bars, controllers, starters, contactors, relays, fuses, breakers, disconnects, feeders, and transformers. Incorporate the guidelines above for inspecting connections and fuses and identifying phase imbalance

Transformers

For oil-filled transformers, use a thermal imager to look at high- and low-voltage external bushing connections, cooling tubes, and cooling fans and pumps, as well as the surfaces of critical transformers. Keep in mind that like an electric motor, a transformer has a maximum operating temperature that represents the maximum allowable rise in temperature above ambient. Rely on us for all your tools & consumable needs. Update your tool box with these popular products!

DYMO XTL 300 Label **Printer Kit**

- 3-Year Limited Warranty- Maximized print area helps reduce label wast
- $\ensuremath{\mathsf{PC}}\xspace$ -connectivity* and free $\ensuremath{\mathsf{DYMO}}\xspace$ ID software for easy transfer of labels to and from the XTL 300 for iobsite editing and printing
- Durable built-in cutter for fast label production

DYMO

XTL

1228358 24mm Max Label Width

Hexagon Drive

25 Piece Socket Set 1/4 In

Extra short two component handle ratchet for ease of use in limited space

The bits fit in small plastic holders

2x3 and 1x4 bits for easy storage

Pocket sockets and bit set 1/4" with the most

popular sizes and one wobble extension bar to be flexible for different applications

46 Piece Socket Set 1/4 In **Square Drive**

- Sockets have Dynamic Drive for higher efficiency and maximum grip
- A reversible ratchet with
- quick release button
- The set includes ¼" compact spinner disc, 150 mm long flexible extension bar and 1.5 mm, 2 mm and 2.5mm hexagon wrenches



S-460

BAHCO 3581265 1/4"

Fa-430 Smoke Absorber

- · Air-purifying fume extractor realizing powerful suction with quiet operation
- Freestanding flexible ducts facilitate
- production changeovers
- Three airflow levels are selectable
 according to working environments



()HAK(O

7192109 53db, 120W

FA-430 Aus/NZ

2125 Particulate Filter

- The 3M[™] 2125 is a soft, lightweight filter pack, which is designed for use with the 6000/7500 series half face respirators and 6000/7500 series full face respirators
- They provide the user with a high protection from contaminated environments in a wide range of industrial contaminants
- With a filter type of P2, it can protect you against solid and liquid particles with effective filtration efficiency



Cr Lithium Button Batteries

- These CR batteries feature lithium chemistry, which has a high energy density
- Perfect for use with intermittent high load applications
- The self-discharge on this range of coin cells is low, giving them an excellent shelf life. Under the correct conditions, 90% of the battery storage will remain even after 10 years in storage



Panasonic

5132871 CR2032 3V, 20mm Diameter CR-2032/HFN

3M[™] Cubitron[™] li Cut-Off Wheel

- Engineered to cut faster and last longer
- than competitive ceramic products 3M Precision Shaped Grain is selfsharpening runs cool and optimises
- mineral breakdown for extra-long life Rigid reinforced resin-bonded wheel slices through almost all materials



254197 14" SL25

138 Pieces Socket Set Hexagon Drive

- The ratchet wrench comes with a
- compact sturdy soft grip handle
- Thumb slide direction lever
- 1/2", 1/4", 3/8" Hexagon drive
- Made from alloy Steel with a matt finish



BAHCO 8766180 1/4"-3/8"-1/2"



3M COW T41 125x1,6x22, 36+, PN65455

CUBITRAN

Black Mushroom Hook Tape

- Can be opened & closed hundreds of times
- Up to 12x the performance
- of standard systems
- Removes the need for mechanical fasteners • VHB[™] high strength acrylic foam tape
- backing for strong permanent bonds



4587321 25mm X 5m

nz.rs-online.com



1889482

BAHCO



Digital Depth Micrometer

- Base 100mm long x 16mm wide
- 4.5mm diameter depth rods • 0 to150mm / 0 to 6in. range
- Friction thimble

18 Piece Mechanical Screwdriver Set

- 18 piece set containing popular sizes for mechanical and general purpose environments
- Made with durable chrome-molybdenum
- and chrome-vanadium steel · Supplied in a blow moulded case

TOOLS & CONSUMABLES

Digital Level/Inclinometer

- Quick and accurate
- measurement of gradient Selectable acoustic signal
- to indicate 0° or 90°
- Hold function
- Choice of measurement units: degrees °, percentage %, or in/ft



3157834 150mm

T-handle Hex Key Set

- Ball end hex keys for almost any hex driving eventuality
- Chrome vanadium steel A strong, durable material that contributes to the long tool life
- Nylon plastic, fibre injected handles for a comfortable grip
- The hex keys are heat treated to HRC 48 52



537811 10 Piece Set

170 Piece Hss-Tin Coated Drill Set

- Ground flute
- Sizes increase in 0.5mm increments
- · Ideal for general workshop applications







4593972 18 Piece (Each)

78 Piece Mechanics Tool Kit

- 1/2in and 1/4in socket components
- Chrome Vanadium steel construction
- Sandblasted finish
- Sockets stamp with sizes for
- quick identification
- Tool storage supplied in a handy blow moulded tool box



8296568 78 Piece

Heavy Duty Ratchet Action Cable Cutter

- Pump action, heavy-duty cable cutter with a powerful double pawl ratchet jaw closure
- Relatively small physical size allows for easy access & handling compared with longer lever types with a similar cutting capacity
- Polyethylene handle grips for comfort over long periods of use
- Shears cables smoothly and efficiently

5416898 240mm Cutting Capacity







6673916 Lcd Inclinometer

¼in Air Blow Gun

· Venturi action nozzle multiplies air volume output, and makes gun completely safe, because - unlike conventional units - output air flows around the unit and not through it

- Manufactured from aluminium
- for longevity
- ¼in BSP Inlet



4885568 12bar

5-Digit Laser Tachometer

- Direct reading RPM
- Memory recall of last reading, max, min
- Reflective target tapes included
- 10-99999rpm 1mW





1238771 10-99999rpm 1mw

ELECTRONICS

Start designing the products of tomorrow, today!

Datamate L-Tek 2mm cable socket kit.

- Polarised mouldings
- High reliability connector system
- The L-Tek Datamate connectors are available with or without Latches.
- Mates with known industry equivalents



HARWIN 9094433 2mm, 6P (Pack of 2) M80-8880605

Vishay VS-26MB Series **Bridge Rectifiers**

- Universal, 3 way terminals: push-on, wrap around, or solder
- High thermal conductivity package, electrically insulated case Center hole fixing
- Excellent power/volume ratio







BDS2A100680RK



Connector

8-Way Male RJ45 Straight





High Voltage Coaxial Connector Jack

Nickel plated brass bodied 50Ω connectors with PTFE insulators and beryllium copper contacts

Designed for RF and high

voltage application

Radiall 🚺

2127400 Panel Mount, 50Ω

R316553000

Self-Contained Fibre Cleaner

• A thumb activated, spring loaded window mechanism exposes a fresh section of tape with each actuation

- Two elongated slots in the window
- allow a thorough double wipe of a connector end face
- A side window indicates how much tape is left in the cleaner





3097962 33.6 x 29.5 x 37.7mm

74271221

2119421 400 Applications





Openable Ferrite Sleeve Housing has no projecting parts Key sold separately UL94-V0 plastic case

2251272 100W ,680R

BDS100 Thick Film Power

Available in 6 configurations with 2 or 4 easy to connect terminals

Easy mounting lsotop case

 Optimum stability Space saving solution

Resistor



Rectangular Snap Fixing Cable Ferrites

- Designed to attach to cables in order to reduce electromagnetic interference from being induced or radiated
- The ferrite is housed in a hinged nylon 66 carrier, which is simply snapped around cable and is supplied with a cable tie which can be used to prevent the ferrite sliding along cable when attached to the integral retaining lug

EMI Suppression Axial Ferrite Bead

- Axial ferrite rings fit over the cable, absorbing energy emitted by cables without affecting the transmitted data
- These ferrite rings can be fixed on the cable by using heat shrink sleeving
- Attenuation is better than ferrite
 rings owing to the increased ferrite level, and is increased by threading the cable through several times

USB Field USB A receptacle

ELECTRONICS

- Sealed against fluids and dust
- Shock, vibration and traction resistant
- No cabling operation in field
- (no tools required)

 Mechanical coding/
- polarization (2 positions)
- Improved EMI protection



Richco 2224343 5-6mm dia.

Type III+ Female Crimp **Terminal Contact**

A range of Series 1 Contacts for TE Connectivity connectors





7100289	18-14AWG (Pack of 5)	66601-2
7100283	18-16AWG (Pack of 5)	66101-3

Non-Fused Terminal Block

• 48 way type F 3 row adapter with rows z, b and d loaded



2264093

	NIX TACT		
2927682	64/F 48		

22 O O





H Littelfuse

D45PK9-K

7383122	80 mA, 250 V ac/dc	0242.080UAT1
7932112	50 Ω	CA120/195-VC

nz.rs-online.com





1449783 9.5 x 4.75 x 9.5mm (Pack of 500) 74270033

ABS Angled D-sub Connector Backshell

- Nickel plated ABS hoods to UL94-V0 with conductive plastic strain relief grommet
- Meets FCC20780 and European screening requirements
- Accepts 4-12mm foil, lap or braided cable

Amphenol SOCAPEX

5369332 Male, Cable Mount

USBF TV 6 N

80mA Ceramic Cartridge **Fuse**

- Hazardous area barrier network fuses offers a range of products designed to enable greater safety when operating electronic equipment within potentially explosive environments
- Applications include electrical connections, electrical components and test equipment





Battery

Lead Acid Rechargeable

• 5 years standby design Float Standby use

• Low gas emissions 99% plus recombination

• Excellent recovery from deep discharge

Add Promo Code "MROPRO" to

receive 15% discount

EVERY PART MATTERS.

RS PRO 7 Piece VDE

• Slotted and Crosshead screwdrivers

rigorous health and safety standards VDE voltage tester included

Add Promo Code "MROPRO" to

• VDE approved tools for working in

Ergonomic soft grip handles

receive 15% discount

Screwdriver Set

RS PRO RS380 Clamp Meter

- 400 A AC Current Measurement
- 2000 Counts LCD display Auto power off
- Low battery indicator

Add Promo Code "MROPRO" to receive 15% discount





1231935 400A ac CAT III 600 V

55 Pieces Socket Set 1/4 in Square Drive

- Chrome Vanadium for excellent strength and corrosion resistance
- Soft comfortable ratchet handle for reduced fatigue and a tighter grip
- Fitted case reduces lost parts and quick identification of missing parts

Add Promo Code "MROPRO" to receive 15% discount





\$50.90 **\$43.27**

6867253 12V, 5Ah

BNC, TNC connector type

Suitable for terminating both 50 Ω and 75 Ω connector

Ratchet Crimping Tool

• Supports RG58 and RG59 wire size

Add Promo Code "MROPRO" to receive 15% discount

\$44.22 \$37.59



\$53.00 \$45.05

RS Pro French Colour Code Multi Compartment Kit

- Portable, compact and uncluttered storage in minimum space
- Contains 8 Ferrule compartments
- Plastic see-through cover
- Marked compartments, sorted by size and ease of selection

Add Promo Code "MROPRO" to receive 15% discount





8179236 Socket & Bit Ratchet Set



4730648 For BNC, TNC

\$106.80 \$90.78 2280321 0.5mm² 10mm² Wire End Ferrules \$62.20 \$52.87

30





EVERY PART MATTERS.



Socket Screws - Hex head BZP Steel

- High-quality threaded design ensures a comfortable screw into the socket
- BZP Steel as standard
- Head height is equal to shank diameter
- Cost effective, more so than stainless steel

Add Promo Code "MROPRO" to receive 15% discount

RS PRO Aluminium Tape

- Breaking load is 12N/cm
- Elongation is 5%
- Operating temperature ranges between -20°C and 110°C
- Flame retardant and self-extinguishing

Add Promo Code "MROPRO" to receive 15% discount

Cabinet Key Diecast Zinc

- Four position arm tool, offering five differing drive possibilities
- This universal cross key is made of alloy
- with excellent workmanship and durability
- Compact size, easy to carry and store, an essential tool for maintenance applications

Add Promo Code "MROPRO" to receive 15% discount



PRO

4838130 M2.5 x 12mm (Box of 100) \$110.2

\$110.24 **\$93.70**

1468961 0.07mm, W.50mm, L.45m

\$10.04 **\$8.53**

4393019 Bright Chrome Plated

\$11.97 **\$10.17**

15% OFF SELECTED RS PRO PRODUCTS!

To receive 15% discount on these selected products, please quote Promotion Code **MROPRO** in your order.



nz.rs-online.com

This offer cannot be used in conjunction with any other offer or discount. This offer is valid till the 31st of March 2020. Promotion code has to be quoted at the time of order to avail the discounted price. RS reserves right to cancel or modify the promotion at any time without prior notification.



Connect to a full range of services



With a range of flexible delivery and collection options we make it easy for you to receive your order when and where you need it.



We offer easy access to product support resources - online, by phone or your local Account Manager



With over 60,000 products stocked for next day delivery, you can focus on what matters most when time is of the essence.



eProcurement Solutions

Our experienced teams are here to help you consolidate vendors, remove complexity and reduce cost within your process.



Join our community of over half a million engineers, designers and students to access free CAD software, design tools and resources.



Stay in control of your spend & reduce your purchase to pay costs with our invoicing and payment services.

Contact us to learn more about any of our products or services.

Visit nz.rs-online.com

0800 888 780

ordersNZ@rs-components.com

