



Fall Protection

3M™ DBI-SALA® Fixed Beam Anchor



#2108406

Fixed Beam Anchor — 12 in., Model #2108406

Specifications:

- Attachment type: Clamp
- Fits I-beam flange width: 2.5 in.-12 in. (6.3 cm-30.5 cm)
- Capacity: 310 lbs. (141 kg) ANSI, 420 lbs. (190 kg) OSHA
- Size: 20 in. x 2.5 in. x 4 in.
- Weight: 5.3 lbs. (2.4 kg)
- Standards: Meets OSHA 1910.66, OSHA 1926.502, ANSI A10.32, ANSI Z359.1
- High-strength steel and aluminum construction

Fixed Beam Anchor — 18 in., Model #2108407

Specifications:

- Attachment type: Clamp
- Fits I-beam flange width: 2.5 in.-18 in. (6.3 cm-45.7 cm)
- Capacity: 310 lbs. (141 kg) ANSI, 420 lbs. (190 kg) OSHA
- Size: 20 in. x 2.5 in. x 4 in.
- Weight: 5.3 lbs. (2.4 kg)
- Standards: Meets OSHA 1910.66, OSHA 1926.502, ANSI A10.32, ANSI Z359.1
- High-strength steel and aluminum construction

3M Personal Safety Division

3M Fall Protection Business
3833 SALA Way
Red Wing, MN 55066

Technical Service: 800-328-6146
3M.com/FallProtection

3M PSD products are
for occupational use only.

© 3M 2017. All rights reserved.
3M, DBI-SALA, and Protecta are trademarks
of 3M Company and affiliates.
Used under license in Canada.
All other trademarks are property
of their respective owners.
Please recycle. Release 1, November 2017