



Eaton 5PX UPS

Enterprise class battery backup with extended runtime designed for virtualized environments

5PX features and benefits:

Extended Runtime: Add up to four extended battery modules for maximum runtime.

Virtualization-ready: Available in convenient bundles with a network card and management software for rapid integration into your virtual environment.

Efficiency: Provides industry leading efficiency of up to 99 percent.

Manageability:

- **Energy metering:** The 5PX meters energy consumption right down to the outlet segments. No other UPS in the industry offers this capability.
- **UPS management:** By integrating the Eaton Intelligent Power[®] Manager software, you can monitor and manage the power devices on your network.

LCD display: Eaton's next generation LCD offers a graphical interface which provides all critical UPS information in a single screen view.

More power: Protects more devices by providing 28 percent more wattage compared to traditional UPSs.

Battery life: Eaton's exclusive ABM[®] technology increases battery service life by 50 percent.

Intelligent Power Manager (IPM)

By integrating IPM with the Eaton 5PX, you can:

- Remotely monitor and manage multiple devices across your network from a single interface; this can be integrated into an already existing platform, such as VMware, Microsoft or Citrix
- Suspend non-critical virtual machines, consolidate critical virtual machines and shut down unused servers to extend battery runtime.
- Set server power consumption limits for extended battery runtime with UCS management software

To learn more, please visit:

Eaton.com/intelligentpower

Services and support

Eaton provides product support 24 hours a day, 7 days a week. From battery replacement to full UPS service plans, Eaton has one of the top service models in the industry.

Three-year warranty

The 5PX warranty covers both the UPS and the batteries for three years.



The Eaton 5PX is an ENERGY STAR[®] qualified UPS. ENERGY STAR is intended to help consumers save money and protect the environment through energy efficient products and practices.



5PX MODEL SELECTION GUIDE*

Catalog Number	Rating (VA / watts)	Input connection	Output receptacles	Dimensions (H x W x D), in	Net weight, lb
120V, 50/60 Hz					
5PX1000RT	1000 / 1000	5-15P	(8) 5-15R	3.4 x 17.4 x 20.6	62
5PX1500RT	1440 / 1440				65
5PX2200RT	1950 / 1920				65
5PX3000RT2U	3000 / 2700	L5-30P	(1) L5-30R (6) 5-20R	3.4 x 17.4 x 25.4	87
5PX3000RT3U					86
208V/230V, 50/60 Hz					
5PX1500iRT	1500 / 1350	C14-10A	(8) C13-10A	3.4 x 17.4 x 20.6	61
5PX2200iRT	2200 / 1980	C20-16A	(1) C19-16A		63
5PX3000iRT2U	3000 / 2700		(8) C13-10A		84
120V, 50/60 Hz Virtualization-ready bundles with Network Card-MS					
5PX1500RTN	1440 / 1440	5-15P	(8) 5-15R	3.4 x 17.4 x 20.6	65
5PX2200RTN	1950 / 1920	5-20P	(8) 5-20R	3.4 x 17.4 x 20.6	65
5PX3000RTN	3000 / 2700	L5-30P	(6) 5-20R, (1) L5-30R	3.4 x 17.4 x 25.4	87
208/230V, 50/60 Hz Virtualization-ready bundles with Network Card-MS					
5PX3000iRTN	3000 / 2700	C20	(8) C13, (1) C19	3.4 x 17.4 x 25.4	84
Extended Battery Modules					
	DC voltage	For use with	Max qty / UPS	Dimensions (H x W x D), in	Net weight, lb
5PXEBM48RT	48V	All 1000, 1500 & 2200 models	4	3.4 x 17.4 x 20.6	72
5PXEBM72RT2U	72V	All 3000 2U models		3.4 x 17.4 x 25.4	102
5PXEBM72RT3U		All 3000 3U models		5.1 x 17.4 x 19.6	98

*Due to continuous product improvement programs, all specifications are subject to change without notice. Please visit Eaton.com/5PX to view complete and updated product specifications.


Additional Options	Catalog Number	For use with
Connectivity		
Network Card-MS	NETWORK-MS	All models*
Environmental Monitoring Probe	116750224-001	All models (requires Network Card-MS)
Power Distribution & Bypass		
HotSwap Maintenance Bypass (MBP)	EHBPL1500R-PDU1U	All 1000 & 1500 models
The HotSwap Maintenance Bypass allows you to exchange or service the UPS without shutting down the connected load	EHBPL2000R-PDU1U	All 2200 models
	EHBPL3000R-PDU1U	All 3000 models
Mounting Hardware		
2-post rail kit	103007018-5591	All models

* Network Card-MS is included with catalog numbers 5PX1500RTN, 5PX2200RTN, 5PX3000RTN and 5PX3000iRTN.

What's in the box

- Tower pedestals
- Four-post rail kit
- User manual CD
- Quick start guide
- USB cable
- RS-232 serial cable
- Phillips Head screw driver
- 2 IEC to IEC jumper cables (208V/230V models)

5PX UPS rear panel (1000 & 1500 VA)



Battery runtime

You can get up to five hours of battery runtime using the internal batteries and extended battery modules. For a detailed, interactive battery runtime chart, please visit: Eaton.com/5PX (View the individual technical pages for details of each UPS.)



Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com

Eaton.com/powerquality

©2017 Eaton
All Rights Reserved
Printed in USA
5PX01FXA / GG
August 2017

To interact with the Eaton 5PX, please visit:
Eaton.com/5PX

Eaton, Intelligent Power and ABM are registered trademarks.

All other trademarks are property of their respective owners.

ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. ENERGY STAR is a registered mark owned by the U.S. government.