



Harsh Environment Safety Switch with Viewing Window

DH361UDKW

UPC:782114022696

Dimensions:

Height: 10.5 INLength: 23 INWidth: 12.5 IN

Weight:22 LB

Notes:For 2-pole applications; use outside poles of 3-pole switch. Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened.

Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

• Special Features: Upper viewing window

• Type: Single-Throw

Amperage Rating: 30AEnclosure: NEMA 12

• Enclosure Material: Painted galvanized steel

• Fuse Configuration: Non-fusible

• Number Of Poles: Three-pole

• Number Of Wires: Three-wire

• Product Category: Heavy Duty, Non-Fusible

• Voltage Rating: 600V

 Max Hp Rating: 7.5 at 480 Vac TD 1 Ph, 10 at 600 Vac TD 1 Ph, 10 at 240 Vac TD 3 Ph, 20 at 480 Vac TD 3 Ph, 30 at 600 Vac TD 3 Ph, 5 at 250 Vdc

Supporting documents:



- Eatons Volume 2-Commercial Distribution
- Eaton Specification Sheet DH361UDKW

Certifications:

• UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.