

Ferrule style high speed fuse links

FWC-16A10F

UPC:051712796453

Dimensions:

- Height: 23 MM
- Length: 38 MM
- Width: 11 MM

Weight:.006 KG

Warranties:

Not Applicable

Specifications:

- Type: FWC, Ferrule style
- Application: DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- Amperage Rating: 16A
- Voltage Rating: 700 Vac, 700 Vdc (UL)
- Interrupt Rating: 200kA ac RMS Symmetrical, 50kA at 300 Vdc
- Fuse Indicator: Non Indicating
- Packaging Type: Standard
- Used With: Finger safe holders/blocks and striker
- Pre Arc (I2T): 25
- Clearing (I2T): Clearing at Rated voltage: 150
- Diameter: 10 MM
- Material: Ceramic
- Color: White
- Class: Class aR
- Connection: Ferrule end X ferrule end
- Watt Losses: 3.5W
- Mounting: Fuse holder and blocks
- Quantity: 10
- Fuse Size: 10 X 38 mm





Supporting documents:

• 16AMP 600V AC FERRULE 10 X 38MM

Certifications:

- CSA Certified
- UL Recognized

Product compliance:

• CE Marked

© 2016 Eaton. All rights reserved.