



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Eaton 9130 UPS

PW9130L1000T-XL

UPC:790341052720

### Dimensions:

- **Height:** 9.1 IN
- **Length:** 15.1 IN
- **Width:** 6.3 IN

**Weight:**30.9 LB

**Notes:**Thermal protection switches load to bypass in case of overheating, Allows UPS operation without utility input

### Warranties:

- 2 year limited factory

### Specifications:

- **Type:** UPS
- **Topology:** Online/Double-conversion
- **Form Factor:** Tower
- **Color:** Black
- **VA Rating:** 1000 VA
- **Wattage:** 900 W
- **Package Contents:** 1 ready-to-go UPS|Software suite CD|USB cable|User guide|Quick start instructions|Cord-retention brackets
- **Efficiency:** >86% with resistive load
- **Input Connection:** 5-15P
- **Input Cord Length:** 6 ft
- **Input Nominal Voltage:** 120V default (100/110/120/127V)
- **Input Voltage Range:** 50/60 Hz
- **Nominal Frequency:** 80-144V
- **Input Frequency Range:** 45-65 Hz
- **Input Power Factor:** 0.90
- **Receptacle:** (6) 5-15R
- **Output Power Factor:** .9



- **Output Waveform:** Sine wave
- **Output Voltage Range:**  $\pm 2\%$  steady-state
- **[ETIM] Max Volt Dist Output(Linear Load):**  
<3%
- **Battery Management:** ABM technology
- **Batteries Replacement:** Hot-swappable  
internal batteries and extended battery modules  
(EBMs)
- **Battery Rating:** (3) 12V, 9 Ah
- **Battery Type:** 36 Vdc, (3) 12V, 9 Ah
- **Communication:** (1) USB, (1) RS-232 serial
- **Expansion Slots:** BD slot optional
- **User Interface:** Graphical display, 4-button  
programmable menu
- **Altitude:** 3000m
- **BTU Rating:** Online: 500, Battery: 674
- **Noise Level:** <50 dB
- **Relative Humidity:** 5-90% non-condensing
- **Temperature Range:** 0° to 40°C (32° to 104°F)

**Supporting documents:**

- [Product and Service Catalog](#)
- [Product Data Sheet - PW9130L1000T-XL](#)

**Certifications:**

- EN 55022
- cUL Listed
- UL Listed
- VCCI

**Product compliance:**

- FCC Class B