Weatherproof receptacle covers



Industrial specification grade device covers

Product description

Metal and nylon covers

Weatherproof covers for 30A, 50A & 60A straight blade receptacles

- UL Listed for wet locations (cover closed) and damp locations (cover open or closed)
- Meets 2014 NEC® 406.9 (A) and 406.9 (B)(2)
- · Self-closing spring door assures full protection
- Gasketing material provides excellent resistance to weather



(47.8mm)

3.29"Dia.





Diecast aluminum receptacle covers

Description	Catalog no.
Weatherproof lift lid cover for 4.69" (119.10mm) flush box, use box 2.125" (53.96mm) deep or larger	□ 5741NS*
Weatherproof lift lid cover for FS/FD boxes, use box 2.125" (53.96mm) deep or larger	□7420C

c(UL)us

Weatherproof covers for 50A locking devices in FS/FD boxes

Features

- UL Listed for wet locations (cover closed) and damp locations (cover open or closed)
- Meets 2014 NEC® 406.9 (A) and 406.9 (B)(2)
- · Self-closing spring door assures full protection
- Gasketing material provides excellent resistance to weather

Diecast aluminum & glass-filled nylon covers



Description	Color	Catalog no.	
Diecast aluminum lift lid cover	Diecast aluminum	□ 7770	•
Glass-filled nylon lift lid cover	Y	□ 7788CR	•
Glass-filled nylon lift lid cover	BK	□ 7788BK	•
Glass-filled nylon lift lid cover	GY	□ 7788GY	•

Weatherproof covers for power-lock devices in FS/FD boxes

Features

- UL Listed for wet locations (cover closed) and damp locations (cover open or closed)
- Meets 2014 NEC® 406.9 (A) and 406.9 (B)(2)
- · Self-closing spring door assures full protection
- Gasketing material provides excellent resistance to weather

Diecast aluminum & glass-filled nylon covers

Description	Color	Catalog no.	
Glass-filled nylon lift lid cover for 4-wire 30A receptacles	RD	□ 20446N*	•
Glass-filled nylon lift lid cover for 4-wire 30A receptacles	GY	□ 20416N	•
Lift lid cover for 4-wire 30A receptacles	Diecast aluminum	□ 20416D	•

^{*} Not CSA certified

Color information:

BK (Black), GY (Gray), RD (Red), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.





^{*} Not UL Listed