

UL Listed Raintight EMT Steel Compression Connectors & Couplings

Type 7000NSR Raintight Connectors

Use:

To ground and secure EMT raceway to boxes and enclosures in wet locations.

Features:

- UL Listed Raintight
- No disassembly required
- Male hub threads NPS
- Available with and without insulated throat
- Concretetight

Material/Finish:

- Steel Body & Nut Zinc Electroplated
- EPDM Rubber KO Sealing Ring


Third Party Certification:



UL Listed: E-14895
Listed Raintight

Applicable Third Party Standards:

UL Standard: 514B



Type 7050NSR — Type 7400NSR

Dimensions in Inches						
Trade Size (Inches)	Catalog Number	Insulated Throat Catalog Number	Body Length	Maximum Diameter	Thread Length	Weight / 100 pcs kgs (lbs)
1/2	7050NSR	7050NSRT	1.44	1.10	0.34	4.5 (10)
3/4	7075NSR	7075NSRT	1.50	1.36	0.34	6.8 (15)
1	7100NSR	7100NSRT	1.75	1.63	0.39	10.0 (22)
1-1/4	7125NSR	7125NSRT	2.00	2.07	0.40	16.3 (36)
1-1/2	7150NSR	7150NSRT	2.00	2.31	0.40	18.1 (40)
2	7200NSR	7200NSRT	2.32	2.79	0.41	24.5 (54)
2-1/2	7250NSR	7250NSRT	3.62	3.63	0.65	68.0 (150)
3	7300NSR	7300NSRT	3.75	4.29	0.65	83.9 (185)
3-3/4	7350NSR	7350NSRT	3.85	4.80	0.72	97.5 (215)
4	7400NSR	7400NSRT	3.90	5.27	0.72	108.0 (238)

Type 6000NSR Raintight Couplings

Use:

To ground and secure EMT raceway sections together in wet locations.

Features:

- UL Listed Raintight
- No disassembly required
- Concretetight

Material/Finish:

- Steel Body & Nut Zinc Electroplated


Third Party Certification:



UL Listed: E-14895
Listed Raintight

Applicable Third Party Standards:

UL Standard: 514B



Type 6050NSR — Type 6400NSR

Trade Size (Inches)	Catalog Number	Dimensions in Inches		Weight / 100 pcs kgs (lbs)
		Body Length	Maximum Diameter	
1/2	6050NSR	1.80	1.10	5.4 (12)
3/4	6075NSR	1.93	1.36	8.2 (18)
1	6100NSR	2.15	1.63	11.8 (26)
1-1/4	6125NSR	2.43	2.07	19.1 (42)
1-1/2	6150NSR	2.50	2.31	20.9 (46)
2	6200NSR	2.95	2.79	27.2 (60)
2-1/2	6250NSR	4.10	3.63	70.8 (156)
3	6300NSR	4.77	4.29	98.9 (218)
3-3/4	6350NSR	5.15	4.80	117.0 (258)
4	6400NSR	5.55	5.27	130.6 (288)