EDS Switch Covers and Sealing Chamber/Switch Assemblies

Explosionproof, Dust-Ignitionproof

Malleable Iron Body and Cover. Furnished with Internal Ground Screw.

Class I, Division 1 and 2, Groups C, D Class II, Division 1 and 2, Groups E, F, G Class III NEMA 7CD, 9EFG

Factory Assembled Switch Assembly

30 Amp, 120 lleable Iron (F31-Q ‡ (F32-Q ‡ (F33W-Q ‡	-277 Vac ^ Aluminum EDKF31-AQ ‡ EDKF32-AQ ‡ EDKF33W-AQ
(F31-Q ‡ (F32-Q ‡ (F33W-Q ‡	EDKF31-AQ ‡
(F32-Q ‡ (F33W-Q ‡ —	EDKF32-AQ ‡
(F33W-Q ‡ _	
_	EDKF33W-AQ —
_	_
(-R31-Q ‡	
C-R32-Q ‡	
C-R33W-Q ‡	
_	
_	
_	
_	
	- - -

Nameplate Mounting Bracket

Description Catalog Number



Bracket with blank silver/black nameplate for EFDB series

NPBRKT-EFDB

To order bracket with control station, add suffix -NPBRKT to end of catalog number.

To order engraved nameplates, add desired markings after catalog number. Maximum of 2 lines with 12 characters (including spaces) per line.

Note: Mount bracket between cover screws and cover. Do not mount bracket between ground joint flame path between cover and backbox.



^{◆ 20} Amp Switches 1 HP at 120 Vac and 2 HP at 240 Vac.

^{→ 30} Amp Switches 2 HP at 120 Vac or 240 Vac.

[†] Contains Factory Sealed Switch; no sealing chamber.

[‡] With sealing chamber.