

SNO*MELTER®

RESIDENTIAL AND COMMERCIAL AUTOMATIC SNOW REMOVAL

G-Mat – Sno*Melter® G-Mats are standard size snow/ice melting mats in 18-inch and 36-inch widths. They are engineered to provide 50 watts per square foot and are factory stocked in 240 Vac models only. Mats are supplied with standard 20-foot cold leads. G-Mats are UL Listed. Contact your local representative for availability of voltages up to 480 Vac.



H-Mat – H-Mats are custom sized snow/ice melting mats. They are available in outputs up to 72 watts per square foot and in voltages up to 480 Vac. H-Mats are supplied with standard 10-foot cold leads. H-Mats are UL Listed. Please contact your local EasyHeat representative for details.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
G04X36250	4' long x 36" wide mat, 600 watts, 240 Vac	1	–	0-13627-00195-4	
G04X36450	4' long x 36" wide mat, 600 watts, 480 Vac	1	–	0-13627-00198-5	
G04X36750	4' long x 36" wide mat, 600 watts, 277 Vac	1	–	0-13627-00364-4	
G04X36850	4' long x 36" wide mat, 600 watts, 208 Vac	1	–	0-13627-00285-2	
G05X18250	5' long x 18" wide mat, 375 watts, 240 Vac	1	–	0-13627-00286-9	
G05X18450	5' long x 18" wide mat, 375 watts, 480 Vac	1	–	0-13627-00356-9	
G05X18750	5' long x 18" wide mat, 375 watts, 277 Vac	1	–	0-13627-00288-3	
G05X18850	5' long x 18" wide mat, 375 watts, 480 Vac	1	–	0-13627-00294-4	
G05X36250	5' long x 36" wide mat, 750 watts, 240 Vac	1	–	0-13627-00421-4	
G05X36450	5' long x 36" wide mat, 750 watts, 480 Vac	1	–	0-13627-00422-1	
G05X36750	5' long x 36" wide mat, 750 watts, 277 Vac	1	–	0-13627-00365-1	
G05X36850	5' long x 36" wide mat, 750 watts, 480 Vac	1	–	0-13627-00423-8	
G06X18250	6' long x 18" wide mat, 450 watts, 240 Vac	1	–	0-13627-00424-5	
G06X18450	6' long x 18" wide mat, 450 watts, 480 Vac	1	–	0-13627-00357-6	
G06X18750	6' long x 18" wide mat, 450 watts, 277 Vac	1	–	0-13627-00290-6	
G06X18850	6' long x 18" wide mat, 450 watts, 208 Vac	1	–	0-13627-00425-2	
G07X18250	7' long x 18" wide mat, 525 watts, 240 Vac	1	–	0-13627-00426-9	
G07X18450	7' long x 18" wide mat, 525 watts, 480 Vac	1	–	0-13627-00358-3	
G07X18750	7' long x 18" wide mat, 525 watts, 277 Vac	1	–	0-13627-00427-6	
G07X18850	7' long x 18" wide mat, 525 watts, 208 Vac	1	–	0-13627-00161-9	
G08X18250	8' long x 18" wide mat, 600 watts, 240 Vac	1	–	0-13627-00496-2	
G08X18450	8' long x 18" wide mat, 600 watts, 480 Vac	1	–	0-13627-00359-0	
G08X18750	8' long x 18" wide mat, 600 watts, 277 Vac	1	–	0-13627-00353-8	
G08X18850	8' long x 18" wide mat, 600 watts, 208 Vac	1	–	0-13627-00273-9	
G09X18250	9' long x 18" wide mat, 675 watts, 240 Vac	1	–	0-13627-00674-4	
G09X18450	9' long x 18" wide mat, 675 watts, 480 Vac	1	–	0-13627-00741-3	
G09X18750	9' long x 18" wide mat, 675 watts, 277 Vac	1	–	0-13627-00354-5	
G09X18850	9' long x 18" wide mat, 675 watts, 208 Vac	1	–	0-13627-00289-0	
G10X18250	10' long x 18" wide mat, 750 watts, 240 Vac	1	–	0-13627-00742-0	
G10X18450	10' long x 18" wide mat, 750 watts, 480 Vac	1	–	0-13627-00360-6	
G10X18750	10' long x 18" wide mat, 750 watts, 277 Vac	1	–	0-13627-00166-4	
G10X18850	10' long x 18" wide mat, 750 watts, 208 Vac	1	–	0-13627-00747-5	
G10X36250	10' long x 36" wide mat, 1500 watts, 240 Vac	1	–	0-13627-00873-1	
G10X36450	10' long x 36" wide mat, 1500 watts, 480 Vac	1	–	0-13627-00748-2	
G10X36750	10' long x 36" wide mat, 1500 watts, 277 Vac	1	–	0-13627-00160-2	
G10X36850	10' long x 36" wide mat, 1500 watts, 480 Vac	1	–	0-13627-00874-8	
G15X18250	15' long x 18" wide mat, 1125 watts, 240 Vac	1	–	0-13627-00885-4	
G15X18450	15' long x 18" wide mat, 1125 watts, 480 Vac	1	–	0-13627-00886-1	
G15X18750	15' long x 18" wide mat, 1125 watts, 277 Vac	1	–	0-13627-00355-2	
G15X18850	15' long x 18" wide mat, 1125 watts, 208 Vac	1	–	0-13627-00887-8	
G15X36250	15' long x 36" wide mat, 2250 watts, 240 Vac	1	–	0-13627-00888-5	
G15X36450	15' long x 36" wide mat, 2250 watts, 480 Vac	1	–	0-13627-00165-7	
G15X36750	15' long x 36" wide mat, 2250 watts, 277 Vac	1	–	0-13627-00889-2	
G15X36850	15' long x 36" wide mat, 2250 watts, 208 Vac	1	–	0-13627-00207-4	
G20X18250	20' long x 18" wide mat, 1500 watts, 240 Vac	1	–	0-13627-00890-8	
G20X18450	20' long x 18" wide mat, 1500 watts, 480 Vac	1	–	0-13627-00361-3	



G-Mats Cont.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
G20X18750	20' long x 18" wide mat, 1500 watts, 277 Vac	1	—	0-13627-00891-5	
G20X18850	20' long x 18" wide mat, 1500 watts, 208 Vac	1	—	0-13627-00892-2	
G20X36250	20' long x 36" wide mat, 3000 watts, 240 Vac	1	—	0-13627-00893-9	
G20X36450	20' long x 36" wide mat, 3000 watts, 480 Vac	1	—	0-13627-00178-7	
G20X36750	20' long x 36" wide mat, 3000 watts, 277 Vac	1	—	0-13627-00894-6	
G20X36850	20' long x 36" wide mat, 3000 watts, 208 Vac	1	—	0-13627-00895-3	
G30X18250	30' long x 18" wide mat, 2250 watts, 240 Vac	1	—	0-13627-00896-0	
G30X18450	30' long x 18" wide mat, 2250 watts, 480 Vac	1	—	0-13627-00362-0	
G30X18750	30' long x 18" wide mat, 2250 watts, 277 Vac	1	—	0-13627-00897-7	
G30X18850	30' long x 18" wide mat, 2250 watts, 208 Vac	1	—	0-13627-00244-9	
G30X36250	30' long x 36" wide mat, 4500 watts, 240 Vac	1	—	0-13627-00898-4	
G30X36450	30' long x 36" wide mat, 4500 watts, 480 Vac	1	—	0-13627-00366-8	
G30X36750	30' long x 36" wide mat, 4500 watts, 277 Vac	1	—	0-13627-00899-1	
G30X36850	30' long x 36" wide mat, 4500 watts, 208 Vac	1	—	0-13627-00900-4	



Step Mat – Step Mats come standard in 2- or 3-step models. Each is available in 3-foot or 6-foot tread width with 8-inch risers. Mats are 50 watts per square foot and are supplied with 10-foot cold leads as standard. They are factory stocked in 208 Vac and 240 Vac models only. Custom step mats are available for non-standard power densities (up to 72 watts per square foot), voltage and size needs. Step Mats are UL Listed.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
2M(*)30X8	2 step, 3' x 8" tread, 200 watts	1	3	—	
2M(*)60X8	2 step, 6' x 8" tread, 400 watts	1	4	—	
3M(*)30X8	3 step, 3' x 8" tread, 300 watts	1	3	—	
3M(*)60X8	3 step, 6' x 8" tread, 600 watts	1	4	—	



(*) Insert voltage code: (8) for 208 Vac; (2), 240 Vac; (7), 277 Vac; (3), 347 Vac; (4), 480 Vac; (6), 600 Vac

Extra Length Cold Leads – Cold leads longer than standard lengths are sold either factory-spliced onto mats or cut-to-order on separate reels. Factory-spliced leads are available in 5-foot increments and the price includes both leads. Cut-to-order leads are sold by the foot. Use #14 AWG cold lead for mats under 14 amps. Use #10 AWG cold lead for mats up to 30 amps. Extra length cold leads are UL Listed and CSA Certified. Note: Most local codes require extra cold lead lengths to be factory-spliced onto mats. Check with your local inspector.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
#14AWG COLD LEAD	5' increment, factory spliced	—	—	—	
#10AWG COLD LEAD	5' increment, factory spliced	—	—	—	
#14AWG COLD LEAD	Per/ft: Cut-to-order on separate reel	—	—	—	
#10AWG COLD LEAD	Per/ft: Cut-to-order on separate reel	—	—	—	
SKDG	Splice kit: makes 3 splices	1	1	0-13627-07041-7	
NMPLT	Sno*Melter nameplate (per NEC 426-13)	1	3	0-13627-07046-2	
DT1	Detecto™ Electric Fault Indicator	1	1.0	0-13627-01296-7	CE



MI TRACE™

CONSTANT WATTAGE, PRE-TERMINATED CABLE



MI Trace™ is a fixed resistance, constant-wattage cable provided in pre-terminated lengths with factory-sealed connections. The cable is manufactured with an Alloy 825 outer sheath and normally used in high-temperature industrial applications. It is available in custom engineered lengths for 120, 208, 240, 277, 347, 480 and 600 Vac applications. MI Trace cable is UL Listed, CSA Certified, and Factory Mutual Approved for ordinary locations. Please contact your local EasyHeat representative for details.