



Catalog No. CL25A310TJ

Description: **SERIES CL-Contactor**

UPC No 801701812343

Products > Contactors > IEC Contactors > Contactor

IEC Contactors. C-2000 Nonreversing and Reversing. AC Controlled, 3-Pole. HP Ratings AC-3 Duty. 5-75 Hp (460V) Nonreversing Standard Terminals. A 1NO front mounted auxiliary contact block is supplied (unassembled) with contactors that begin with CL25 and CL45. Add suffix "S" to product number for 1NO-1NC side auxiliary (assembled). Maximum Current @ 460 V (A) AC-3: 22A. 1-Phase HP @60 Hz, 115V: 1.5. 1-Phase HP @60 Hz, 230V: 3. 3-Phase HP @60 Hz, 200V: 5. 3-Phase HP @60 Hz, 230V: 7.5. 3-Phase HP @60 Hz, 460V: 15. 3-Phase HP @60 Hz, 575V: 15. KW @ 50 Hz, 380/415V: 11.

Descriptors

Category	Contactor
GO Schedule	C2

Specifications

Contacts	1NO
Coil Voltage	110 (50 Hz) / 120 (60 Hz)

Publications

Title	Publication No.	Publication Type
C2000 CL25A310T	GEP1260-05-020	Drawings-Outline and Dimensional
GEP1260-05-020C2000 CL25A310T		

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, time current curves, CSI Specifications and promotional literature.