



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

**Search Parameters:**

[e-Catalog](#) > [Load Centers](#) > Residential Load Centers

**Load Centers, Residential Load Centers**

Product #: TM860SCUGEN

Short Description: DOUBLE MAIN GENERATOR PANEL SURFACE

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

Category	Single Phase - USA
Input/Output Voltage	120/240V ac
Type	Standard
Interrupting Capacity Rating	22
Amperage	60A
Device Type	Two Interlocked Main Breakers
Enclosure	Indoor Type 1 Enclosure, Surface Mount
UL/CUL Listing	UL
Phase	1 Phase
Socket Type	0
1" Space	8
1/2" Space	8 , 42
Feed	Top Bottom
Door	Yes
GSA Compliance	Yes
GO Schedule	137D
List Price	\$570



[View Larger](#)

**Publications/Resources**

[TM860SCUGEN](#)

**Additional Resources for Single Phase - USA**

[Ads](#)

[Application and Technical](#)

[Brochures](#)

[Catalogs and Buyers Guides](#)

[Data Sheets](#)

[Drawings-Outline and Dimensional](#)

[Installation and Instruction](#)

[BIM Files](#)

[Buy Log :1-17](#)

- Suitable for use in accordance with Article 702 of the national electrical code, ANSI/NFPA 70
- Single-phase, 2 interlock 60A or 30A main breakers, 8 circuits max.
- Safety and convenience when using a generator – 14,000 peak wattage, 11,520 continuous load, 48 amps at 240 volts.
- Maintains power to such critical circuits as those for furnace, pump, refrigerator, lights.
- Connected dual breaker mechanism ensures that only one source is active at a time