



GENESIS SERIES

Low Voltage Cable Part No. 2104

Description: 22 AWG 4/C STR CL2R, CMR, C(ETL)US FT4
Specifications: UL Standards 13 & 444, NEC Articles 725 & 800, CSA C22.2 No. 214

Construction:

Conductor 22 AWG 7/30 Stranded Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Blk, Red, Ylw, Grn
Insulation Diameter 0.042 nom.
Lay Length N/A

Jacket PVC
Jacket Thickness 0.015" nom.
Cable Diameter 0.132" nom.
Legend (Ink Print) HONEYWELL P/N 2104 4C22 3038058 (ETL) CL2R OR CMR C(ETL)US FT4 SUN RES
(RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 15 pf/ft nom.
Impedance 100 Ohms nom.
DC Resistance 16.6 Ohms/M' at 20°C
Flame Rating UL 1666 (Riser), CSA-C22.2 No. 2556 (FT4)