



GENESIS SERIES

Low Voltage Cable Part No. 2115

Description: 18 AWG 4/C STR CL2R, CMR, C(ETL)US FT4
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800, CSA C22.2 No. 214

Construction:

Conductor 18 AWG 19/0.0092" Stranded Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Blk,Red,Wht,Grn
Insulation Diameter 0.058 nom.
Lay Length 4.5" nom.

Jacket PVC
Jacket Thickness 0.015" nom.
Outside Diameter 0.170" nom.
Legend (Ink Print)

HONEYWELL P/N 2115 4C18 3038058 (ETL) CL2R OR CMR C(ETL)US FT4 SUN RES
(RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 15 pf/ft nom.
Impedance 100 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 1666 (Riser), CSA-C22.2 No. 2556 (FT4)