



GENESIS SERIES

Low Voltage Cable Part No. 2117

Description: 18 AWG 8/C STR CMR-CL2R-FT4
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

Construction:

Conductor 18 AWG 19/0.0092" Stranded Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Blk,Red,Wht,Grn,Brn,Blu,Org,Ylw
Insulation Diameter 0.058 nom.
Lay Length 6.0" nom.

Jacket PVC
Jacket Thickness 0.016" nom.
Outside Diameter 0.224" nom.
Legend (Ink Print)

HONEYWELL P/N 2117 8C18 3038058 (ETL) CL2R OR CMR C(ETL)US FT4 SUN RES
(RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 15 pf/ft nom.
Impedance 100 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 1666 (Riser), CSA FT4