



GENESIS SERIES

Low Voltage Cable Part No. 2202

Description: 22 AWG 2/C STR OAS CL2R, CMR, C(ETL)US FT4
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800, CSA C22.2 No. 214

Construction:

Conductor 22 7/.0096 Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Blk,Red
Insulation Diameter 0.042" nom.
Lay Length (Twist) 1. 5" nom.
Drain Wire 24 7/32 Tinned-Copper
Shield Alum/Mylar tape

Jacket PVC
Jacket Thickness 0.015" nom.
Outside Diameter 0.114" nom.
Legend (Ink Print) HONEYWELL P/N 2202 2C22 SHIELDED 3038058 (ETL) CL2R OR CMR C(ETL)US
FT4 SUN RES (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D
E F 1 2 3 4 5 6 7 8 9

Properties:

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 45 pf/ft nom.
Impedance 40 Ohms nom.
DC Resistance 16.5 Ohms/M' at 20°C
Flame Rating UL 1666 (Riser), CSA-C22.2 No. 2556 (FT4)