

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)


Product Datasheet

[Catalog Home](#)

[Home Page](#)

[Search](#)

1292RAC -- Grounding Bushing 3" Trade Size, 150 Degree, #14 - #1/0 Lug



Product Specifications

Family	Rigid and IMC Fittings
Fittings Classification	Grounding Bushings
Sub Class	Insulated Grounding Bushings
Trade Size	3"
Standard Packaging	Carton
Ship Carton Length	5.5
Ship Carton Width	4.5
Ship Carton Height	4.75
WT. PER HU.	60
Unit Carton Quantity	5
Ship Carton Quantity	5
UPC Number	050169012925
Product UPC-A Labeled	Yes
Catalog PDF Page	PDF Catalog Page

Applications

- For use on threaded rigid/IMC conduit to provide a means of grounding conduit through an insulated bushing

Product Features

- Lay-in lug style provides an easy means of inserting a ground wire
- Dual rated aluminum grounding lugs may be used with copper or aluminum grounding conductors

- Insuliner temperature rated at 150° C
- Malleable construction insures mechanical protection for the raceway
- Zinc electro plated for corrosion protection

Compliances

UL 514-B listed, E195975 CSA - C22.2 #18