


Sealing Washers - Steel



Catalog #: 2454

APPLICATIONS

For use whenever a positive seal is required between the shoulder of a fitting and an enclosure
One piece construction assures proper installation - no need to worry about aligning multiple components

PRODUCT FEATURES

Steel ring is zinc electro plated for added corrosion protection
Neoprene gasket
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

UL LISTED

Standard 514B, UL Listed E195973

CSA

C22.2 No. 18

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO MSDS for WP Boxes and Fittings, January 2015.pdf

GENERAL PRODUCT INFORMATION

Trade Size: 1 in.

DRAWING DIMENSIONS

Dimension A: 1-5/8 in.
Dimension B: 11/64 in.
Dimension C: 1-1/4 in.

PACKAGING

Package Type: Carton
Std. Pkg.: 25 per bag
Ship Carton Qty.: 50
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 1.60
Ship Carton Length (in.): 6.25
Ship Carton Width (in.): 4.50
Ship Carton Height (in.): 2.88
Ctn Weight (Lbs.): 0.80
UPC Number: 050169024546
I2of5: 50050169024541