CATALOG NO.	ACCOMMODATES CONDUCTOR RANGE			REFERENCE DIMENSIONS			RECOMMENDED SCREW TORQUE "INCH POUNDS"	
	WATER PIPE	REBAR	GROUND	Н	L	W	PIPE CLAMP	WIRE CLAMP
4 C-5 (JUNIOR)			10-2 STR - 10-2 STR	I.56 [40]	2.25 [56]	. 56 [   4 ]	50 LB-IN.	50 LB-IN.
C - I I N C - I I D C - I I B		#4-#8		. 8   [ 46 ]		.63 [16]		
C - 22 C - 22D C - 22B	/ 4 - 2   [ 32 - 5   ]			2.38	3.63	. 75		
C - 4	2  /2-4 [64-  4]		10-2 STR	4.13	6.25	. 96 [24]		
C - 8	4 1/2-6 [114-165]		10-2 STR	4.29	8.34 [212]	l.25 [32]		


## NOTES:

I. MATERIAL:

BODY: SOLID CAST BRONZE.

HARDWARE: STEEL, ZINC PLATED. (ACCEPT AS NOTED)

- 2. CONNECTORS ARE UL LISTED TO STANDARD UL467, GROUNDING AND BONDING EQUIPMENT. FOR INDICATED CONDUCTOR RANGE.
- 3. CONNECTORS ARE CSA CERTIFIED TO STANDARD C22.2, NO. 41, GROUNDING AND BONDING EQUIPMENT FOR INDICATED CONDUCTOR RANGE.
- 4 LOW COST, ECONOMY CONNECTOR.
- 5. CATALOG NUMBERS WITH SUFFIX "D" INDICATED THAT CONNECTORS ARE UL467 LISTED FOR DIRECT BURIAL IN EARTH AND CONCRETE, AND ARE SUPPLIED WITH SILICON BRONZE HARDWARE. (EXAMPLE: C-IID)
- 6. CATALOG NUMBERS WITH SUFFIX "B" INDICATED THAT CONNECTORS ARE SUPPLIED WITH BRASS HARDWARE. (EXAMPLE: C-IIB)
- 7. DIMENSIONS IN BRACKETS [ ] ARE IN MILLIMETERS ROUNDED TO THE NEAREST WHOLE NUMBER. UNLESS OTHERWISE NOTED, AND ARE FOR REFERENCE ONLY.
- 8 CONDUCTOR HOLE DIA. IS .31 [8].
- 9. TO ACCOMMODATE THE SMALLER WATER PIPE SIZES, SOME CONNECTORS REQUIRE THE INSTALLER TO REVERSE THE BOTTOM SADDLE PORTION OF THE PIPE CLAMPING ELEMENT.



12/11/2008 8:49:00 AM

DESCRIPTION

ECO BY C'H'K

