



CFBGFR

by Burndy Catalog ID: CFBGFR

Prop65

H-Tap Crimpit cover, Flame retardent.

- Connector end stops
- Flexible fingers
- snap tight latches
- Hinged one piece contruction

Features: One-Piece Design: No Extra Parts Or Hardware Required, Slips Over Connector And Latches Securely Shut: Fast, Easy, Reliable Insulation Of H-Tap Compression, Eliminates Tapping: Economical, Fast, Easy Installation, Flash Barriers: Protects Against Electrical Flashover, CF-FR Flame Retardant Design: Self-Extinguishing Retardant Properties, Minimum 28 Oxygen Index: Self-Extinguishing Retardant Properties, UL 94 V-O Rated: Self-Extinguishing Retardant Properties, H Tap Catalog Number: YH8C8C, YH6C6C, Color Code: Green, Orange Connector

Product Details

General

Application For O, D3, N, And KR Die Size H-Tap Compression Connectors Color Black Color Code Green Connector Type H-Tap Insulation Y Item Type 3B Material Polycarbonate Operating Temperature 90 °C Plated N Plating Type Unplated Sub Brand CRIMPIT Temperature Rating 194 Trade Name CRIMPIT** Type CF-FR, Flame Retardant UPC 781810068830 UPC 12 Digit 7818100688300		
Color Code Green Connector Type H-Tap Insulation Y Item Type 3B Material Polycarbonate Operating Temperature 90 °C Plated N Plating Type Unplated Sub Brand CRIMPIT Temperature Rating 194 Trade Name CRIMPIT™ Type CF-FR, Flame Retardant UPC 781810068830	Application	For O, D3, N, And KR Die Size H-Tap Compression Connectors
Connector Type Insulation Irsulation Item Type 3B Material Operating Temperature Plated Plating Type Unplated Sub Brand CRIMPIT Temperature Rating Type CF-FR, Flame Retardant UPC Issue AB IN Tap H-Tap Insulation I H-Tap H-Tap I H-	Color	Black
Insulation Y Item Type 3B Material Polycarbonate Operating Temperature 90 °C Plated N Plating Type Unplated Sub Brand CRIMPIT Temperature Rating 194 Trade Name CRIMPIT Type CF-FR, Flame Retardant UPC 781810068830	Color Code	Green
Item Type3BMaterialPolycarbonateOperating Temperature90 °CPlatedNPlating TypeUnplatedSub BrandCRIMPITTemperature Rating194Trade NameCRIMPIT™TypeCF-FR, Flame RetardantUPC781810068830	Connector Type	Н-Тар
MaterialPolycarbonateOperating Temperature90 °CPlatedNPlating TypeUnplatedSub BrandCRIMPITTemperature Rating194Trade NameCRIMPIT™TypeCF-FR, Flame RetardantUPC781810068830	Insulation	Y
Operating Temperature90 °CPlatedNPlating TypeUnplatedSub BrandCRIMPITTemperature Rating194Trade NameCRIMPIT™TypeCF-FR, Flame RetardantUPC781810068830	Item Type	3B
Plating Type Unplated Sub Brand CRIMPIT Temperature Rating 194 Trade Name CRIMPIT™ CRIMPIT™ CRIMPIT™ CRIMPIT™ CRIMPIT™ CRIMPIT™ CRIMPIT™ CF-FR, Flame Retardant UPC 781810068830	Material	Polycarbonate
Plating Type Sub Brand CRIMPIT Temperature Rating 194 Trade Name CRIMPIT™ CRIMPIT™ CRIMPIT™ CF-FR, Flame Retardant UPC 781810068830	Operating Temperature	90 °C
Sub BrandCRIMPITTemperature Rating194Trade NameCRIMPIT™TypeCF-FR, Flame RetardantUPC781810068830	Plated	N
Temperature Rating194Trade NameCRIMPIT™TypeCF-FR, Flame RetardantUPC781810068830	Plating Type	Unplated
Trade NameCRIMPIT™TypeCF-FR, Flame RetardantUPC781810068830	Sub Brand	CRIMPIT
Type CF-FR, Flame Retardant UPC 781810068830	Temperature Rating	194
UPC 781810068830	Trade Name	CRIMPIT™
	Туре	CF-FR, Flame Retardant
UPC 12 Digit 7818100688300	UPC	781810068830
	UPC 12 Digit	7818100688300

Dimensions

Dimension - Height inch	1.16 in
Dimension - L Length Overall mm	44 mm
Dimension - Length Overall inch	1.75 in
Dimension - Width inch	1.24 in
Thickness	0.08 in

Rating - KVA	35 kV	
Rating - Minimum Voltage	600	
Voltage - Maximum	35000	
Voltage Rating	600 V	

Conductor Related

Conductor - Co	pper Str Size	#8 AWG;#6 AWG
Conductor - Co	oper Str Size Range	#8 AWG-#6 AWG
Conductor - Ma	x Length	0.65 in

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

Logistics

Minimum Pack Quantity	
Minimum Pack Quantity	

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)