Hubbell Floor Boxes Recessed Multi-Service Concrete Floor Boxes





Nobody delivers like Hubbell Commercial Solutions

Hubbell Floor Boxes Recessed Multi-Service Concrete Floor Boxes





CFB7G Series Multi-Service Floor Box

The CFB7G series floor box is the ideal solution for today's conference and training rooms. Increasing demand for power and audio/video services creates the need for a high-capacity floor box. The CFB7G series provides flexibility to deliver a wide range of communication, active multi-media devices and power connections. CFB7 low profile covers are available in solid brass and aluminum, which provide an attractive finish for any office environment.

CFB11G Series Multi-Service Floor Box

The CFB11G series floor box is designed for maximum capacity to service Audio/Video communications and power requirements. Providing 11-gangs to populate with various services, this floor box is the ultimate in capacity and functionality. Multiple conduit knockouts allow power, voice/data and multi-media cables to be pulled separately.

CFB7G and CFB11G Series Features

- cULus 514A Listed and scrub water approved for carpet, tile and wood floors
- Attractive brass or aluminum covers with stainless steel locking studs
- 4" or 6" depth of concrete pour
- 2" trade size knockouts allow capacity for pre-terminated connectors
- · Leveling feet provide before pour adjustment
- Supplied with 11-gauge galvanized steel temporary concrete cover
- Ideal for the most demanding applications that require A/V and multi-media services
- · Accepts industry standard wallplates
- Can be used with the on-grade barrier for grade level installations, which prevents corrosion from contact with the grade
- Over 3.75" of space behind faceplates for active modules, bend radius and pre-terminated connectors

CFB8 Ballroom Series Floor Boxes

The CFB8 series of floor boxes is the ideal solutions for environments which require recessed activation with cover load ratings exceeding the UL benchmark of 300lbs. The Hubbell CFB8 Ballroom series box is an ideal solution for heavily burdened traffic areas which require an architectural finish. Our 20,000lb (with a 2x safety factor) load rating and 8 gangs of capacity make the CFB8 series ideal for heavy abuse applications such as money carts in casinos, book carts in libraries and automobiles in show rooms.

CFB8 Ballroom Series Features

- 20,000 lb cover load rating with 2x safety factor (40,000 lbs)
- 8 gangs of connectivity
- Twelve 1", 1 ¼", 1 ½" Concentric Knockouts
- · Removable device mounting plates for easy installation
- Individual or multi-gang pass throughs
- Machined aluminum covers
- cULus 514A Listed and scrub water approved for carpet, tile and wood floors
- Leveling feet provide before pour adjustment
- Accepts industry standard wallplates



Applications

Ballrooms Auto Dealerships Casinos Libraries Exhibition Centers Conference Centers







Applications Conference Rooms Commercial Environments



CFB7G Series			CFB11G Series		
Dimensions Inches (mm)					
	CFB7G4	CFB7G6	CFB11G4	CFB11G6	
Min. Depth of Pour	4.08" (103.5)	6.08" (154.3)	4.08" (103.5)	6.08" (154.3)	
Adjustability	Before Pour	Before Pour	Before Pour	Before Pour	
Dimensions: A	4.08" (103.5)	6.08" (154.3)	4.08" (103.5)	6.08" (154.3)	
В	10.0" (254.0)	10.0" (254.0)	13.5" (342.9)	13.5" (342.9)	
С	12.2" (309.9)	12.2" (309.9)	12.2" (309.9)	12.2" (309.9)	
Trade Size Knockouts: Sidewalls	(4) x 1", 1¼" concentric	(4) x 1", 1¼", 1½" concentric	(4) x 1", 1¼" concentric	(4) x 1", 1¼", 1½" con- centric	
Back	(3) x 1", 1¼", 1½" concentric; (1) x 2"	(3) x 1", 1¼", 1½" concentric; (1) 2"	 (2) ³/₄", 1" concentric; (4) 1", 1¹/₄", 1¹/₂" concentric, (1) 2" 	(2) ¾", 1" concentric; (4) 1", 1¼", 1½" concentric, (1) 2"	
Bottom	(4) x 1", 1½", 1¼" concentric	(4) x 1", 1¼", 1½" concentric	(5) 1", 1¼", 1½" concentric; (2) ¾", 1" concentric	(5) 1", 1¼", 1½" concentric; (2) ¾", 1" concentric	
Side View	X - 1.01"(25.7)	X - 2.37" (60.2)	X - 1.02" (25.9)	X - 2.37" (60.2)	
Depth behind	Y - 2.41"(61.2)	Y - 3.77" (95.8)	Y - 2.42" (61.47)	Y - 3.81" (96.8)	
mounting plate	Z - 3.51" (89.2)	Z - 3.65" (92.7)	Z - 3.50" (88.9)	Z - 3.72" (94.5)	
Accepts industry	(1) 1-gang	(1) 1-gang	(2) 1-gang	(2) 1-gang	
standard size wallplates	(1) 2-gang	(1) 2-gang	(1) 3-gang	(1) 3-gang	
(sold separately)	(1) 4-gang	(1) 4-gang	(1) 6-gang	(1) 6-gang	
Interior Configuration	1-Gang 4-Gang	2-Gang	1-Gang	3-Gang 6-Gang	

Covers

	CFB7G Series			CFB11G Series		
Solid brass and brushed aluminum edging Four (4) stainless steel locking studs secure cover closed Covers are fully removable						
for easy access into box	Brass	Aluminum	Brass	Aluminum		
Flange and cover;	1/4" edging		1/4" edging			
Beveled edge for carpet	CFB7CVRBRS	CFB7CVRALU	CFB11CVRBRS	CFB11CVRALU		
Flange and cover; Square edge for tile	1/2" edging		1/4" edging			
	CFB7TBRS	CFB7TALU	CFB11TBRS	CFB11TALU		
Note: Covers provide a recess	for floor covering insert					


Accessories

On-grade Barrier

CFBOGPAN4

The on-grade barrier is intended for use on installations at grade level. This accessory is installed prior to the concrete pour and provides a barrier between the soil. The on-grade barrier comes with leveling feet and anchor points. Can be used with other Hubbell floor boxes.

Pour Pan Dimensions: -15.75 in. sq. 4 in. depth





c Uus

Hubbell Floor Boxes **Recessed Multi-Service Concrete Floor Boxes**




Floor Boxes

FIGOL DOX		CFB8 Series				
Dimensions Inches (mm)		СРВ		A REAL PROPERTY AND A REAL		
A		CFB8FC1		CFB8FC2		
Application		Carpet		Tile, Finished Concrete		
Min. Depth of Pour		6.95" [177mm]		7.15" [182mm]		
Adjustability	•	Before Pour		Before Pour		
Dimensions A nches (mm) B C		6.95" (176.5) 15.00" (176.5) 13.00" (330.2)		7.15" (181.6) 14.75" (374.7) 12.75" (323.9)		
Trade Size Kı	nockouts:					
Sidewalls		(4) x 1.5", 1.25", 1" conce		(4) x 1.5", 1.25", 1" concentric		
Back		(4) x 1.5", 1.25", 1" concentric		(4) x 1.5", 1.25", 1" concentric		
Bottom Side View		(4) x 1.5", 1.25", 1" concentric		(4) x 1.5", 1.25", 1" concentric		
Side View Inches (mm)		X = 2.27" (57.7) Y = 4.01" (101.9) Z = 3.13" (79.5)		X = 2.27" (57.7) Y = 4.01" (101.9) Z = 3.13" (79.5)		
Accepts industry standard size wallplates (sold separately) 4.63" Maximum Cover Height		One, two, three & four gang plates. Customer configuration dependant		One, two, three & four gang plates. Customer configuration dependant		
		4-Gang		4-Gang		
Covers						
		CFB8FC1 Covers		CFB8FC2 Covers		
machined fro no additional	loor box covers are m Aluminum and have finish options	E) (3		E) (3		
Carpet Cover, with 2 egress doors (0.20" depth)		CFB8CVRALU1	—	Not Available	—	
Flush cover, with 2 egress doors		Not Available	_	CFB8CVRALU2	_	
Blank box co			CFB8JBC1		CFB8JBC2	
Cover Load F Recommende Maximum Loa	d Loading	20,000 lbs 40,000 lbs	20,000 lbs 40,000 lbs	20,000 lbs 40,000 lbs	20,000 lbs 40,000 lbs	
	arough 3" (76mm) mandrel in center of a static and don't apply to rolling loads.					
Δοτροσοι	ries					

Accessories

CFBOGPAN4 **On-grade Barrier** The on-grade barrier is intended for use on installations at grade level. This accessory is installed prior to the concrete pour and provides a barrier between the soil. The on-grade barrier comes with leveling feet and anchor points. Can be used with other Hubbell floor boxes.







www.hubbell-wiring.com www.hubbell-premise.com



Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484 • Phone (800) 288-6000 • FAX (800) 255-1031 Hubbell Premise Wiring • Hubbell Incorporated (Delaware) • 23 Clara Drive • Suite 103 • Mystic, CT 06355 • Phone (800) 626-0005 • FAX (860) 535-8328 Printed in U.S.A. Specifications subject to change without notice. Twist-Lock® and Style Line® are registered trademarks of Hubbell Incorporated. Hubbell-Pro™, ScrubShield™ and X-END™ are trademarks of Hubbell Incorporated.