

hubbell-acmeelectric.com

www.hubbell.com

208/500 - 85/100/110 208/500 Primary Volts - 85/100/110 Secondary Volts - 1Ø Industrial Control Transformer - Finger/Guard

1069



Catalog #: FS350

PRODUCT FEATURES

UL listed, CSA certified, and CE Marked

Voltage Regulation exceeds NEMA requirements

Constructed out of electrical lamination with pecision wound coils

Touch Protected terminations

Covered under Acme's 10 year limited warranty

BENEFITS

Small and lightweight design
Durable molded plastic terminals
Fast wire connection terminal

UL STANDARD

UL 506

CSA STANDARD

C22.2 No 66

WARRANTY

Acme Electric Warranty Card www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf

GENERAL PRODUCT INFORMATION

 VA:
 50

 Primary Voltage:
 208/500

 Secondary Voltage:
 85/100/110

 Frequency:
 50/60 Hz

 Max Temperature Rise:
 80°C

 UL Insulation Class:
 130°C

PRODUCT MEASUREMENTS

Height (In./cm): 3.64 (9.2) Width (In./cm): 3.75 (9.5) Depth (In./cm): 2.59 (6.6)

CONFIGURATION

Mounting Type: Floor Wiring Diagram: C

PACKAGING

Ship Weight (Lbs/Kg): 5 (2.3)

COMPLIANCES

 UL Standard:
 UL 506

 UL Listed:
 File E79947

 CSA Standard:
 C22.2 No 66

 CSA Listed:
 LR7357-16

 CE:
 CE Marked

Warranty: Acme Electric Warranty Card www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf