

Flush Furniture Feed FRPT 3-Inch Core Hole Units



Large Capacity, Single-Service Flush Furniture Feed FRPT – Two-Piece Units

Description	Catalog Number	Description	Color/Material	Catalog Number
Large Capacity, Single-Service Through Floor Fitting with (1) 2 in. E.M.T. stem. Will accommodate up to 36 Category 5e cables.	PT2FIT	Large Capacity Cover/Flange	Brass Finish Black Gray	FF2BRS FF2BK FF2GY
<p>Specifications:</p> <ul style="list-style-type: none"> UL Listed and CSA Certified. 1-2 hour fire rating. For 2¼ to 7 in. floor thickness. UL installation spacing. Minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area. Approved for use in the City of Chicago. Single-Service, Power or Data. 		<p>Specifications:</p> <ul style="list-style-type: none"> UL Listed and CSA Certified. Cover/flange with 1¼ in. and 2 in. trade size combination knockout. Painted aluminum cover and flange. Approved for use in the City of Chicago. 		FF2BK

Note: See page M-22 for technical information.

Flush Furniture Feed FRPT – One-Piece Units

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
3-Service Furniture Feed Poke-Through	Black Gray Ivory	PT73FFSDBK PT73FFSDGY PT73FFSDI	Single-Service Furniture Feed Poke-Through	Gray Ivory	PT7FFSDGY PT7FFSDI
<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> PT73SD floor fitting. Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power. Painted aluminum flange. UL Listed and CSA Certified. 		<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> PT71SD floor fitting. Aluminum cover with (1) KO to accept a ¾ in. connector. Painted aluminum flange. UL Listed and CSA Certified. 		PT7FFSDGY	

Note: See page M-23 and M-24 for technical information.

Flush Furniture Feed FRPT – Two-Piece Units

Description	Catalog Number	Description	Catalog Number
3-Service Furniture Feed Through-Floor Fitting with (1) ¾ in. E.M.T. stem for power and (2) ½ in. low voltage conduit holes.	PT73SD	Single-Service Furniture Feed Through-Floor Fitting with (1) ¾" E.M.T. stem for power or low voltage applications.	PT71SD
<p>Specifications:</p> <ul style="list-style-type: none"> UL Listed and CSA Certified. 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design). 		<p>Specifications:</p> <ul style="list-style-type: none"> UL Listed and CSA Certified. For 2¼ to 7 in. floor thickness. UL installation spacing. Minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area. 	

Service Fittings

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
3-Service Furniture Feed Service Fitting	Black Gray Ivory	FRF3BK FRF3GY FRF3I	Single-Service Furniture Feed Service Fitting	Brass Finish Black Gray	FRF1BRS FRF1BK FRF1GY
<ul style="list-style-type: none"> Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power. Painted aluminum flange. UL Listed and CSA Certified. 		<ul style="list-style-type: none"> Aluminum cover with (1) KO to accept a ¾ in. connector. Painted aluminum flange. UL Listed and CSA Certified. 		FRF3GY	FRF1GY

Note: See page M-13 for 3-inch FRPT accessories.