

Fire-Rated Poke-Throughs for Concrete Floors



2X2 Flush FRPT 3-Inch Core Hole Units

ScrubShield
Complies with UL514A



2X2 Flush FRPT – One-Piece Units


Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Poke-Through	Black	PT2X2BL	2X2 Poke-Through	Black/Brass	PT2X2BRS3
	Gray	PT2X2GY		Brass Finish/Brass	PT2X2BRS
	Black	PT2X2IGBL*		Black/Brass	PT2X2IGBRS3*
	Gray	PT2X2IGGY*		Brass Finish/Brass	PT2X2IGBRS*

<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> ■ PT2X2FIT through-floor fitting. ■ Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks. ■ Non-metallic cover. ■ Painted aluminum flange. ■ UL Listed and CSA Certified. ■ Approved for use in the City of Chicago. 	 PT2X2GY	<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> ■ PT2X2FIT through-floor fitting. ■ Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks. ■ Non-metallic cover. ■ Solid brass flange. ■ UL Listed and CSA Certified. ■ Approved for use in the City of Chicago. 	 PT2X2BRS3
---	---	--	---

Note: * Includes pre-wired 20A isolated ground duplex Style Line® receptacle.



2X2 Flush FRPT – Two-Piece Units

Description	Catalog Number
Multi-Channel Through-Floor Fitting with (1) ¼ in. E.M.T. stem with junction box for power and (2) ½ in. E.M.T. stems for low voltage.	PT2X2FIT

 PT2X2FIT	<p>Specifications:</p> <ul style="list-style-type: none"> ■ UL Listed and CSA Certified. ■ 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping (D900 Series Design)). ■ For 2¼ in. to 7 in. floor thickness. ■ UL installation spacing. Minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area. ■ Approved for use in the City of Chicago.
---	---

Service Fittings

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Service Fitting	Black	PT2X2SFBL	2X2 Service Fitting	Black/Brass	PT2X2SFBR3
	Gray	PT2X2SFGY		Brass Finish/Brass	PT2X2SFBR

<ul style="list-style-type: none"> ■ Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks. ■ Non-metallic cover. ■ Painted aluminum flange. ■ UL Listed and CSA Certified. 	 PT2X2SFBL	<ul style="list-style-type: none"> ■ Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks. ■ Non-metallic cover. ■ Solid brass flange. ■ UL Listed and CSA Certified. 	 PT2X2SFBR3
--	---	---	--

Accessories

Description	Color/Material	Catalog Number
Non-Metallic Replacement Covers	Brass Finish	PT2X2CBRS
	Black	PT2X2CBL
	Gray	PT2X2CGY

 PT2X2CBL
--

Note: See page M-13 for 3-inch closure plug.
See page M-20 for technical information.