



BURNDY Catalog Number	K3A31U2N
UPC Number	781810601150
Description	THREE:6STR-350 DUAL RATE
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Width (in)	3.52
Length (in)	4.31
Bolt Hole Size (in)	0.57
Thickness	0.31
D - in	3.16
Pad Width (in)	3.52
E - in	1.75
N (in)	0.63
General	
Number of Conductors	3
Number of Holes	2
Product Description	Aluminum Universal Terminal, 3 Conductor, 2 Hole, 6 AWG (Str)-350 kcmil, 1/2" Stud, 1.75" Stud Hole Spacing, 3 Screws, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	6 AWG-350 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	6 AWG-350 kcmil
Physical	
Installation Torque	275
Type of Plating	Tin
Connector Type	Terminal
Bolt Hole Size	9/16
Plated (Yes or No)	Y
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

47, industrial Park Drive
Manchester NH03109

47, industrial Park Drive
Manchester NH03109

Phone: 000-346-4175