

Combination Plates, 4- and 5-Gang

Description	Color	Nylon Standard	Nylon Mid-Size	Material	Metal Catalog Number
	Brown	NP38	—	Aluminum	①
	Ivory	NP38I	—	Brass	①
	Light Almond	NP38LA	—	Brass Plated	①
	White	NP38W	—	Chrome	①
				S/S 302/304	SS38
				S/S 430	—
	Black	NP326BK	—	Aluminum	①
	Brown	NP326	—	Brass	①
	Gray	NP326GY	—	Brass Plated	①
	Ivory	NP326I	—	Chrome	①
	Light Almond	NP326LA	—	S/S 302/304	SS326
	White	NP326W	—	S/S 430	—
	Black	NP2262BK	—	Aluminum	①
	Brown	NP2262	—	Brass	①
	Gray	NP2262GY	—	Brass Plated	①
	Ivory	NP2262I	—	Chrome	①
	Light Almond	NP2262LA	—	S/S 302/304	①
	White	NP2262W	—	S/S 430	—
	Brown	NP48	—	Aluminum	①
	Ivory	NP48I	—	Brass	①
	White	NP48W	—	Brass Plated	①
				Chrome	①
				S/S 302/304	①
				S/S 430	—

Note: All nylon wallplates feature pre-inserted captive screws for faster assembly, up to 6-gang.

① Available as a custom wallplate, see pages O-31 to O-34. Consult custom wallplates section for additional openings and combinations.

Specifications

Listings	
Non-Metallic Plates	UL Standard 514D.
Metallic Plates	UL Standard 514D.
Certification	UL Files #E31999,E92074. CSA Standard C22.2 No. 42.1. CSA File 1733174.

Product	Thickness	Mounting Screw(s)	Appearance
Nylon Plate	.06 in. (1.5).	Steel (painted slotted screw head).	Smooth gloss finish.
302/304 Stainless Steel Plate (18% Chromium, 8% Nickel)	.035 in. (0.9) nominal.	302/304 stainless steel (18% chromium, 8% nickel). Slotted screw head.	Horizontal brushed finish.
430 Stainless Steel Plate (17% Chromium, less than 0.5% Nickel)	.035 in. (0.9) nominal.	302/304 stainless steel (17% chromium, less than 0.5% nickel). Slotted screw head.	Horizontal brushed finish.
Brass Plate (70% Copper, 30% Zinc)	.04 in. (1.0).	Brass (70% Copper, 30% Zinc). Slotted screw head.	Horizontal brushed finish.
Aluminum Plate	.05 in. (1.3).	302/304 stainless steel (17% chromium, less than 0.5% nickel). Slotted screw head.	Horizontal brushed finish.
Brass Plated Steel Plate	.03 in. (0.8) nominal.	Brass slotted head.	Polished, coated to inhibit oxidation.
Chrome Plated Steel Plate	.03 in. (0.8) nominal.	302/304 stainless steel (17% chromium, less than 0.5% nickel). Slotted screw head.	Polished, coated to inhibit oxidation.
Steel Painted Plate	.03 in. (0.8) nominal.	Steel (painted slotted screw head).	Powder coat paint.

Note: All nylon plates include captive mount screws.

Nylon plates have an operating temperature of -40°C to 85°C.

Dimensions in Inches (mm)