



BURNDY Catalog Number
UPC Number
Description
Status

QR31
 7818103346077
 250-350 KCMIL CU. MECH.
 Active

Web Use
 BURNDY Product Line

Dimensional

Width (in)	1.25
B Length (Fraction)	1-3/16
Length (in)	2.63
Height (in)	1.69
B Length (in)	1.19
Width (Fraction)	1-1/4
Diameter (in) - Total	0.63
Length (Fraction)	2-5/8

General

Number of Screws	2
Product Description	Splice or Reducer Qiklink, 250 - 350 kcmil, 2-5/8 in L, 1-1/4 in W

Conductor(s)

Copper Solid Size (Side A) - Range	N/A
Copper Str Size(Side B) - Range	250 kcmil-350 kcmil
Copper Str Size (Side A) - Range	250 kcmil-350 kcmil
CopperSolid Size (Side B) - Range	N/A

Physical

Installation Torque	325
Type of Plating	Unplated
Connector Type	Splice,Reducer
Plated (Yes or No)	N
Product Material	Copper Alloy

Approvals / Certifications

UL Listed	Y
CSA Certified	N
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175