



Twist-Lock® Devices

Accessories

for 20 and 30 Ampere 3 Wire Receptacles and Flanged Devices



SS720

Wallplates, 1-Gang

Description	Color	Single Receptacles with Face Dia. 1.60" (40.6)
Nylon, smooth.	Black	NP720BK
Stainless steel 302/304, .035 in. (0.9), horizontal brushed finish.		SS720
Brass .04 in. (1.0), horizontal brushed finish.		SB720



HBL7425WOA

IP44
SUITABILITY**Weatherproof Plates**

Description	Single Receptacles with Face Dia. 2.15" (54.6)
Cast aluminum, for FS/FD box mounting.	HBL7420
Gray thermoplastic, for FS/FD box mounting, corrosion resistant.	HBL7425WOA
Same as above except yellow.	HBL74CM25WOA



WP2

IP44
SUITABILITY**Weatherproof Plate for Flanged Inlets and Flanged Receptacles**

Description	Catalog Number
Gray thermoplastic, corrosion resistant.	WP2

*Note: Weatherproof plates are UL Listed for wet and damp location with cover closed.
Those with suffix WOA are UL Listed with cover open.
See Section K, page K-24 for more information.*



HBL2899

Closure Cover for 3 Wire Flanged Inlets

Description	Catalog Number
Rubber closure plug.	HBL2899

Note: Closure cover not UL Listed, CSA Certified.