



BURNDY Catalog Number
UPC Number
Description
Status

YA30A6
 7818107555188
 300 AL 1-HOLE 3/8
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Dimensional

Straight
 3.90
 Standard
 Chamfered
 0.39
 Standard
 0.36
 1.53
 1.38
 1-3/4

Number of Holes

General

1
 Aluminium Tube Hylug, 1 Hole
 w/o Inspection Window, Al-300
 kcmil, Cu-300 kcmil, 600V-35kV,
 3/8" stud, Closed, Compression,
 0.44 in BCD, Blue

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Aluminum Size (Range)
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 300 kcmil
 N/A
 N/A
 300 kcmil

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin - Electro Plated
 3/8
 Blue
 Y
 470
 Aluminum

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Y
 Y
 Compliant
 N
 N
 UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175