



A.



B.



C.



D.

## PB800 and PB900 Series Mechanical Panel Mount Timers



- Automated control for pumps, cleaners, and other types of loads
- 3 different mounting methods
- Quick connect terminals for easy installation

Model #	Switch	Dial	Input Voltage	No. of Trippers	Manual Override
A. <b>PB873MKZ</b>	SPST	7-Day	120 VAC, 60 Hz	56	No
<b>PB913N</b>	SPST	24-Hour	120 VAC, 60 Hz	48	No
B. <b>PB914N</b>	SPST	24-Hour	208-277 VAC, 60 Hz	48	No
<b>PB913N66</b>	SPST	24-Hour	120 VAC, 60 Hz	48	Yes
C. <b>PB914N66</b>	SPST	24-Hour	208-277 VAC, 60 Hz	48	Yes
<b>PB913N84</b>	SPST	24-Hour	120 VAC, 60 Hz	4	Yes
D. <b>PB914N84</b>	SPST	24-Hour	208-277 VAC, 60 Hz	4	Yes

For replacement parts, trippers and accessories, see page 153.

### Rating:

#### Switch Rating:

20 A Resistive, 120-277 VAC  
1250 W Tungsten 125 VAC  
1 HP (16 FLA), 120 VAC  
2 HP (12 FLA), 240 VAC  
360 VA Pilot Duty, 120-240 VAC

**Timing Cycle:** 24-Hour – minimum ON time 1 hour, maximum ON time 23 hours, 30-minute intervals  
7-Day – minimum ON time 6 hours, maximum ON time 162 hours, 3-hour intervals

**Quick Connect Terminals:** (4) ¼" male (2) for load and (2) for independent clock motor

**Dimensions:** 3 ½" (84.8 cm) H x 2 ½" (17.4 cm) W x 1 ⅝" (49.6 cm) D

**Warranty:** 1 year