

SNAP-IN LAMPHOLDERS

Porcelain • Phenolic

Medium Base E26



INCANDESCENT

U-Clip Snap-In Sockets

One-piece phenolic sockets, with or without vulcanized fiber cover riveted to body. Rust-resistant spring steel clip. Standard leads are No. 18 AWG 105°C AWM-TEW plastic insulated wire, 6" long, stripped 3/4".

Available with ground lead on request.

Standard pack: bulk

• 660W-250V • UL Listed E-3810 • CSA Certified LR-1863 • NOM Certified 057

Cat. No.	Description	Fiber Cover
2553*	U-Clip Snap-in Socket	No
2553-200	U-Clip Snap-in Socket, shallow mounted	No

*Also available with fiber cover on special request.



2553

Porcelain Snap-In Socket

White unglazed porcelain. Copper alloy, nickel-plated screw shell. Rust-resistant, spring-tempered steel clip. Standard leads are No. 18 ga. 105°C AWM-TEW plastic insulated wire, 9" long, stripped 3/4". Other wire types available.


Standard pack: bulk

Cat. No. 8064


• 660W-250V • UL Listed E-3810 • CSA Certified LR-1863 • NOM Certified 057



2553-200




Cat. No. 2553




Cat. No. 2553-200

PANEL THICKNESS
0.015-0.031 (0.38-0.79)




SUGGESTED
PANEL OPENING

U-CLIP SNAP-IN SOCKETS



Cat. No. 8064

PANEL THICKNESS 0.055-0.070 (1.40-1.78)



SUGGESTED PANEL OPENING



8064

PORCELAIN SNAP-IN