

Commercial Grade

"Smart" CFL Lampholders

Specifications and Features

- "Smart" CFL Lampholders are color-coded for easy wattage identification
- Bottm Snap-in versions for easier panel assembly available for 16 Ga. and 18-20 Ga. panels
- All 4-pin lampholders have internal rejection feature that prevents insertion of 2-pin lamps
- Metal-spring lamp-retainer clip provides positive lamp retention and is more durable than plastic clips
- Two wiring ports per contact speed harness wiring
- Wire-routing options for top or bottom side of mounting panel for easier assembly
- Bodies are white thermoplastic (with color-coding as indicated)
- Quick-connect push-in wiring terminals accept No. 18 AWG solid or twisted-and-overtinned leads, stripped 3/8 inch

10MM COMPACT FLUORESENT LAMPOHOLDERS WITH ROUND BODIES & 6.

For G24d Lamp Bases, 2-Pin

Rating	Color	Cat. No.	Lamp Base	Wattage		
75W 600V	Black	26725-2A1	G24d-1	10W/13W		
75W 600V	Green	26725-2A2	G24d-2	18W		
75W 600V	Orange	26725-2A3	G24d-3	26W		



26725-4A2

For G24q and GX24q Lamp Bases, 4-Pin - Bottom Screw Down Mounting

Rating	Color	Cat. No.	Lamp Base	Wattage
75W 600V	Black	26725-4A1	G24q-1	10W/13W
75W 600V	Green	26725-4A2	G24q-2 GX24q-2	18W
75W 600V	Orange	26725-4A3	G24q-3 GX24q-3	26W
75W 600V	Yellow	26725-4A4	G24q-4	26W/32W
75W 600V	Blue	26725-4A5	G24q-5	42W
75W 600V	Red	26725-4A6	G24q-6	42W
75W 600V	White Body Only	26725-4A9 Universal*	G24q-3 GX24q-4	26W/32W/42W



26725-4A3



26725-406

Twist-in Socket For G24g and GX24g Lamp Bases, 4-Pin

TWISE IN COCKET OF CLE IN GIVE IN LAMP BUSCS, I'I III						
Rating	Color	Cat. No.	Lamp Base	Wattage		
120W, 600V	White Body with Black	26800-4A1	G24q-1 GX24q-1	13W		
120W, 600V	White Body with Green	26800-4A2	G24q-2 GX24q-2	18W		
120W, 600V	White Body only	26800-4A9 Universal*	G24q-3 GX24q-4	26W / 32W / 42W		
120W,600V	White Body with Purple	26800-4A8 Universal	GX24q-5 GX24q-6	57W / 70W		

