

## 430MI9WLEVS

30 Amp Mechanical Interlock with Local Monitoring Inform™ Technology – LEV Series

30 Amp, 240 Volt 3-Phase, 3P, 4W, LEV Series North American-Rated IEC 60309-1 & 60309-2 Pin & Sleeve Mechanical Interlock with Local Monitoring, Industrial Grade, IP66/IP67/IP68/IP69/IP69K, Watertight, Non-Fused – Blue (240 VAC)



UPC Code : 078477380857

Country Of Origin : Mexico

- Inform technology identifies disturbances that can impact machine performance and minimize unplanned downtime by monitoring line- and load-side voltage, liquid accumulation inside the enclosure, ground continuity and welded contacts
- Green LEDs on the cover provide a visual indication that the device is operating under normal conditions, flash red if there is a failure, or flash yellow if there is a buildup of liquid inside of the enclosure that may lead to a potential failure

If using a variable frequency drive (VFD), it must be installed between the mechanical interlock switch and the motor.

[Click here to learn more about our full line of LEV Series IEC 60309 devices.](#)

[Click here to learn more about Inform Technology.](#)

### Technical Information

#### Electrical Specifications

**Amperage** : 30 A

**Current Interrupting** : Certified for current interrupting at full-rated current and voltage

**Dielectric Voltage** : 2200V for 1 minute

**Endurance** : 6,000 cycles under load

**Horsepower Rating** : 10 HP

**Phase** : 3-Phase

**Pole** : 3

**SCCR** : 10kA

**Voltage** : 240 VAC

**Wire** : 4

#### Environmental Specifications

**Flammability** : Rated V-0 per UL 94

**Gasket Aging** : 70°C for 168 hr per UL50E

**IP Rating** : IP66, IP67, IP68, IP69, IP69K

**NEMA Rating** : 3R, 4X, 12

**NSF** : 14159-1, Hygienic Requirement for the Design of Meat & Poultry Processing Equipment

**Operating Temperature** : -40°C to 75°C

**UV Resistance** : UV stabilized F1 rated enclosure

#### Material Specifications

**Contact Material** : Nickel-Plated Brass

**Gasket Material** : Chloroprene

**Handle Material** : PBT+PC with TPE Overmold

**Housing Material** : PBT+PC

**Housing Screws** : 303 Stainless Steel

#### Mechanical Specifications

**Cold Impact** : 5 ft-lb impact at -31°F for 3 hrs per UL746C

**Crush Test** : 100 lbs for 1 minute per surface

**Mold Stress Relief** : 70°C for 7 hours without deformation

#### Product Features

**Color** : Blue

**Configuration** : North American

**Device Type** : Non-Fused Mechanical Interlock

**Feature** : LED Indication

**Series** : LEV Series

#### Standards & Certifications

**CSA** : C22.2 No 94.1-07

**IEC Rating** : IEC 60309-1, 60309-2, 60309-4

**UL** : UL231, UL1682, UL1686, UL50, UL50E, UL60947-4-1, UL60947-1, UL746

#### Warranty

**Warranty** : 5-Year Limited

## Features and Benefits

### SAFETY BENEFITS

- Mechanically interlocked receptacle prevents connecting or disconnecting plugs under load
- High visibility LEDs provide visual confirmation of power being delivered to or removed from connected equipment (minimum 10 year LED lifespan)
- Equipment ground monitoring reduces shock hazard by validating the integrity of the ground connection

### SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

